imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



HIS COPY IS PROVIDED O	N A RESTRICTED BASIS AND IS NOT TO BE	ISED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.	
Ma te ria l	HighConductivity SeamlessCopperTube	Tongue also stamped with:	
Plating	Ele c tro - Tin	4/0 SIR/ FLEX IC AX4/0-14H43 R REF	
Wire Size	4/0 SIR/ FLEX		
Wire Type	Stranded Copper: Class B & C, Compact, Class G, H, I, K, M, Locomotive		
Wire Strip Length	1-1/16 in.		
Stud Size	1/4 in.		
UL Liste d Wire Connector	Yes, for a pplic ations up to 35kv. Consult cable manufacturer for voltage stress relief instructions with a pplic ations greater than 2000 volts.	.35±.04 .27±.02 DIA	
UL Temperature Rating	90 ° C		
C.S.A Certified Wire Connector	Ye s	Beveled wire entry .81±.01	
Panduit Color Code on Bamel	PURPLE	1.03±.04	
Panduit Die Index No on Bamel	p. P54		
Alternate Industry Die Index No.() on Barrel	(15)	Wire inspection window 1.80 REF	
		45°±5°	
C ERTIFI	ED LISTED Wire Connector	.16±.01 2.03 REF	
		CORP. TINLEY PARK, ILLINO IS	
		LCAX4/0-14H-X CopperLug - One-Hole, Standard Flex Barrel, 45° Angle Tongue	
0 1/08 JHNU LEN			
EV DATE BY CH	DESCRIPT	$\begin{array}{c c c c c c c c c c c c c c c c c c c $	