imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



		ROVID	ED ON	A RESTRICTED BASIS AND IS NOT TO BE U	SED IN ANY WAY DETRIMENTAL T	O THE INT	ERESTS OF PANDUIT CORP.	
Ma	te ria l			High Conductivity Seamless CopperTube	_			
Plat	ting			Ele c tro -Tin				
Wire Size				8 SIR/ FLEX		Wine inspection window		
Wire Type				Stranded Copper. Class B & C Compact, Class G, H, I, K, M, Locomotive		window .20±.02 DIA		
Wire Strip Length		1	3/4 in.					
Stud Size			# 10	.23±.04				
UL Liste d Wire Connector				Yes, for a p p lic ations up to 35kv. Consult c a b le manufacturer for voltage stress re lief instructions with a p p lic ations g reater than 2000 volts.	53:	•53±.04	1.03 REF .70±.04 PANDUIT RED DIE P21	
UL Temperature Rating			90 ° C					
C.S.A Certified Wire Connector			Ye s		•			
Panduit Color Code on Bamel		ode	RED	.08±.01 —	90°±5°			
Panduit Die Index No. on Bamel		ex No.	P21					
Altemate Industry Die Index No.() on Banel				N/ A				
C ERTIFIED				B USIED Wire Connector		.18±.01 – 7±.01 – – .90 REF	Be ve le d wire entry E	
							ANDUIT CORP. TINLEY PARK, ILLINO B	
							LC BX8-10F-L CopperLug - One-Hole, Long Flex Barrel, 90° Angle Tongue	
0 6/03 SAC				RELEASED		10850	SCALE DRAWING NO / CAD FILE	
V	DATE	BY	СНК	DESCRIPT	ION	ECN	N/A IC BX8-10F-C UST	