imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



| THIS COPY IS PRO | VIDED ON | A RESTRICTED BASIS AND IS NOT TO BE U | SED IN ANY WAY DETRIMENTA | L TO TI | | ERESTS OF PANDUIT CORP. |
|--|----------|--|--|---------|---------|---|
| Material | | High Conductivity Seamless Copper Tube | | | | |
| Plating | | Electro-Tin | | | | |
| Wire Size | | 4/0 AWG | | | | 63 R Ref |
| Wire Type | | Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric | | | | Color coded barrel markings |
| Wire Strip Length | | 1-5/8 in. | 1.06±.04 | str cu | 24/0-12 | |
| Stud Size | | 1/2 in. | Powere die per edit contract of the second s | | | |
| UL Listed Wire Connector | | Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts. | .63±.04 | - 1.75 | ±.02 - | .53±.02 DIA (2) PLS |
| UL Temperature Rating | | 90° C | | | | — 5.13±.06 — |
| C.S.A Certified Wire Connector | | Yes | | | | |
| Panduit Color Code on Barrel | | PURPLE | | | | |
| Panduit Die Index No. on Barrel | | P54 | | | | ◄── 1.56±.04 ──► Beveled wire entry |
| Alternate Industry Die Index No. () on Barrel | | (15) | | | | .57±.01 .71±.01 |
| | CERTIFIE | B D LISTED Wire Connector | .14±.01 | | | |
| | | | | | | CORP. TINLEY PARK, ILLINOIS |
| | | | | | | LCC4/0-12-X Copper Lug - Two-Hole, Long Barrel |
| | NU JHNU | | N10883DF-LCC4/0-12-CUST | | RGB | |
| EV DATE B | BY CHK | DESCRIPTION | ECN | -R | SUP | SCALE N/A DRAWING NO / CAD FILE LCC4_0-12-CUST |