mail

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Material	High Conductivity Seamless Copper Tube	
Plating	Electro-Tin	
Wire Size & Type	Stranded Copper Flex Cable; 373.7 kcmil (925/24) Diesel Locomotive, 350 kcmil Class K & Class M	1.53±.04
Wire Strip Length	2-9/16 in.	
Stud Size	3/8 in.	
UL Listed Wire Connector	Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.	.38±.04 1.00±.02
UL Temperature Rating	90° C	
C.S.A Certified Wire Connector	Yes	
Panduit Color Code on Barrel	BLUE	
Panduit Die Index No. on Barrel	P76	
Alternate Industry Die Index No. () on Barrel	(19)	



11/16 JHNU JHNU

SAB DRL

BY CHK

9/02

REV DATE

01

00

CERTIFIED

J					SCALE		
J		RELEASED		10336	Copper Lug - Two-Hole, Flared Long Barrel SCALE DRAWING NO / CAD FILE		
	RGB	GB REVISED I.D. TOLERANCE: ±.03 WAS ±.01		N10881MX- LCCF350-38D-CUST		LCCF350-3	8D-6
_							TINLEY PARK, ILLINOIS
>		USTED Wire Connector	.22±.01 –				
	(19)					777	
	P76					<u></u>	.84±.03 1.22±.05
	BLUE				-	← 2.50±.04 —	
	Yes				1		Flared wire
	90° (C					
	volto with	for applications up to 35kv. sult cable manufacturer for age stress relief instructions applications greater than volts.	.38±.0	04	02 - 5.18±	41±.02 DIA (2) PLS .06	
	3/8 ii	n.					
	2-9/1	l 6 in.	1.00±.0	PAND 925/12 373.7 K	CO COL	PANDUIT BLUE DIE P76 (19)	
		s K & Class M	1.53±.0			DO	

- Color coded barrel markings

- .44 R Ref