imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



| HIS COPY IS PROVIDED | ON A RESTRICTED BASIS AND IS NOT TO BE | USED IN ANY WAY DETRIMENTAL TO | | ERESTS OF PANDUIT CORP. |
|--|--|---|---------------------------|--|
| Ma te ria l | High Conductivity Seamless Copper Tube | | | |
| Plating | Ele c tro - Tin | | | |
| Wire Size | 4 STR/ FLEX (ALL),3 & 5 FLEX* | | | |
| Wire Type | Stranded Copper. Class B& C Compact, Class G, H, I, K, M, Locomotive (*Locomotive only) | .48 R REF Color coded barrel markings | | |
| Wire Strip Length | 1-1/8 in. | | КИ Х4-3 | |
| Stud Size | 3/8 in. | | 4 STR/FIEX LC C X4-38D | |
| UL Liste d Wire Connector | Yes, for a p plic ations up to 35kv. Consult c able manufacturer for voltage stress relief instructions with a p plic ations g reater than 2000 volts. | |)±.02 — | .41±.02 DIA (2) PIS |
| UL Temperature Rating | 90 ° C | - 3.09±.06 | | |
| C.S.A Certified Wire Connector | Ye s | _ | | |
| Panduit Color Code on BamelGRAYPanduit Die Index No. on BamelP29 | | | | |
| | | $- 1.05 \pm .04 - Be ve le d wire entry$ | | |
| Altemate Industry Die Index No.() on Banel | (8) | Wire inspection window | | |
| CERT | B B B B B B B B B B B B B B | | | |
| | | | | CORP. TINLEY PARK, ILLINO K |
| | | | 10410 | LCCX4-38D-L CopperLug - Two-Hole, Long Flex Bamel with Window |
| 3 1/05 JHNUTLA EV DATE BY CI | PANDUIT REPIACED WIRE RANGE ON BARREL MARKING DESCRIPTION | | 12412 ECN | SCALE DRAWING NO / CAD FILE |
| | DESCRIP | | EUN | N/A ICCX4-38D-CUST |