## imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Μ	a te ria l			High Conductivity Seamless CopperTube						
Pl	a ting			Ele c tro - Tin						
W	'ire Size			4 SIR/ FLEX			38DF		-Wire inspection window	
Wire Type				Stranded Copper. Class B & C Compact, Class G, H, I, K, M, Sizes 3, 4 & 5 Locomotive	.62±.04	PANDUIT PANDUIT 4 STR FILS 15 CX4-38DF				
W	Wire Strip Length			1-1/8 in.	.36±.04 –	<b></b> 1 (	$00\pm.02$ —	.41±.02 DIA (2) PIS		
Stud Size			3/8 in.			001.02				
	L Liste d V onne c to			Yes, for a p p lic ations up to 35kv. Consult c able manufacturer for voltage stress relief instructions with a p p lic ations g reater than 2000 volts.						
UL Temperature Rating				90 ° C						
C.S.A Certified Wire Connector Panduit Color Code on Barrel Panduit Die Index No. on Barrel			Ye s	← 1.84±.04 ←						
		de	GRAY	.08±.01		t l				
		x No .	P29			90°	±5°		PANDUIT	
Altemate Industry Die Index No.() on Banel			y	(8)				1.05	±.04	GRAY DEE P29 (4)
		CI		© USIED Wire Connector			2.34	.38±.01	Beveled wire entry	Cobrcoded banelmankings
		1 1					1			
_									CORP.	TINLEY PARK, ILLINO I
									LCCX4-38DF-	
3	1/05 JHNUTICO PANDUIT REPLACED WIRE RANGE ON			PANDUIT REPLACED WIRE RANGE ON BARRE			12412			
٤V	DATE	BY	СНК	DESCRIPT	ION		ECN	SCALE N/A	DRAWING NO / CAD F	LC C X4-38DF-C UST