imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



00 EV	6/03 SAC SAC DATE BY CHK			D	10850 ECN	ICCX8-14BF-L CopperLug - Two-Hole, Long Flex Banel with Window, 90° Angle Tongu SCALE DRAWING NO / CAD FILE	
							CORP. TINLEY PARK, ILLINO
		c	ERIIFI	B Connector	۹		.18±.01 .27±.01 - 1.74 REF - 1.74 REF - 1.74 REF
Altemate Industry Die Index No.() on Banel				N/A			
Panduit Die Index No. on Bamel		ex No.	P21		90°±5° 1.02 REF .70±.04 PANDUII		
Panduit Color Code on Banel			ode	RED	.07±.01		
C.S.A Certified Wire Connector				Ye s			
UL Temperature Rating			90 ° C]	 1.37±	±.04	
	L Liste d V o nne c to			Yes, for a p p lic ations up to 35kv. Consult c able manufacturer for voltage stress relief instructions with a p p lic ations g reater than 2000 volts.			
Stud Size				1/4 in.	.25±.04	.75±	$ \begin{array}{c}02 \\ \hline \\ (2) \\ PIS \end{array} $
W	'ire Strip I	Lengtł	ı	3/4 in.			
Wire Type				Stranded Copper. Class B & C Compact, Class G, H, I, K, M, Locomotive	.48±.04		Wire inspection window
Wire Size				8 SIR/ FLEX			
Pl	a ting			Ele c tro -Tin			
141	a te ria l			High Conductivity Seamless Copper Tube			