

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







									LCD8-1،	
										P. TINLEY PARK, ILLING
						-	1.	.99 REF		
		С	ERTIFIE	ED LISTED Wire Connector				.27±.01 -		barrel markings led wire ntry
								.18±.01 -		Color coded
Alternate Industry Die Index No. ( ) on Barrel			У	N/A					.56±.04	PANDUIT RED DIE P21
Panduit Die Index No. on Barrel				P21	.07±.01			90°±5° .89		
Panduit Color Code on Barrel			ode	RED	<u></u> ↓	4 - 1.00±.02		4		
C.S.A Certified Wire Connector				Yes			— 1.62±.04			
UL Temperature Rating				90°C						
UL Listed Wire Connector				Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.	.201.04		1.00±.02		— .2/±.02 DIA (2) PLS	
Stud Size				1/4 in.			- 1 00+ 02		— 27+ 02 DIA	27±.02 DIA
Wire Strip Length			۱	5/8 in.	<b></b>			1		
Wire Type				Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric	.48±.04			window		
W	'ire Size			8 AWG					W	ire inspection
Ρl	ating			Electro-Tin						
	aterial			High Conductivity Seamless Copper Tube						