

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China








Material	High Conductivity Seamless Copper Tube		
Plating	Electro-Tin		
Wire Size	1 STR/FLEX		
Wire Type	Stranded Copper: Class B & C, Compact, Class G, H, I, K, M, Locomotive	.76±.04 ANDUIT	
Wire Strip Length	3/4 in.		
Stud Size	5/16 in.	.32±.04 - 1.00±.02 - (2)	±.02 E PLS
UL Listed Wire Connector	Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.		
UL Temperature Rating	90° C		
C.S.A Certified Wire Connector	Yes	1.76±.04	
Panduit Color Code on Barrel	GREEN		
Panduit Die Index No. on Barrel	P37	.12±.01	<u> </u>
Alternate Industry Die Index No. () on Barrel	(11)	90°±5°	.6
(F)	® (U)	.39±.01	-

LISTED Wire Connector

CERTIFIED



-Wire inspection window

						PANDUIT CORP. TINLEY PARK, ILLINOIS
						LCDX1-56DF-X
00	6/03	SAC	SAC	RELEASED	10850	Copper Lug - Two-Hole, Standard Flex Barrel, 90° Angle Tongue
REV	DATE	BY	СНК	DESCRIPTION	ECN	SCALE DRAWING NO / CAD FILE LCDX1-56DF-CUST