



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832


Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



ALL DIMENSIONS ARE IN mm

Part Number	Class 2R Wire Size	Stud Size	Wire Strip Length	Current Rating	Panduit Die Index No. for Class 2R Wire	l ±2.76	o ±.50	i ±.50	a ±2.25	m (ref)	c ±.50	e ±.50	n ±2.25	d ±.50	b ±2.25	t
*LCMD6-5CD-Q	4-6 mm ²	M5	11.0	30A	P10	52.5	5.50	3.80	9.5	7.8	22.00	25.00	6.2	5.50	10.0	1.17±.30
LCMD10-6CD-Q	10 mm ²	M6	12.5	-----	P21	55.8	6.20	4.50	11.0	9.8	22.00	25.00	6.0	6.60	11.0	1.20±.35
*LCMD16-6CD-Q	16 mm ²	M6	16.0	65A	P24	59.5	7.20	5.50	14.5	10.3	22.00	25.00	6.5	6.60	13.0	1.26±.40
LCMD25-8CD-Q	25 mm ²	M8	16.5	-----	P29	62.0	8.80	6.90	15.0	10.0	22.00	25.00	8.0	9.00	15.5	1.60±.40
LCMD35-8CD-Q	35 mm ²	M8	19.0	-----	P29	67.0	10.40	8.20	17.5	12.3	22.00	25.00	8.5	9.00	15.5	2.05±.40
LCMD50-10CD-X	50 mm ²	M10	21.8	-----	P37	71.5	12.30	9.80	20.3	11.5	22.00	25.00	10.0	11.00	18.0	2.50±.40
LCMD70-10CD-X	70 mm ²	M10	24.8	-----	P45	78.5	14.20	11.50	23.3	14.5	22.00	25.00	11.0	11.00	20.5	2.85±.40
LCMD95-10CD-X	95 mm ²	M10	26.0	-----	P54	85.5	16.50	13.50	24.5	15.0	22.00	25.00	13.0	11.00	24.5	3.05±.40
LCMD120-10CD-X	120 mm ²	M10	26.0	-----	P62	90.0	18.60	15.20	24.5	15.5	22.00	25.00	14.0	11.00	27.5	3.50±.45
LCMD150-10CD-X	150 mm ²	M10	29.0	-----	P66	95.5	21.00	16.50	27.5	18.0	22.00	25.00	16.0	11.00	30.5	4.45±.45
LCMD185-10CD-X	185 mm ²	M10	29.7	-----	P76	97.5	23.00	18.60	28.2	16.5	22.00	25.00	17.0	11.00	33.5	4.55±.50
LCMD240-10CD-5	240 mm ²	M10	36.5	-----	P87	111.5	26.00	20.80	35.0	21.0	22.00	25.00	19.0	11.00	37.5	5.30±.50



- NOTES:
1. Material: High conductivity seamless copper tube.
 2. Plating: Parts are tin plated.
 3. Wire Type: Class 2R Stranded Copper.
 4. UL Listed or *Recognized Wire Connector: Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.
 5. UL Temperature Rating: 90°C
 6. C.S.A. Certified Wire Connector: Yes



				N10637BI-C41693			FLD	FLD	PANDUIT CORP. TINLEY PARK, ILLINOIS	
									METRIC LUGS - SLOTTED LCMD SERIES 6-240mm ²	
									CUSTOMER DRAWING	
02	9/10	TLCO	TLCO	ADDED .76mm TO TOLERANCE l. ADDED .25mm TO TOLERANCES a, c, e, n, d, b. ADDED .15mm TO TOLERANCE t.				UNLESS OTHERWISE SPECIFIED DIMENSIONAL TOLERANCES ARE: (.X) ± (.XXX) ± (.XX) ± ANGLES ±		UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN INCHES, THIRD ANGLE PROJECTION
01	2/08	JHNU	TLCO	REMOVED CLASS 5F WIRE SIZES AND DIE INDEX NUMBERS. ADDED UL RECOGNIZED TO NOTE 4 ALONG WITH RECOGNIZED LOGO & CURRENT RATING COLUMN. CHANGED DIE INDEX NUMBERS: P33 TO P29 & P42 TO P37.				DRAWN BY PWSc	MAT'L:	SCALE NONE
00	1/07	PWS	PWS	DRAWING RELEASED		PC00643	DATE 1/07	SEE NOTES ABOVE	DRAWING NO / CAD FILE	DWG B SIZE
REV	DATE	BY	CHK	DESCRIPTION		ECN	-R	SUP	CHK'D PWSc	C41693_02