# mail

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





## Quartz Crystal Specification Part No. + Packaging: LFXTAL003164Bulk

#### Description

- Industry standard leaded package Resistance welded, hermetically sealed in an inert atmosphere, glass to metal seals on leads
- Standard 2 leg HC49 package
- Model HC49Model Issue number 15

#### **Frequency Parameters**

	· · · ·	
	Frequency	10.0MHz
•	Frequency Tolerance	±20.00ppm
	Frequency Stability	±50.00ppm
	Operating Temperature Range	-10.00 to 60.00°C
	Overtone Order	Fundamental
	Ageing	±3ppm typical per year
	Electrical Parameters	

- Load Capacitance 30.00pF
   Shunt Capacitance 7pF max
   Drive Level 4100 (2000)
- Drive Level
   1mW max

   ESR
   35.00Ω max

### **Environmental Parameters**

- Shock: 981m/s<sup>2</sup>, 6ms, 3 times in each of 3 mutually perpendicular planes
- Vibration: 10Hz-60Hz, 0.75mm amplitude, 60Hz-500Hz, 98.1m/s<sup>2</sup>, 30mins in 3 mutually perpendicular planes
- Storage Temperature Range: -55 to 125°C

#### Compliance


RoHS Status (2011/65/EU)	Compliant
REACh Status	Compliant
MSL Rating (JDEC-STD-033):	Not Applicable

#### Packaging Details

- Pack Style: Bulk Loose in bulk pack Pack Size: 100
- Alternative packing option available



#### Outline (mm)



Sales Office Contact Details: UK: +44 (0)1460 270200 Germany: 0800 1808 443

France: 0800 901 383 USA: +1.760.318.2824 Email: info@iqdfrequencyproducts.com Web: www.iqdfrequencyproducts.com