



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




	Hi-Rel Magnetics	Inductance		Test Freq. (kHz)	DC Resistance		Rated DC Current	
		Spec. (uH)	Tol.		Spec. (Ohm)	Tol.	Idc 1 (A max.)	Idc 2 (A Typ.)
35	LGJ12565TS-2R0N6R2-H	2.0uH	+/-30%	1	8.0m	+/-20%	10.0	6.2
36	LGJ12565TS-4R2N5R5-H	4.2uH	+/-30%	1	11.2m	+/-20%	7.3	5.5
37	LGJ12565TS-7R0N5R0-H	7.0uH	+/-30%	1	17.7m	+/-20%	5.7	5.0
38	LGJ12565TS-100M4R8-H	10uH	+/-20%	1	20.2m	+/-20%	5.0	4.8
39	LGJ12565TS-150M4R2-H	15uH	+/-20%	1	23.7m	+/-20%	4.2	4.4
40	LGJ12565TS-220M3R5-H	22uH	+/-20%	1	31.6m	+/-20%	3.5	3.8
41	LGJ12565TS-330M2R8-H	33uH	+/-20%	1	40.6m	+/-20%	2.8	3.4
42	LGJ12565TS-470M2R4-H	47uH	+/-20%	1	57.8m	+/-20%	2.4	2.8
43	LGJ12565TS-680M2R0-H	68uH	+/-20%	1	78.7m	+/-20%	2.0	2.4
44	LGJ12565TS-101M1R6-H	100uH	+/-20%	1	0.123	+/-20%	1.6	1.9
45	LGJ12565TS-151M1R3-H	150uH	+/-20%	1	0.212	+/-20%	1.3	1.4
46	LGJ12565TS-221M1R0-H	220uH	+/-20%	1	0.273	+/-20%	1.0	1.2
47	LGJ12565TS-331MR87-H	330uH	+/-20%	1	0.494	+/-20%	0.87	0.95
48	LGJ12565TS-471MR70-H	470uH	+/-20%	1	0.77	+/-20%	0.7	0.75
49	LGJ12565TS-102MR45-H	1000uH	+/-20%	1	1.68	+/-20%	0.45	0.5
50	LGJ12565TS-152MR37-H	1500uH	+/-20%	1	2.8	+/-20%	0.37	0.4

Note) : Idc 1: Depends on the Inductance Saturation. (-10% Saturation from initial L Value)

Idc 2: Depends on the self temperature rise. (+40°C typ.)

Operating temperature: -40°C ~ +125°C (Including self temperature rise)

Storage temperature: -40°C ~ 125°C



Recommended Land Pattern (Unit: mm)