



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832


Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Radial Leaded Inductors[LHL]

LHL10TB273J



■ Features

- Item Summary
27mH±5%, 60mA, φ11.0x14.0mm Radial
- Lifecycle Stage
Mass Production
- Standard packaging quantity (minimum)
Taping 500pcs

■ Products characteristics table

| | |
|---|---|
| Inductance | 27 mH ± 5 % |
| Case Size (mm) | 11.0x14.0 |
| Rated Current (max) | 60 mA |
| DC Resistance (max) | 67 Ω |
| Q (min) | 40 |
| LQ Measuring Frequency | L : 1kHz Q : 0.0796MHz |
| Self Resonant Frequency (min) | 0.15 MHz |
| Operating Temp. Range | -25 to +105 °C (Including-self-generated heat) |
| Temperature characteristic (Inductance change) | ± 7 % |
| RoHS2 Compliance (10 subst.) | Yes |
| REACH Compliance (173 subst.) | Yes |
| Soldering | Wave |

■ External Dimensions

| | |
|--------------|---------------|
| Dimension D | Max φ11.0 mm |
| Dimension H2 | Max 14.0 mm |
| Dimension d | φ0.6 ±0.05 mm |
| Dimension F | 5.0 ±1.0 mm |
| Dimension l | 5.0 ±1.0 mm |

2017.04.30

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.
 TAIYO YUDEN reserves the right to make change to the Date at any time without notice.
 Before making final selection, please check product specification.