

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









LI0402B301R-10

UNCONTROLLED DOCUMENT


PHYSICAL DIMENSIONS:



IZI D AND V EDECUENC



AGILENT E4991A RF Impedance/Material Analyzer HP 16194A Test Fixture. TEST REF. 3235






ELECTRICAL CHARACTERISTICS:									
Z @ 100M (Ω)	1Hz	DCR (Ω)	Rated Current						
Nominal	300								
Minimum	225								
Maximum	375	0.80	200 mA						

NOTES: UNLESS OTHERWISE SPECIFIED


- 1. TAPED AND REELED per CURRENT EIA SPECIFICATIONS 7" REELS, 10,000 PCS/REEL, PAPER TAPE.
- 2. TERMINATION FINISH IS 100% TIN.
- 3. COMPONENTS SHOULD BE ADEQUATELY PREHEATED BEFORE SOLDERING.
- 4. OPERATING TEMP. RANGE: -40°C~+125°C. (INCLUDING SELF-HEATING)

LAND PATTERNS FOR REFLOW SOLDERING



(For wave soldering, add 0.762 [.030] to this dimension.)

RECOMMENDED SOLDERING CONDITIONS





	DIMENSIONS ARE IN mm [INCHES].				This print is the property of Laird								
					Tech. and is loaned in confidence		 						
					subject to return upon request an with the understanding that no	I SIFA							
					copies shall be made without the		Laird						
					written consent of Laird Tech. All								
					rights to design or invention are								
	D	ADD OPERATING TEMPERATURE UPDATE LAIRD LOGO AND REFLOW CURVE	08/05/13	QU	reserved.								
		UPDATE LAIRD LOGO AND REFLOW CURVE			PROJECT/PART NUMBER:	REV	PART TY	PE:	DRAWN BY:				
	С	UPDATE COMPANY LOGO	07/08/08	JRK	LI0402B301R-10	D	CO-	FIRE	ТМВ				
	В	CHANGE REEL QTY FROM 4000, ADD PAPER	11 /17 /07	JRK	LIU402B301K-10		00	TIKE	TWID				
6	В	TAPE TO NOTE #1, ADD ROHS SYMBOL	11/13/07	JKK	DATE: 04/05/04 SC/	NE: N	TS	SHEET:					
	Α	ORIGINAL DRAFT	04/05/04	TMB	CAD #	DL #		2	of 2				
	REV	DESCRIPTION	DATE	INT			-		01 2				