

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







# LI0603G121R-10

# UNCONTROLLED DOCUMENT

## PHYSICAL DIMENSIONS:

Α	1.60 [.063]	<sup>±</sup> 0.15	[.006]
В	0.80 [.031]	± 0.15	[.006]
С	0.80 [.031]	± 0.15	[.006]

D 0.36 [.014] ± 0.15 [.006]


# B C C

ELECTRICAL CHARACTERISTICS:									
Z @ 100M ( Ω )	1Hz	DCR $\left(\begin{array}{c}\Omega\end{array}\right)$	Rated Current						
Nominal	120								
Minimum	90								
Maximum	150	0.20	700 mA						

NOTES: UNLESS OTHERWISE SPECIFIED


- 1. TAPED AND REELED per CURRENT EIA SPECIFICATIONS 7" REELS, 4000 PCS/REEL.
- 2. TERMINATION FINISH IS 100% TIN.
- 3. COMPONENTS SHOULD BE ADEQUATELY PREHEATED BEFORE SOLDERING.
- 4. OPERATING TEMP. RANGE: -40°C~+125°C. (INCLUDING SELF-HEATING)

# Z vs FREQUENCY IMPEDANCE UNDER DC BIAS




## FREQUENCY (MHz)

|Z| , R, AND X vs. FREQUENCY




HP 16194A Test Fixture. TEST REF. 3235

### LAND PATTERNS FOR REFLOW SOLDERING



(For wave soldering, add 0.762 [.030] to this dimension)

## RECOMMENDED SOLDERING CONDITIONS





$\overline{}$									
DIMENSIONS ARE IN mm [INCHES].				This print is the property of Lair	d				
				Tech. and is loaned in confidence	3		•	. ="	
				subject to return upon request a with the understanding that no	ina	Laird			
				copies shall be made without the	,				
				written consent of Laird Tech. Al	١				
				rights to design or invention are reserved.					
<b>-</b>									
				PROJECT/PART NUMBER:	REV	PART TY	PE:	DRAWN BY:	
С	ADD OPERATING TEMPERATURE UPDATE LAIRD LOGO AND REFLOW CURVE	09 /05 /13	QU	LI0603G121R-10	0	CO-FIRE		ТМВ	
·	UPDATE LAIRD LOGO AND REFLOW CURVE	06/03/13	QU	L10003012110 10	1 0	"	IMD		
В	UPDATE COMPANY LOGO ADD ROHS SYM	07/15/08	JRK	DATE: 03/26/04 s	CALE:		SHEET:		
A	ORIGINAL DRAFT	03/26/04	TMR			_	0	of 2	
	C. I.	55, 20, 61		CAD # LLOCO 7 01 01 D 10 0	OOL #	_		or Z	
REV	l description	I DATE	INIT	1 1060.561218-10-6 1		_			