

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







# LI1806E101R-10

### **UNCONTROLLED DOCUMENT**

#### PHYSICAL DIMENSIONS:

A 4.50 [.177] ± 0.25 [.010]


B 1.60 [.063] ± 0.25 [.010] ± 0.25 [.010]

± 0.25 [.010] D 0.51 [.020]


C 1.60 [.063]

IMPEDANCE (Ω)


#### Z vs FREQUENCY IMPEDANCE UNDER DC BIAS







AGILENT E4991A RF Impedance/Material Analyzer HP 16194A Test Fixture. TEST REF. 3124






ELECTRICAL CHARACTERISTICS:											
Z @ 100M ( <u>Ω</u> )	1Hz	DCR ( $\Omega$ )	Rated Current								
Nominal	100										
Minimum 75											
Maximum	125	0.30	500 mA								

NOTES: UNLESS OTHERWISE SPECIFIED


- 1. TAPED AND REELED per CURRENT EIA SPECIFICATIONS 7" REELS, 2000 PCS/REEL.
- 2. TERMINATION FINISH IS 100% TIN.
- 3. COMPONENTS SHOULD BE ADEQUATELY PREHEATED BEFORE SOLDERING.
- 4. OPERATING TEMP. RANGE: -40°C~+125°C. (INCLUDING SELF-HEATING)

#### LAND PATTERNS FOR REFLOW SOLDERING



(For wave soldering, add 0.762 [.030] to this dimension.)

#### RECOMMENDED SOLDERING CONDITIONS



DIMENSIONS ARE IN mm [INCHES].			This print is the property of Lair	ď						
				Tech, and is loaned in confidence subject to return upon request a						
		with the understanding that no		II 2II N						
-				copies shall be made without the written consent of Laird Tech. Al		-ana				
				rights to design or invention are reserved.						
	ADD OPERATING TEMPERATURE	00 /05 /47	QU	PROJECT/PART NUMBER:	ᇻ	EV	PART TY	PE:	DRAWN BY:	
U	D ADD OPERATING TEMPERATURE UPDATE LAIRD LOGO AND REFLOW CURVE		QU	LI1806E101R-10		D co-		FIRE	тмв	
С	CHANGE REEL QTY FROM 3K TO 2K	11/05/08	JRK	LITOGOLIOTIC TO	Т			TIKE		
В	UPDATE COMPANY LOGO ADD ROHS SYM			1 04/05/04 1	CALE	OOL #		SHEET:	SHEET: 2 of 2	
Α	ORIGINAL DRAFT	04/05/04	тмв	, , , , , , , , , , , , , , , , , , ,	OOL			2		
REV	DESCRIPTION	DATE	INT					_	· -	