

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







AMPROBE°

Data Sheet



LM-200LED LED Light Meter

A professional tester specifically designed to accurately measure light output of the LED light sources.

- Lux or Foot-candle user selectable measurement units
- Measuring Range to 400,000 Lux or 40,000 Foot candles
- Built-in memory with 99 records storage
- Data Hold to freeze reading on the digital display
- MAX recording to capture highest light measurement
- Measuring lights source include all visible ranges
- Spectral response close to CIE luminous spectral efficiency
- Angled light cosine correction
- Extended length of wire for light sensor approximately 5 feet (1.5m)
- Measurements according to JISC1609:1993 and CNS 5119 general A class specifications
- **■** Includes protective sensor cap
- Large, 3-1/2 digit display

No hassle warranty

No waiting.





(note: \$500 MSLP limit)





LM-200LED LED Light Meter

Data Sheet

General Specifications

Display	2000 count LCD
Sensor	Silicon photodiode and filter.
Environment	Indoor operation
Altitude	Up to 2000m.
LED Light Measurement	3½ digits, 2000 readings
Range	40, 400, 4,000, 40,000, 400,000 Lux 40, 400, 4,000, 40,000 Foot-candle
Accuracy	+/-3% (Calibrated to standard incandescent lamp 2856° K) and corrected LED day while-light spectrum. +/-6% other visible light sources
Temperature / Humidity	
Operating	-10 °C to 40 °C (14°F to 104°F), 0 to 80 %RH.
Storage	-10 °C to 50 °C (14°F to 122°F), 0 to 70 %RH.
Power Supply	9V NEDA 1604, IEC 6F22, JIS 006P battery
Battery life	200 hours
Auto Power Off	approx 6 min
Dimension (Base)	130 x 63 x 38 mm (5.1 x 2.5 x 1.5")
Dimension (Sensor)	80 x 55 x 29 mm (3.2 x 2.2 x 1.1")
Weight	220 g (.48 lb.) include battery
Included Accessories	Users manual, 9 volt battery



Amprobe® Test Tools

website: www.Amprobe.com email: info@amprobe.com Everett, WA 98203

Tel: 877-AMPROBE

Amprobe® Test Tools Europe

In den Engematten 14 79286 Glottertal, Germany Tel.: +49 (0) 7684 8009 - 0

> ©2010 Amprobe Test Tools. All rights reserved. 7/2010 LM-200LED_DS Rev A