

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









This document was generated on 04/09/2013

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: <u>15266-1015</u>

Status: Active

Overview: Premo-Flex™ FFC and Etched Polyimide Jumpers

Description: 0.50mm Pitch Premo-Flex™ FFC Jumper, Same Side Contacts (Type A), 31 Circuits,

0.102m Cable Length, 0.27mm Cable Thickness, Tin (Sn) Plating

Documents:

<u>Drawing (PDF)</u>
<u>Product Specification PS-15266-001 (PDF)</u>

<u>RoHS Certificate of Compliance (PDF)</u>

General

Product Family Cable Series 15266

Comments Contacts on the same side, Type A

Crimp Quality Equipment Ye

Overview <u>Premo-Flex™ FFC and Etched Polyimide Jumpers</u>

Product Name Premo-Flex™FFC Jumper

UPC 884982445185

Physical

Cable Length0.102mCircuits (Loaded)31Circuits (maximum)31Packaging TypeBagPitch - Termination Interface0.50mm

Temperature Range - Operating -40°C to +105°C

Wire Size AWG N/A

Wire/Cable Type Flat Flex Cable


Electrical

Current - Maximum per Contact 0.5A Voltage - Maximum 60V AC

Material Info

Reference - Drawing Numbers

Packaging Specification PK-15266-001
Product Specification PS-15266-001
Sales Drawing SD-15266-001



EU RoHS
ELV and RoHS
Compliant
REACH SVHC
Not Reviewed
Low-Halogen Status
Not Reviewed



Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
For a multiple part number RoHS Certificate of Compliance, <u>click here</u>

Please visit the <u>Contact Us</u> section for any non-product compliance questions.

Search Parts in this Series

<u>15266</u>Series

Use With

www.molex.com/product/ffcfpc_th.html

This document was generated on 04/09/2013

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION