



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Low Profile, Panel Flush Light Pipe



Light pipe transmits from SMD LED to the front of a panel

Applications

- security cameras
- entertainment systems
- telephone systems
- panel and cabinet illumination
- medical devices

Key features

- allows easy panel removal
- low profile, panel flush design blends in until light is emitted
- mates to any PCB using SMD 4 (sold separately)
- optical grade acrylic for maximum light transmission
- efficient production assembly
- available in standard lengths of .300" to 1.20"
- custom lengths available upon request
- RoHS compliant

Product specifications

Materials	
LPCM (litepipe)	clear optical grade acrylic, UL rating 94-HB
SMD 4 (PCB mount)	nylon, (black) UL rating 94-V2

Installation specification	
mounting hole	.173" [4.4mm] min to .183" [4.6mm] max without retaining ring RTN 150
	.173" [4.4mm] min to .200" [5.1mm] max with retaining ring RTN 150
panel thickness	MAX : DIM A - .300" [7.62mm]

Ordering data

LPCM lightpipe
 ordering code (example)
 (Min 030 = .300") (Max 120 = 1.20")

LPCM **XXX** CTP

LITEPIPE ORDERING CALCULATIONS:
 DIM A - DIM B (.200" [5.1mm]) = MIN LIGHTPIPE LENGTH
 DIM A - DIM C (.100" [2.5mm]) = MAX LIGHTPIPE LENGTH

XXX = length in inches				
Standard sizes*				
030	040	050	060	070
080	090	100	110	120

*Custom Lengths Available Upon Request

Dimensions (Not drawn to scale)

