

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







SS, LSK Series







SPECIFICATIONS:

RATING: 0.5A 50VDC

· Compact Size, Multiple Functions

· RoHS and Lead-Free Compliant

· Customizable Actuator Height

TEMPERATURE: -30°C to 105°C


ELECTRICAL LIFE: 10,000 Cycles

Contact Resistance: $30m\Omega$ Max.

Insulation Resistance: $500M\Omega$ Min. at 500VDC


FEATURES:






Suggested PCB Layout 0.079 [2.0] 0.165 [4.2] [0.8] 0.051 [1.3] 0.827 [21.0] 0.031

Electrical Schematic








MATERIALS:


Body: Steel **Actuator:** Polyoxymethylene Base: Phenolic Board CONTACTS: Silver Plated Copper TERMINALS: Silver Plated Brass




0.024 [0.6]

0.016 [0.4]

0.165 [4.2] 0.343 [8.7]



Electrical Schematic





LSS-430101A4

LSK-420201A7

LSS-420101Ax (x for Actuator Length)

LSS-430101Ax (x for Actuator Length)

[6.3]

0.366

Q


LSK-430201Ax (x for Actuator Length)

0.079 [2.0] Travel

0.217 [5.5]

0.866 [22.0]

0.366



П

0.039 [1.0]

0.020 [0.5]

0.079 [2.0]


0.276 [7.0]

0.079 [2.0] Travel


0.039 [1.0]

0.020 [0.5]


0.079 [2.0]




Electrical Schematic



Suggested PCB Layout



Electrical Schematic





0.866 [22.0]

0.650 [16.5]

M2.6x0.45

0



43 - 4 Pole, On-On-On



[14.0] [16.5] 17.5

0.551 0.650 0.689



0.024 [0.6]

0.016 [0.4]

0.165 [4.2]

0.343 [8.7]

0.146 [3.7]





X - Varies From 2 to 20



SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



EXAMPLE PART NUMBERS:

LSK-420201A5 4P2T On-On Model 020, PCB Pins, 5.0mm Side Actuator

LSK-430201A5 4P3T On-On-On Model 020, PCB Pins, 5.0mm Side Actuator

LSS-420101A5 4P2T On-On Model 010, PCB Pins, 5.0mm Vert. Actuator

LSS-430101A5 4P3T On-On-On Model 010, PCB Pins, 5.0mm Vert. Actuator