

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







• PC Board and Solder Terminal Options

· RoHS and Lead-Free Compliant

Customizable Actuator Height


5.5A 250VAC ELECTRICAL LIFE: 10,000 Cycles

CONTACT RESISTANCE: 30mΩ Max.

Insulation Resistance: $500M\Omega$ Min. at 500VDC

DIELECTRIC STRENGTH: 500VAC for 1 Minute

Suggested PCB Layout



Electrical Schematic



MATERIALS:

FEATURES:

SPECIFICATIONS:


RATING: 11A 125VAC

Body: Steel

ACTUATOR: Polyphenylene Oxide Base: Phenolic Board, UL94 V-0 CONTACTS: Silver Alloy

TERMINALS: Silver Plated Copper

LSU11-120002Ax (x for Actuator Length)



Electrical Schematic



LSU11-220001Ax (x for Actuator Length)

LSU11-220002Ax (x for Actuator Length)

0.138 [3.5]

0.157 [4.0] Travel

0.276 [7.0]

[17.7]

0.697

0.220 [5.6]

0.020 [0.5] 0.327 [8.3]

Terminal

1 - PCB Pin

2 - Solder

Type

Actuator

A - Rounded

Ridged

Type

Actuator

9mm (Standard)

X - Varies From 2 to 20

Height

0.024 [0.6] 0.315 [8.0]

0.071 [1.8]

0.114 [2.9] 0.303 [7.7]

000 - 22.4 x 14.0, Unthreaded


001 - 22.4 x 14.0. Threaded

Model


1.358 [34.5]

1.122 [28.5]

0.882 [22.4]



Suggested PCB Layout



Electrical Schematic





Electrical Schematic



LSU11-220002A5

LSU11-220001A7



EXAMPLE PART NUMBERS:

LSU11-120001A9 1P2T On-On Model 000, PCB Pins, 9.0mm Actuator

LSU11-120002A9 1P2T On-On Model 000, Solder, 9.0mm Actuator

LSU11-220001A9 2P2T On-On Model 000, PCB Pins, 9.0mm Actuator

LSU11-220002A9 2P2T On-On Model 000, Solder, 9.0mm Actuator



LSU11 - 11A, Vertical Knob

Series

E+SWITCH®

0.551 [14.0]

Number of

Poles / Positions

- 1 Pole, On-On

22 - 2 Pole, On-On