



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





LT-10 Lamp Tester

Goes From Your Pocket to Answers in Seconds

The Amprobe LT-10 Lamp Tester is a pocket-sized tool that takes the guesswork out of troubleshooting fluorescent lighting systems. Quickly determine by process of elimination, whether it's the bulb, pins, voltage or ballast. The highly responsive 48" antenna, will save you trips up and down the ladder. The LT-10 Lamp Tester will go from your pocket to answers in seconds.

- Determine if fluorescent light bulbs are operational prior to installation or removal
- Verify voltage presence without the need for another tool
- Increase productivity by minimizing trips up and down a ladder
- All tests performed with easy, single button operation
- Ultra-compact design for portability
- Industry leading 48" removable, fully retractable antenna
- Insulated antenna sleeve for safe testing
- Compatible with fluorescent light bulbs:
 - T2, T4, T5, T8, T9, T10, T12 and fluorescent energy saving light bulbs



Troubleshooting Lighting Systems is Easy as 1-2-3:

1. Check if fluorescent light bulb is damaged with LAMP and PIN TEST functions
2. Verify if voltage is present at the ballast with VolTect™ non-contact voltage detection
3. If light bulb passes the test in step 1 and the voltage is present in step 2, but the lamp is still not working, then replace ballast.

LT-10 SPECIFICATIONS

Specifications	LT-10
Compatible lamps	T2, T4, T5, T8, T9, T10, T12 and fluorescent energy saving light bulbs
Test voltage	Approximately 3 kV / 280 kHz
Field strength	Approximately 100 μV/m at 260 - 300 kHz
Maximum antenna length	48"
Filament test	T2, T4, T5, T8, T9, T10, T12
VolTect™ non-contact voltage detection	AC 90 V to AC 600 V, 50/60 Hz CAT II 300 V, CAT I 600 V
Supplied with	48" antenna, adaptor plate, users manual, battery and carrying case

For more detailed specifications see users manual.

LT-10 DETAILED SPECIFICATIONS

Specifications	Range
Compatible lamps	T2, T4, T5, T8, T9, T10, T12 and fluorescent energy saving light bulbs
Test voltage	Approximately 3 kV / 280 kHz
Field strength	Approximately 100 μ V/m at 260 - 300 kHz
Maximum antenna length	48"
Filament test	T2, T4, T5, T8, T9, T10, T12
VolTect™ non-contact voltage detection	AC 90 V to AC 600 V, 50/60 Hz CAT II 300 V, CAT I 600 V
Non-contact voltage sensitivity with probe tip (typical)	LED illuminates and beeps at approx. 3 mm (0.12 in) distance from a wire carrying 120 Vac LED illuminates and beeps at approx. 5 mm (0.2 in) distance from a wire carrying 230 Vac
Drop proof	36"
Operating time	One second ON, one second OFF for maximum five cycles and wait for 1 minute before taking another measurement
Operating temperature	-10°C to +50°C (14°F to 122°F) \leq 85% RH
Storage temperature	-10°C to +50°C (14°F to 122°F) \leq 85% RH
Operating altitude	Up to 2000 meters
Battery	One 9V lithium or alkaline battery only, 6LR61/6LF22/MN1604 or equivalent.
Battery life	Up to 500 tests (Alkaline typically)
Dimensions (L x W x H)	Approximately 170 x 40 x 24 mm (6.69 x 1.57 x 0.94 in) without antenna
Weight	Approximately 80 g (0.18 lb) with battery installed, excluding 48" antenna
Safety compliance	IEC 61010-1, UL 61010-1, CAN/CSA-C22.2 No. 61010-1-2004
EMC compliance	IEC 61326-1
Certification	CSA and CE
Calibration	NA
Warranty	1 Year

For complete specifications please download the product datasheet and the users manual on www.Amprobe.com.