



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us


Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com





Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



SW2014



Revision level			Revision Record	Changed	Date	Approved	Date
Drawing	State	Part					
00.0	Design Release		SEE ECN# 013638	GRW	11/30/2016	KAC	11/30/2016



SECTION A-A

- NOTES:
1. FLAMMABILITY SELF-EXTINGUISHING (EN613861)
  2. OPERATING TEMPERATURE -76° F TO +302° F (-60° C TO +150° C)
  3. RoHS
  4. HF
  5. USE WITH HELAGUARD LTP OR LTPUL SERIES METALLIC FITTINGS FOR IP66 + IP67 + IP68 + IP69 RATINGS
  6. MANUFACTURED TO UL360 REQUIREMENTS
  7. CONSULT FACTORY OR WEBSITE FOR AVAILABLE LENGTHS

Conduit Nominal Size		HellermannTyton Item Number	Man'f Part Reference	Outside Dimension (OD)		Inside Dimension (ID)		Minimum Bend Radius	
inches	mm			in	mm	in	mm	in	mm
1/4	10.0	LTPHC10B-25M	LTPHC10	0.46	11.8	0.28	7.0	1.38	35.0
5/16	12.0	LTPHC12B-25M	LTPHC20	0.56	14.2	0.39	10.0	1.57	40.0
3/8	16.0	LTPHC16B-25M	LTPHC16	0.70	17.8	0.50	12.6	1.77	45.0
1/2	20.0	LTPHC20B-25M	LTPHC20	0.83	21.1	0.63	16.0	2.56	65.0
3/4	25.0	LTPHC25B-25M	LTPHC25	1.04	26.4	0.83	21.0	3.94	100.0
1	32.0	LTPHC32B-25M	LTPHC32	1.30	33.1	1.04	26.5	5.31	135.0
1-1/4	40.0	LTPHC40B-10M	LTPHC40	1.65	41.8	1.39	35.4	6.89	175.0
1-1/2	50.0	LTPHC50B-10M	LTPHC50	1.89	47.9	1.59	40.4	9.05	230.0
2	63.0	LTPHC63B-10M	LTPHC63	2.35	59.7	2.03	51.6	11.02	280.0

<b>Material</b> GALVANIZED STEEL & THERMOPLASTIC RUBBER	Units: <b>inches</b> Dimension without tolerances details to: .xxxx = ±.0005 .xxx = ±.005 .xx = ±.01 .x = ±.03 None = ±.06 ∠ = ±0.5° Dimension Formatted in/[mm]	The copyright of this drawing is reserved by HellermannTyton. It is issued on condition that it is not reproduced, copied, or disclosed to a third party, either wholly or in part, without the consent of HellermannTyton.	Drawn GRW 11/30/2016	Article/Type-No LTPHC SERIES		Scale
	Approved KAC 11/30/2016		Title <b>HELAGUARD FLEXIBLE METALLIC GALVANIZED STEEL CONDUIT, LIQUID-TIGHT JACKETED THERMOPLASTIC COVER</b>		Project Number PRP 16-1963	
	North America Email: corp@htamericas.com Web: www.hellermann.tyton.com			Drawing-No PRODUCTION : Phase	Format AH	
				<b>16-1963-001-CSU</b>		Sheet 1/1