



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





LVSM1NP

LVSM1PL

Our Low Voltage Wall Switches are designed for virtually any area. The soft contours of its architecturally-pleasing design fit easily into any décor. Momentary version switches are available and feature multiple button configurations making them the perfect switch solution for low voltage occupancy sensors, daylighting controls and networked lighting control panels.

Product Features

- Attractive, architecturally pleasing design
- Momentary or latching button action
- 1-4 buttons with or without LED
- Mounts to standard single-gang box
- California Title 24 compliant
- Five-year limited warranty
- Low voltage device: 24VDC

Compliance and Certification



Ordering Information

LVS	—		—		—		—	
SWITCH MODEL LVS		SWITCH TYPE M Momentary L Latching		NUMBER OF BUTTONS 1-4		PILOT PL w/ Pilot LEDS NP No Pilot		COLOR WH White IV Ivory LA Light Almond G Gray

Latching buttons are for special applications only, consult factory if you are not certain about how to use a latching button

General Specifications

Electrical Ratings	Each switch: 100mA @ 30VDC Max Each pilot LED: 18-30VDC, internal 2.2kohm, ½ Watt resistor
Configurations	1 - 4 buttons, with or without pilot LED Momentary
Operating environment	Indoor use only Operating temperature: 32° to 122°F (0° to 50°C) Relative humidity (non-condensing): 10%-90%
Construction	Housing – Rugged, high-impact, injection-molded plastic Color-coded leads
Dimensions	1.88"W x 4.25"H x 1.56"D (47.75mm x 107.95mm x 39.63mm)
Weight	3.0 oz [85.0 g]
Color	White, Ivory, Light Almond, Gray
Mounting	Single-gang NEMA-style switch box (average switch box) Decorator-style wall plate not included
Warranty	Five-year limited