



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



LXV300 series

LED Power Supply

Constant Voltage Power Supplies

LED Power
300W

LED POWER

next generation power source

FEATURES

- High Efficiency 94%
- IP67 Waterproof
- Active PFC (Typical 0.99)
- OVP, SCP, OTP
- -35 to 70°C deg operation
- Wide Input 90-305VAC
- UL8750 recognised
- EN61347-1, -2-13 compliant

The LXV300 series of constant voltage LED power supplies from Excelsys Technologies can deliver up to 300W of output power in an extremely compact package size.

The LXV300 series of constant voltage power supplies provides a range of output voltage solutions for specific LED requirements. With industry leading efficiencies, and an extensive protection feature set, the LXV300 series provides high reliability and high performance in a compact package. The LXV300 series carries the CE mark for safety and is also RoHS compliant. For more details contact sales@excelsys.com

Model Number	Output Voltage	Output Current	Input Voltage	OVP Max	OCP Hiccup	Efficiency
LXV300-012SW	12V	23.3A	90-305VAC	18V	110-180%	92.0%
LXV300-024SW	24V	12.50A	90-305VAC	35V	110-180%	93.0%
LXV300-036SW	36V	8.33A	90-305VAC	50V	110-180%	94.0%
LXV300-042SW	42V	7.14A	90-305VAC	55V	110-180%	93.5%
LXV300-048SW	48V	6.25A	90-305VAC	61V	110-180%	93.5%
LXV300-052SW	52V	5.76A	90-305VAC	66V	110-180%	93.5%
LXV300-054SW	54V	5.55A	90-305VAC	66V	110-180%	94.0%
LXV300-056SW	56V	5.35A	90-305VAC	78V	110-180%	94.0%
LXV300-060SW	60V	5.00A	90-305VAC	78V	110-180%	94.0%
LXV300-084SW	84V	3.57A	90-305VAC	105V	110-180%	94.0%
LXV300-105SW	105V	2.85A	90-305VAC	130V	110-180%	94.0%
LXV300-150SW	150V	2.00A	90-305VAC	185V	110-180%	94.0%

Input Specifications

Parameter	Conditions/Description	Min	Nom	Max	Units
Input Voltage Range	Universal Input	90		305	VAC
Input Frequency Range		47		63	Hz
Input Current	100VAC in, 300W output			3.3	A
Power Factor	220VAC, 110 VAC	0.96		0.99	
Inrush Current	At 230 Vac input, 25°C cold start			50	A

Output Specifications

Parameter	Conditions/Description	Min	Nom	Max	Units
Line Regulation				±1	%
Load Regulation				±3	%
Voltage Accuracy	% of Vout			±5	%
Ripple and Noise	20MHz Bandwidth. See Note 1			2.0	% pk-pk
Dynamic Response	Output Deviation R/S : 1 A /uS Settling Time Load : 25% ~ 75% full Load			5% Vo 10 mS	
Overshoot				10	%
Turn-on Delay	Measured at 220VAC and full load			3	s
Short Circuit Protection	Auto Recovery				
Over Voltage Protection	Non -latching. See individual models OVP levels				
OverTemperature Protection	Internal Component Temperature			110	°C

General Specifications

Parameter	Conditions/Description	Min	Nom	Max	Units
Isolation Voltage	Input to Output See Note 2 Input to Chassis	3750 1500			VAC VAC
Efficiency	See individual models		94.0		%
Safety Agency Approvals	UL8750, EN61347-1, -2-13 pending				
No load Power Dissipation	Measured at 120VAC and 220VAC			3.0	W
MTBF	MIL HDBK-217F, 110VAC input, 80% load, 25°C		296,000		Hours
Lifetime	220VAC input, 80% load, 45°C		156,000		Hours
Weight			1540		g
Operating Temperature		-35		+70	°C
Storage Temperature		-40		+85	°C
Relative Humidity	Non-condensing (operating)	10		100	%RH
Power Derating	At 100 VAC, derates linearly from 100% at 60°C to 80% at 70 °C At 277 VAC, derates linearly from 100% at 65°C to 90% at 70 °C				

Note 1.
Note 2.Output connected in parallel with 0.1uF ceramic capacitor and 10uF electrolytic capacitor.
Primary to Secondary Isolation test not to be carried on power supply.

Europe/Asia

Excelsys Technologies Ltd t: +353 21 4354716
27 Eastgate Drive f: +353 21 4354864
Eastgate Business Park e: sales@excelsys.com
Little Island, Cork, Ireland
IRELAND

North America

Excelsys Technologies t: (972) 771 4544
519 Interstate 30, #309 f: (972) 421 1805
Rockwall, TX 75087 e: salesusa@excelsys.com
USA

EMC			
Parameter	Standard	Level	Units
Emissions			
Conducted	EN55015	Level B	
Radiated	EN55015	Level B	
Harmonic Distortion	EN61000-3-2	Compliant	
Flicker and Fluctuation	EN61000-3-3	Compliant	
Immunity			
ESD	EN61000-4-2	Level 4	
Radiated RFI	EN61000-4-3	Level 3	
Fast Transients - burst	EN61000-4-4	Level 4	
Input Line Surges	EN61000-4-5	Level 4	
Conducted RFI	EN61000-4-6	Compliant	
Power Freq Magnetic Field	EN61000-4-8	Compliant	
Voltage Dips	EN61000-4-11	Compliant	

INPUT / OUTPUT WIRING


INPUT CABLE

SJTW 18AWG 2C
Black (L) and White(N), Green (Earth) 650±20mm

OUTPUT CABLE

SJTW 18AWG 2C
Black (-V) and Red (+V) 220±20mm

MECHANICAL SPECIFICATIONS



LXV300-012SW

LXV300-024SW
LXV300-036SW
LXV300-042SW

LXV300-048SW
to
LXV300-150SW

All Tolerances ± 0.2mm unless specified

Specifications are subject to change without notice
LXV300 Datasheet 27 April 2011



Europe/Asia		North America	
Excelsys Technologies Ltd	t: +353 21 4354716	Excelsys Technologies	t: (972) 771 4544
27 Eastgate Drive	f: +353 21 4354864	519 Interstate 30, #309	f: (972) 421 1805
Eastgate Business Park	e: sales@excelsys.com	Rockwall, TX 75087	e: salesusa@excelsys.com
Little Island, Cork, Ireland		USA	
IRELAND			