

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



### Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China











# Product Brief LUXEON H

High Voltage LED

LUXEON® H delivers superior color performance and reliability in a high voltage architecture that minimizes driver requirements making it an ideal solution for space constrained and cost sensitive retrofit bulbs and luminaires. With exceptional color stability over temperature and current, LUXEON H simplifies design while providing superior quality of light.

#### LUXEON H Benefits:

- Designed for the demanding compact retrofit bulb market
- Enables simplified solutions—no DC driver required
- Driven directly with rectified AC requiring just a resistor and bridge rectifier enabling more space to be allocated to thermal management
- Products with 50V I-4 watt, I00V/200V 4-8 watt that delivers high quality of light with stable color over operating current and temperature
- LUXEON quality and reliability
- Complete optical, electrical and mechanical design resources help you get to market faster.









#### **LUXEON H Illumination Characteristics**

			Test		Min.	Тур.	Тур.	Max.	Тур.		
		CCT	Current	Min.	Flux	Flux	Voltage	Voltage	Efficacy	Binning	Part
Series	Voltage	(K)	(mA)	CRI	(lm)	(lm)	(V)	(V)	(lm/W)	Description	Number
H50-1	50	2700K	20	80	50	63	53	60	60	ANSI Color Binning	LXAC-PW27
H50-1	50	3000K	20	80	50	67	53	60	63	ANSI Color Binning	LXAC-PW30
H100-8	100	2700K	40	80	300	363	96	98	95	3 SDCM color, One flux, One Vf bin	LXV8-PW27-0014
H100-8	100	3000K	40	80	320	386	96	98	101	3 SDCM color, One flux, One Vf bin	LXV8-PW30-0014
H100-8	100	4000K	40	80	340	408	96	98	106	3 SDCM color, One flux, One Vf bin	LXV8-PW40-0014
H200-8	200	2700K	20	80	300	363	192	196	95	3 SDCM color, One flux, One Vf bin	LXV8-PW27-0024
H200-8	200	3000K	20	80	320	386	192	196	101	3 SDCM color, One flux, One Vf bin	LXV8-PW30-0024
H200-8	200	4000K	20	80	340	408	192	196	106	3 SDCM color, One flux, One Vf bin	LXV8-PW40-0024
H50-2	50	2700K	40	80	150	165	50	52	83	3 and 5 SDCM Color Binning	LXAC-1827
H50-2	50	3000K	40	80	160	175	50	52	88	3 and 5 SDCM Color Binning	LXAC-1830

## LUXEON H Binning LXAC-PW27, LXAC-PW30



## LUXEON H Binning LXV8-PW27, LXV8-PW30, LXV8-PW40



#### LUXEON H Binning LXAC-1827, LXAC-1830

