



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832


Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



DESCRIPTION

SRC Devices' LY-23 is a miniature version of the LY-30. This proximity sensor has been designed in for industrial applications. The modules can be screw- or adhesive-mounted.



FEATURES

- Screw mounting
- No standby power drain

APPLICATIONS

- Position and limit sensing
- Machine tool door sensing
- Door security sensing
- Dishwasher door sensing


SPECIFICATIONS

Parameters	Unit	
Material		ABS
Operate Distance		
Minimum	inches [mm]	0.08 [2.0]
Typical	inches [mm]	0.28 [7.0]
Maximum	inches [mm]	0.47 [12.0]
Body Color		Dark Brown
Wire Length	mm	11.80 [300.0]
Wire Color		Black
Wire AWG	AWG	22
Specifications		
Contact Ratings		
Max. Switching Voltage	VDC	200
Max. Switching Current	A	0.5
Max. Carry Current	A	1.5
Max. Contact Ratings	VA	10
Max. Contact Resistance	Ohms	0.10
Contact Material		Ru
Electrical Ratings		
Insulation Resistance	Ohms	1 x10 ¹¹
Operate Time	ms	0.5
Release Time	ms	0.2
Contact Life	Ops	1 x 10 ⁹
Enviromental Ratings		
Operating Temperature	°C	-40 to +85
Storage Temperature	°C	-40 to +85
Vibration Resistance	Gs	20
Shock Resistance	Gs	30
Weight (sensor)	g	4.6
Weight (magnet)	g	2.6



MECHANICAL DIMENSIONS

Dimensions in inches [mm]



USA 1.866.SRC.8668 EUROPE 44.1225.421999 FAR EAST 886.2.2698.8422

WWW.SRCDEVICES.COM

