



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



### DESCRIPTION

SRC Devices LY-25 series proximity sensor features a hermetically sealed reedswitch mounted in a cylindrical module. The sensor should be mounted on the fixed surface with the activating magnet on the moving surface.



#### FEATURES

- Economic design
- No standby power drain
- High power switches available

#### APPLICATIONS

- Door switching
- Limit switching
- Position and limit switch

### SPECIFICATIONS

Parameters	Unit	
<b>Material</b>		ABS
<b>Body Color</b>		Black
<b>Wire Length</b>	inches [mm]	9.3 [235]
<b>Wire Color</b>		Black and Red
<b>Wire AWG</b>	AWG	24
<b>Specifications</b>		
<b>Contact Ratings</b>		
Max. Switching Voltage	VDC	200
Max. Switching Current	A	0.5
Max. Carry Current	A	1.5
Max. Contact Ratings	VA	10
Max. Contact Resistance	Ohms	0.10
Contact Material		Ru
<b>Electrical Ratings</b>		
Insulation Resistance	Ohms	1 x 10 <sup>11</sup>
Operate Time	ms	0.5
Release Time	ms	0.2
Contact Life	Ops	1 x 10 <sup>9</sup>
<b>Environmental Ratings</b>		
Operating Temperature	°C	-20 to +85
Storage Temperature	°C	-20 to +85
Vibration Resistance	Gs	20
Shock Resistance	Gs	30
<b>Weight</b>	g	3.3



MECHANICAL DIMENSIONS

Dimensions in inches [mm]

