



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Customer Information Sheet

DRAWING No.: M20-106XX00


IF IN DOUBT - ASK



NOT TO SCALE

THIRD ANGLE PROJECTION



ALL DIMENSIONS IN mm



ORDER CODE:

M20-106XX00

No. OF CONTACTS:



SECTION X-X

SPECIFICATIONS:

ELECTRICAL:

- CURRENT RATING = 3A AC/DC
 - VOLTAGE RATING = 250V AC MAX
 - CONTACT RESISTANCE = 20mΩ MAX
 - INSULATION RESISTANCE = 5,000MΩ MIN
 - DIELECTRIC STRENGTH = 1,500V AC FOR 1 MINUTE
- ENVIRONMENTAL:**
- TEMPERATURE RANGE = -40°C TO +105°C

NOTES:

1. CONTACT No. 1 IDENTIFICATION.
2. FOR USE WITH CRIMP CONTACTS:
M20-11600XX (RELDED CONTACTS),
M20-11800XX (LOOSE CONTACTS).
3. THE ABOVE SPECIFICATIONS APPLY WHEN THIS MOULDING IS USED WITH THE SPECIFIED CONTACTS.
4. FOR COMPLETE ELECTRICAL AND MECHANICAL SPECIFICATION, SEE COMPONENT SPECIFICATION COOIXX (LATEST ISSUE).

SB	6	14.07.14	12528
NAME	ISS.	DATE	C/NOTE
APPROVED:		S.BENNETT	
CHECKED:		M.PLESTED	
DRAWN:		S.BENNETT	
CUSTOMER REF.:			
ASSEMBLY DRG:			

HARWIN

www.harwin.com
technical@harwin.com

THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION.

TOLERANCES

X. = ±1mm
X.X = ±0.50mm
X.XX = ±0.10mm
X.XXX = ±0.01mm
ANGLES = ±5°
UNLESS STATED

MATERIAL:

PPE+PS
UL94V-1 BLACK

FINISH: CLEAN, FLASH-FREE

S/AREA: mm²

TITLE:

2.54mm PITCH SIL
CRIMP MOULDING

DRAWING NUMBER:

M20-106XX00

SHT
2 OF 2