



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





2:1 PTFE Heatshrink Tubing

2:1 Polytetrafluoroethylene heatshrink tubing has the lowest coefficient of friction of any polymer and possesses a broad temperature range, allowing it to excel equally in extreme cold and hot environments.

When ordering our 2:1 PTFE heatshrink, order as size after shrinking.

Nominal Size	Part #	Unshrunk Diameter	Shrunk Diameter	Wall Thickness	Put Up/4' Pcs.	Available Colors
24 AWG	M23053-12-201-C	1.27mm	0.69mm	0.30mm	1	Clear (CL)
22 AWG	M23053-12-202-C	1.40mm	0.81mm	0.30mm	1	Clear (CL)
20 AWG	M23053-12-203-C	1.52mm	0.99mm	0.41mm	1	Clear (CL)
19 AWG	M23053-12-204-C	1.65mm	1.09mm	0.41mm	1	Clear (CL)
18 AWG	M23053-12-205-C	1.93mm	1.24mm	0.41mm	1	Clear (CL)
17 AWG	M23053-12-206-C	2.16mm	1.37mm	0.41mm	1	Clear (CL)
15 AWG	M23053-12-207-C	2.79mm	1.70mm	0.41mm	1	Clear (CL)
14 AWG	M23053-12-208-C	3.05mm	1.83mm	0.41mm	1	Clear (CL)
13 AWG	M23053-12-210-C	3.56mm	2.03mm	0.41mm	1	Clear (CL)
12 AWG	M23053-12-211-C	3.81mm	2.26mm	0.41mm	1	Clear (CL)
11 AWG	M23053-12-212-C	4.32mm	2.57mm	0.41mm	1	Clear (CL)
10 AWG	M23053-12-213-C	4.85mm	2.84mm	0.41mm	1	Clear (CL)
9 AWG	M23053-12-214-C	5.21mm	3.15mm	0.51mm	1	Clear (CL)
1/8"	M23053-12-215-C	5.46mm	3.30mm	0.51mm	1	Clear (CL)
8 AWG	M23053-12-216-C	6.10mm	3.58mm	0.51mm	1	Clear (CL)
7 AWG	M23053-12-217-C	6.86mm	4.01mm	0.51mm	1	Clear (CL)
6 AWG	M23053-12-218-C	7.67mm	4.52mm	0.51mm	1	Clear (CL)
5 AWG	M23053-12-219-C	8.13mm	5.03mm	0.51mm	1	Clear (CL)
4 AWG	M23053-12-220-C	9.40mm	5.69mm	0.51mm	1	Clear (CL)
3 AWG	M23053-12-221-C	9.91mm	6.32mm	0.51mm	1	Clear (CL)
1/4"	M23053-12-222-C	10.41mm	6.60mm	0.51mm	1	Clear (CL)
2 AWG	M23053-12-223-C	10.92mm	7.06mm	0.51mm	1	Clear (CL)
1 AWG	M23053-12-224-C	11.43mm	7.90mm	0.51mm	1	Clear (CL)
5/16"	M23053-12-225-C	11.94mm	8.36mm	0.51mm	1	Clear (CL)
0 AWG	M23053-12-226-C	11.94mm	8.81mm	0.51mm	1	Clear (CL)
3/8"	M23053-12-228-C	14.22mm	10.13mm	0.64mm	1	Clear (CL)
7/16"	M23053-12-229-C	16.64mm	11.73mm	0.64mm	1	Clear (CL)
1/2"	M23053-12-230-C	19.05mm	13.31mm	0.64mm	1	Clear (CL)
5/8"	M23053-12-231-C	23.62mm	16.64mm	0.76mm	1	Clear (CL)
3/4"	M23053-12-232-C	28.58mm	19.96mm	0.89mm	1	Clear (CL)
7/8"	M23053-12-233-C	33.27mm	23.14mm	0.89mm	1	Clear (CL)
1"	M23053-12-234-C	38.10mm	26.31mm	0.89mm	1	Clear (CL)

- Shrink Temperature 650°F (343°C)
- Mil-I-DTL-23053/12
- Excellent Dielectric Strength
- Resistant to All Common Solvents, Acids, and Bases
- High Operating Temp. up to to 500°F (260°C)



Splice sleeving



Adhesive lining



Added waterproofing



Hot Fusion Tape

Techflex hot-melt adhesive tape works great in conjunction with our sleeving and heatshrink products. HFA has good adhesion to polyolefin, PET, PVC, copper, and nylon. Hot Fusion Tape is very flexible and can be field cut to fit your application. Use when extra adhesive may be needed, in areas between wire bundles for weatherproofing, or under heatshrink products not available with pre-coated dual wall adhesive. Tape activates easily when shrinking your tubing.

Nominal Size	Part #	Width	Thickness	Standard Spool Put-Ups		Available Colors	Lbs/100'
				Bulk Spool	Shop Spool		
2"	HFA2.00CL	1.97"	0.012"	100'	25'	Clear (CL)	1.16

1-973-300-9242
www.techflex.com