



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



MA260 CAT IV True RMS 200A AC Open Jaw Clamp Meter



Easy-to-use, one button, Auto Sense technology allows meter to recognize the input being measured and will automatically switch to the correct mode of operation. Its convenient Open Jaw design provides quick measurements in tight locations. True RMS provides accurate readings.

Features

- Smart Auto Sensing technology enables the meter to recognize the input and automatically switch to the correct mode of operation
- For AC Voltage, Auto Sense feature evaluates input signal and adjusts Input Impedance to eliminate effects of ghost voltages
- 0.6" (16mm) open jaw size
- True RMS for accurate readings of noisy, distorted or non-sinusoidal waveforms
- Built-in non-contact voltage detector with LED indicator
- 10,000 count backlit LCD display
- Smart Data Hold freezes the reading on the display and automatically changes if a new reading is larger than 50 counts
- Auto Power Off with disable
- Battery capacity (%) displayed on power-up
- Slim housing construction with built-in test lead holders
- Complete with test leads and two AAA batteries

Specifications	Range	Max Resolution	Basic Accuracy
AC Current	200A	0.1A	±3.0%
AC Voltage	1.3V to 1000V	0.1V	±0.9%
DC Voltage	2.1V to 1000V	0.1V	±0.3%
Non-contact Voltage (NCV)	80 to 1000V AC (50 to 60Hz)		
Resistance (Ω)	0 to 10k Ω	1 Ω	±0.9%
Input Impedance	6k Ω up to 30V; Increases to 420k Ω at 1000V		
Diode	0.4 to 0.8V	0.1V	±1.0%
Continuity	Beeper (25 Ω threshold)		
Dimensions	7.6 x 2.1 x 1.2" (193 x 54 x 31mm)		
Weight	9.9oz (280g)		

Ordering

MA260 CAT IV True RMS 200A AC Open Jaw Clamp Meter



UPC Code: 793950382622