imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!




Contact us


Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



MA3010 series







MECHATRONICS

(30 x 30 x 10 mm) 1.18 x 1.18 x 0.39 inches

Frame:

Protection:

Options:

Airflow:

 Construction:
 UL94V-0 PBT impeller & frame

 Bearing option:
 ball bearing or sleeve

 Connection:
 AWG 30, UL1007 lead wires

ball bearing or sleeve	Model No.	Rated Voltage	Operating Voltage	Current	Speed Air Volume		Max. Static Pressure (H20)		Sound Noise	Weight	
AWG 30, UL1007 lead wires	Model 110.	v	v	mA	RPM	M³/Min.	CFM	мм	INCH	dbA	g
ribbed	MA3010L	5	3 - 6.5	60	5,000	0.06	2.15	1.85	0.07	15	8
thermal	MA3010M	5	3 - 6.5	70	7,000	0.09	3.17	2.64	0.11	21	8
tachometer output signal	MA3010H	5	3 - 6.5	140	9,000	0.12	4.22	3.77	0.15	28	8
air intake over struts	MA3010L	12	7 - 13.8	40	5,000	0.06	2.15	1.85	0.07	15	8
-	MA3010M	12	7 - 13.8	70	7,000	0.09	3.17	2.64	0.11	21	8
	MA3010H	12	7 - 13.8	100	9,000	0.12	4.22	3.77	0.15	28	8



Cooling Simplified