



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



# MAC228A Series

## Sensitive Gate Triacs

### Silicon Bidirectional Thyristors

Designed primarily for industrial and consumer applications for full-wave control of AC loads such as appliance controls, heater controls, motor controls, and other power switching applications.

#### Features



- Sensitive Gate Triggering in 3 Modes for AC Triggering on Sinking Current Sources
- Four Mode Triggering for Drive Circuits that Source Current
- All Diffused and Glass-Passivated Junctions for Parameter Uniformity and Stability
- Small, Rugged, Thermowatt Construction for Low Thermal Resistance and High Heat Dissipation
- Center Gate Geometry for Uniform Current Spreading
- These Devices are Pb-Free and are RoHS Compliant



Expertise Applied | Answers Delivered


Littelfuse.com

**TRIACS**  
**8 AMPERES RMS**  
**200 – 800 VOLTS**



**TO-220**  
**CASE 221A**  
**STYLE 4**

#### MARKING DIAGRAM



xx = 4, 6, 8, or 10  
A = Assembly Location (Optional)\*  
Y = Year  
WW = Work Week  
G = Pb-Free Package

\* The Assembly Location code (A) is optional. In cases where the Assembly Location is stamped on the package the assembly code may be blank.

#### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 4 of this data sheet.

# MAC228A Series

## MAXIMUM RATINGS (T<sub>J</sub> = 25°C unless otherwise noted)

Characteristic	Symbol	Value	Unit
Peak Repetitive Off-State Voltage (Note 1) (T <sub>J</sub> = -40 to 110°C, Sine Wave, 50 to 60 Hz, Gate Open)	V <sub>DRM</sub> , V <sub>RRM</sub>	200 400 600 800	V
On-State RMS Current, (T <sub>C</sub> = 80°C) – Full Cycle Sine Wave 50 to 60 Hz	I <sub>T(RMS)</sub>	8.0	A
Peak Non-Repetitive Surge Current (One Full Cycle Sine Wave, 60 Hz, T <sub>J</sub> = 110°C)	I <sub>TSM</sub>	80	A
Circuit Fusing Considerations, (t = 8.3 ms)	I <sup>2</sup> t	26	A <sup>2</sup> s
Peak Gate Current, (t ≤ 2 μs, T <sub>C</sub> = 80°C)	I <sub>GM</sub>	±2.0	A
Peak Gate Voltage, (t ≤ 2 μs, T <sub>C</sub> = 80°C)	V <sub>GM</sub>	±10	V
Peak Gate Power, (t ≤ 2 μs, T <sub>C</sub> = 80°C)	P <sub>GM</sub>	20	W
Average Gate Power, (t ≤ 8.3 ms, T <sub>C</sub> = 80°C)	P <sub>G(AV)</sub>	0.5	W
Operating Junction Temperature Range	T <sub>J</sub>	-40 to 110	°C
Storage Temperature Range	T <sub>stg</sub>	-40 to 150	°C
Mounting Torque	-	8.0	in lb

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

- V<sub>DRM</sub> and V<sub>RRM</sub> for all types can be applied on a continuous basis. Blocking voltages shall not be tested with a constant current source such that the voltage ratings of the devices are exceeded.

## THERMAL CHARACTERISTICS

Characteristic	Symbol	Value	Unit
Thermal Resistance – Junction-to-Case	R <sub>θJC</sub>	2.0	°C/W
Thermal Resistance – Junction-to-Ambient	R <sub>θJA</sub>	62.5	°C/W
Maximum Lead Temperature for Soldering Purposes 1/8" from Case for 10 Seconds	T <sub>L</sub>	260	°C

## ELECTRICAL CHARACTERISTICS (T<sub>C</sub> = 25°C unless otherwise noted; Electricals apply in both directions)

Characteristic	Symbol	Min	Typ	Max	Unit
----------------	--------	-----	-----	-----	------

### OFF CHARACTERISTICS

Peak Repetitive Blocking Current, (V <sub>D</sub> = Rated V <sub>DRM</sub> , V <sub>RRM</sub> ; Gate Open) T <sub>J</sub> = 25°C T <sub>J</sub> = 110°C	I <sub>DRM</sub> , I <sub>RRM</sub>	-	-	10 2.0	μA mA
--	--	---	---	-----------	----------

### ON CHARACTERISTICS

Peak On-State Voltage, (I <sub>TM</sub> = ±11 A Peak, Pulse Width ≤ 2 ms, Duty Cycle ≤ 2%)	V <sub>TM</sub>	-	-	1.8	V
Gate Trigger Current (Continuous DC), (V <sub>D</sub> = 12 V, R <sub>L</sub> = 100 Ω) MT2(+), G(+); MT2(+), G(-); MT2(-), G(-) MT2(-), G(+)	I <sub>GT</sub>	-	-	5.0 10	mA
Gate Trigger Voltage (Continuous DC), (V <sub>D</sub> = 12 V, R <sub>L</sub> = 100 Ω) MT2(+), G(+); MT2(+), G(-); MT2(-), G(-) MT2(-), G(+)	V <sub>GT</sub>	-	-	2.0 2.5	V
Gate Non-Trigger Voltage (Continuous DC), (V <sub>D</sub> = 12 V, T <sub>C</sub> = 110°C, R <sub>L</sub> = 100 Ω) All Four Quadrants	V <sub>GD</sub>	0.2	-	-	V
Holding Current, (V <sub>D</sub> = 12 Vdc, Initiating Current = ±200 mA, Gate Open)	I <sub>H</sub>	-	-	15	mA
Gate-Controlled Turn-On Time, (V <sub>D</sub> = Rated V <sub>DRM</sub> , I <sub>TM</sub> = 16 A Peak, I <sub>G</sub> = 30 mA)	t <sub>gt</sub>	-	1.5	-	μs

### DYNAMIC CHARACTERISTICS


Critical Rate of Rise of Off-State Voltage, (V <sub>D</sub> = Rated V <sub>DRM</sub> , Exponential Waveform, T <sub>C</sub> = 110°C)	dv/dt	-	25	-	V/μs
Critical Rate of Rise of Commutation Voltage, (V <sub>D</sub> = Rated V <sub>DRM</sub> , I <sub>TM</sub> = 11.3 A, Commutating di/dt = 4.1 A/ms, Gate Unenergized, T <sub>C</sub> = 80°C)	dv/dt(c)	-	5.0	-	V/μs

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.


# MAC228A Series

## Voltage Current Characteristic of Triacs (Bidirectional Device)

Symbol	Parameter
$V_{DRM}$	Peak Repetitive Forward Off State Voltage
$I_{DRM}$	Peak Forward Blocking Current
$V_{RRM}$	Peak Repetitive Reverse Off State Voltage
$I_{RRM}$	Peak Reverse Blocking Current
$V_{TM}$	Maximum On State Voltage
$I_H$	Holding Current




### Quadrant Definitions for a Triac




All polarities are referenced to MT1.  
With in-phase signals (using standard AC lines) quadrants I and III are used.

## MAC228A Series



**Figure 1. RMS Current Derating**



**Figure 2. On-State Power Dissipation**


### ORDERING INFORMATION

Device	Package	Shipping
MAC228A4G	TO-220 (Pb-Free)	500 Units / Bulk
MAC228A6G	TO-220 (Pb-Free)	500 Units / Bulk
MAC228A6TG	TO-220 (Pb-Free)	50 Units / Rail
MAC228A8G	TO-220 (Pb-Free)	500 Units / Bulk
MAC228A8TG	TO-220 (Pb-Free)	50 Units / Rail
MAC228A10G	TO-220 (Pb-Free)	500 Units / Bulk

# MAC228A Series

## PACKAGE DIMENSIONS

TO-220  
CASE 221A-09  
ISSUE AH



**NOTES:**

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. DIMENSION Z DEFINES A ZONE WHERE ALL BODY AND LEAD IRREGULARITIES ARE ALLOWED.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.570	0.620	14.48	15.75
B	0.380	0.415	9.66	10.53
C	0.160	0.190	4.07	4.83
D	0.025	0.038	0.64	0.96
F	0.142	0.161	3.61	4.09
G	0.095	0.105	2.42	2.66
H	0.110	0.161	2.80	4.10
J	0.014	0.024	0.36	0.61
K	0.500	0.562	12.70	14.27
L	0.045	0.060	1.15	1.52
N	0.190	0.210	4.83	5.33
Q	0.100	0.120	2.54	3.04
R	0.080	0.110	2.04	2.79
S	0.045	0.055	1.15	1.39
T	0.235	0.255	5.97	6.47
U	0.000	0.050	0.00	1.27
V	0.045	---	1.15	---
Z	---	0.080	---	2.04

**STYLE 4:**

- PIN 1. MAIN TERMINAL 1
- PIN 2. MAIN TERMINAL 2
- PIN 3. GATE
- PIN 4. MAIN TERMINAL 2

Littelfuse products are not designed for, and shall not be used for, any purpose (including, without limitation, automotive, military, aerospace, medical, life-saving, life-sustaining or nuclear facility applications, devices intended for surgical implant into the body, or any other application in which the failure or lack of desired operation of the product may result in personal injury, death, or property damage) other than those expressly set forth in applicable Littelfuse product documentation. Warranties granted by Littelfuse shall be deemed void for products used for any purpose not expressly set forth in applicable Littelfuse documentation. Littelfuse shall not be liable for any claims or damages arising out of products used in applications not expressly intended by Littelfuse as set forth in applicable Littelfuse documentation. The sale and use of Littelfuse products is subject to Littelfuse Terms and Conditions of Sale, unless otherwise agreed by Littelfuse.

Littelfuse.com