



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




## Features

- Surface Mount
- 3 way 0 degree
- 260°C Reflow Compatible
- RoHS Compliant, lead free
- Available on Tape and Reel


## Description

The MAPD-011026 is a 3 Way 0° power divider in a low cost, surface mount package.

Ideally suited for high volume CATV applications.



## Functional Schematic



## Ordering Information

Part Number	Description
MAPD-011026	500 pc reel
MAPD-011026-TB	Sample Test Board

## Pin Configuration

Pin No.	Pin Name
1	Output Port 1
2,3,6,7	Ground
4	Output Port 2
5	Output Port 3
8	Input

\* Restrictions on Hazardous Substances, European Union Directive 2011/65/EU.

## 3-Way 0° Power Divider 5 - 300 MHz

Rev. V2

Electrical Specifications:  $T_A = 25^\circ\text{C}$ ,  $Z_0 = 75 \Omega$ ,  $P_{in} = 0 \text{ dBm}$

Parameter	Frequency	Units	Min.	Typ.	Max.
Insertion Loss (Ref value: 4.77 dB)	5 - 204 MHz 204 - 300 MHz	dB	-	5.1 5.2	5.2 5.3
Isolation	5 - 200 MHz 200 - 300 MHz	dB	25 22	27 23	—
Amplitude Balance	5 - 204 MHz 204 - 300 MHz	dB	—	0.04 0.10	0.1 0.2
Phase Balance	5 - 204 MHz 204 - 300 MHz	deg.	—	0.35 0.65	0.9 1.5
Input Return Loss	5 - 204 MHz 204 - 300 MHz	dB	31 26	34 30	—
Output Return Loss	5 - 204 MHz 204 - 300 MHz	dB	23 20	26 23	—

### Absolute Maximum Ratings<sup>4,5</sup>

Parameter	Absolute Maximum
RF Input Power	0.5 W
DC Current	500 mA
Operating Temperature	-40°C to +85°C

4. Exceeding any one or combination of these limits may cause permanent damage to this device.
5. MACOM does not recommend sustained operation near these survivability limits.
6. Full temperature plots available on request.







### Handling Procedures

Please observe the following precautions to avoid damage:


### Static Sensitivity

These electronic devices are sensitive to electrostatic discharge (ESD) and can be damaged by static electricity. Proper ESD control techniques should be used when handling these devices.


## Typical Performance Curves



## Recommended PCB Layout



## Outline Drawing



## Tape & Reel Information

Item	Dimension
Ao	10.26 mm +/-0.1 mm
Bo	13.46 mm +/-0.1 mm
Ko	6.10 mm +/-0.1 mm
W	24.00 mm +/-0.3 mm
P1	16.00 mm +/-0.1 mm
Orientation	F2
Reference Application Note ANI-019 for orientation	

M/A-COM Technology Solutions Inc. All rights reserved.

Information in this document is provided in connection with M/A-COM Technology Solutions Inc ("MACOM") products. These materials are provided by MACOM as a service to its customers and may be used for informational purposes only. Except as provided in MACOM's Terms and Conditions of Sale for such products or in any separate agreement related to this document, MACOM assumes no liability whatsoever. MACOM assumes no responsibility for errors or omissions in these materials. MACOM may make changes to specifications and product descriptions at any time, without notice. MACOM makes no commitment to update the information and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to its specifications and product descriptions. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document.

THESE MATERIALS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, RELATING TO SALE AND/OR USE OF MACOM PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, CONSEQUENTIAL OR INCIDENTAL DAMAGES, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. MACOM FURTHER DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. MACOM SHALL NOT BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS, WHICH MAY RESULT FROM THE USE OF THESE MATERIALS.

MACOM products are not intended for use in medical, lifesaving or life sustaining applications. MACOM customers using or selling MACOM products for use in such applications do so at their own risk and agree to fully indemnify MACOM for any damages resulting from such improper use or sale.