



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





# Dual-Output, 3-Phase + 1 Phase Quick-PWM Controller for VR12/IMVP-7

MAX17039

## General Description

The MAX17039 is a dual-output, step-down, constant-on-time controller for VR12/IMVP-7 CPU core supplies. The controller consists of two high-current-switching power supplies for the CPU and GPU cores. The CPU regulator (regulator A) is a three-phase constant-on-time architecture. The optional 3rd phase is configured with an external MAX8791 or MAX17491 driver. The second GPU regulator (regulator B) is also a constant-on-time architecture with only single phase.

Both regulators A and B include true differential voltage and current sensing to improve load-line and current-limit accuracy. Switching frequencies are independently programmable, allowing 100kHz to 600kHz per phase operation. Output overvoltage protection (OVP), under-voltage protection (UVP), and thermal protection ensure effective and highly reliable operation. When any of these protection features detect a fault, the controller shuts down both channels.

Regulator A includes transient-phase overlap, which speeds up the response time, reducing the total output capacitance. Regulator A also includes active overshoot suppression to further reduce the required output decoupling capacitance.

Both controllers are fully compliant with Intel's VR12/IMVP-7 serial VID communication and control specifications. CPU and GPU outputs are controlled independently by writing the appropriate data into a function-mapped register file. A slew-rate controller allows controlled transitions between VID codes, controlled soft-start. The SVID interface also allows each regulator to be individually set into a low-power pulse-skipping state. Individual phases can be shut down based on the processors' operating conditions to optimize efficiency. The MAX17039 is available in a lead-free, 56-pin, 7mm x 7mm TQFN package.

## Applications

VR12/IMVP-7 CPU Core Power Supplies  
Voltage-Positioned Step-Down Converters  
Notebooks/Desktops/Servers

**Pin Configuration appears at end of data sheet.**

*Quick-PWM is a trademark of Maxim Integrated Products, Inc.*

## Features

- ◆ Supports all Required IMVP-7 Functions
- ◆ Three-Phase Quick-PWM™ CPU Core (Regulator A)
  - Two Internal Drivers and One External Driver
  - Active Overshoot Suppression
  - Transient-Phase Overlap Mode
  - Dynamic Phase Selection
  - Phase-Good Fault Detection (Internal)
- ◆ One-Phase Quick-PWM with Internal Driver (Regulator B)
- ◆ Intel VR12/IMVP-7-Compliant 25MHz Serial Interface
- ◆ 8-Bit IMVP-7 DAC
- ◆ ±0.4% V<sub>OUT</sub> Accuracy Over Line, Load, and Temperature
- ◆ Active Voltage Positioning with Programmable Gain
- ◆ Accurate Lossless Current Balance
- ◆ Accurate Droop and Current Limit
- ◆ Remote Output and Ground Sense
- ◆ Power-Good Window Comparators (VR\_\_READY)
- ◆ Output Current Monitors (IMON\_)
- ◆ 4.5V to 26V Battery-Input Range
- ◆ Drives Large Synchronous Rectifier MOSFETs
- ◆ Programmable 100kHz to 600kHz Switching Frequency
- ◆ External Thermal-Fault Detection (VR\_HOT#) Output
- ◆ Overvoltage, Undervoltage, and Thermal-Fault Protection
- ◆ Soft-Start and Soft-Shutdown
- ◆ Integrated Boost Switches
- ◆ Low-Profile 56-Lead TQFN Package

## Ordering Information

PART	TEMP RANGE	PIN-PACKAGE	FEATURE
MAX17039GTN+	-40°C to +105°C	56 TQFN	3-phase + 1 phase (1 external driver)

+Denotes a lead(Pb)-free/RoHS-compliant package.

