



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## Specification Sheet

Part Number: MBT20S-S



Stainless Steel Tie, 20.5" Long, 202lb Tensile Strength, SS304, Metal, 100/pkg

<b>Article Number</b>	111-93208
<b>Type</b>	MBT20SS
<b>Color</b>	Metal (ML)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• 304 grade stainless steel offers excellent resistance to corrosion, weather and chemical resistance.</li><li>• Self locking, ball bearing mechanism assures high tensile strength and easy insertion.</li><li>• Fully enclosed head does not allow dirt or grit to interfere with locking mechanism.</li><li>• High tensile strength for dependability and safety on heavy duty applications.</li></ul>
<b>Quantity Per</b>	bag
<b>Product Description</b>	HellermannTyton's stainless steel ties are designed with a ball bearing locking mechanism to assure high tensile strength and easy insertion when securing hoses, cables, pipes and more. Available in 304 or 316 grades of stainless steel, providing protection when used in corrosive environments, fire resistance and temperature extremes.

<b>Short Description</b>	Stainless Steel Tie, 20.5" Long, 202lb Tensile Strength, SS304, Metal, 100/pkg
<b>Global Part Name</b>	MBT20SS-SS304-ML
<b>Minimum Tensile Strength (Imperial)</b>	202.0
<b>Minimum Tensile Strength (Metric)</b>	900.0
<b>Length L (Imperial)</b>	20.5
<b>Length L (Metric)</b>	521.0
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	ball bearing lock
<b>Variant</b>	No Serration
<b>Width W (Imperial)</b>	0.18
<b>Width W (Metric)</b>	4.6
<b>Bundle Diameter Min (Imperial)</b>	0.67
<b>Bundle Diameter Min (Metric)</b>	17.0
<b>Bundle Diameter Max (Imperial)</b>	6.0
<b>Bundle Diameter Max (Metric)</b>	152.0
<b>Thickness T (Imperial)</b>	0.01

**Thickness T (Metric)** 0.3

**Material** Stainless Steel (SS304)

**Material Shortcut** SS304

**Flammability** Non-Burning

**Halogen free** Yes

**Operating Temperature (Metric)** -112°F to +1000°F (-80°C to +538°C)

**Reach Complaint(Article 33)** Yes

**ROHS Complaint** Yes

**Package Quantity(Imperial)** 100

**Package Quantity (Metric)** 100

**Customs Number** 7326908595

**Content Unit(BMEcat)** pcs.

**Weight (Metric)** 5.75

