## imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





## This document was generated on 04/08/2013 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Status:ActiOverview:PremiDescription:0.50m	66-0148 ive o-Flex™ FFC and Etched Polyimide Jumpers nm Pitch Premo-Flex™ FFC Jumper, Opposite Side Contacts (Type its, 0.127m Cable Length, Cable Thickness 0.12mm, Tin (Sn) Platir	
Documents: Drawing (PDF) Product Specification PS-151 General	Packaging Specification PK-15166-001 66-001 (PDF) RoHS Certificate of Compliance (PDF)	(PDF) image - Reference only
Product Family Series Comments Crimp Quality Equipment Overview Product Name UPC	Cable <u>15166</u> Contacts on opposite sides, Type D Yes <u>Premo-Flex™FFC and Etched Polyimide</u> Premo-Flex™FFC Jumper 884982846401	EU RoHS ELV and RoHS Compliant
Physical Cable Length Circuits (Loaded) Circuits (maximum) Net Weight Packaging Type Pitch - Termination Interface Temperature Range - Operat Wire Size AWG Wire/Cable Type	0.127m 14 14 1.000/g Bag 0.50mm -40°C to +105°C N/A Flat Flex Cable	Need more information on product environmental compliance?Email productcompliance@molex.comFor a multiple part number RoHS Certificate Compliance, click herePlease visit the Contact Us section for any non-product compliance questions.
Electrical Current - Maximum per Conta Voltage - Maximum Material Info	act 0.5A 60V AC	Search Parts in this Series <u>15166</u> Series Use With
<b>Reference - Drawing N</b> Packaging Specification Product Specification Sales Drawing	umbers PK-15166-001 PS-15166-001 SD-15166-001	www.molex.com/product/ffcfpc_th.html

This document was generated on 04/08/2013 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION