

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



### Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China








### **Spec Sheet**

# Multilayer Common Mode Choke Coils

# MCF08062E300-T



#### Features

- Item Summary  $30\,\Omega,\,0.15\,\text{A},\,2\,\text{GHz},\,0.85\text{x}0.65\text{x}0.45\text{mm}$
- Lifecycle Stage
  - Mass Production
- Standard packaging quantity (minimum)
  Taping 10000pcs

### ■ Products characteristics table

No. of Lines	2
Common Mode Impedance	$30~\Omega \pm 25~\%$ at $100 MHz$
Case Size (EIA/JIS)	SMD/0806
Cutoff Frequency (typ)	2 GHz
DC Resistance (max)	1.5 Ω
Rated Current (max)	0.15 A
Rated Voltage (max)	5 V
Operating Temp. Range	-40 to +85 ℃
Insulation Resistance (min)	100 ΜΩ
RoHS2 Compliance (10 subst.)	Yes
REACH Compliance (173 subst.)	Yes
Halogen Free	Yes
Soldering	Reflow

### External Dimensions

Dimension A	0.85 ±0.05 mm
Dimension B	0.65 ±0.05 mm
Dimension C	0.4 ±0.05 mm
Dimension E1	0.27 ±0.1 mm
Dimension E2	0.2 +0.05/-0.1 mm
Dimension P	0.5 ±0.10 mm

2017.04.30