

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









## **Audio Coupling**

### Miniature Encapsulated Transformer

## **MET-09-T**

#### **Description:**

Triad's high reliability audio transformers provide the durability and precision required in today's demanding designs. These transformers are available for a wide variety of applications.

# MET-09-T SEC. 275110 SIXO 275120 WCT TFSS21ZZ 4 8 8

#### Electrical Specifications (@20C)

	Power	Matching Impedance		Max. Ma DC	DC Resi	stance (Ω)	Overall
	level (mW)	Primary	Secondary	Unbalance	Primary	Secondary	Turns
				in Primary			Ratio
	40	10ΚΩ СТ	10KΩ CT	1.0	1000	1300	1.0:1.0


Frequency Response: ± 2.0 DB, at 300 Hz to 100K Hz (1 KHz Ref.)

Longitudinal Balance: 60dB Min @ 1 KHz

**Pri-Sec Hipot test (Pri-Sec):** 500 VRMS for 1 sec.


#### Construction:

Plug-in terminals are precision spaced to provide fixed mounting centers. Epoxy molded case includes a .020" recess for ease of solder inspection. Leads are Tin plated 0.020" in diameter.



**RoHS Compliance:** As of manufacturing date February 2005, all standard products meet the requirements of 2011/65/EU, known as the RoHS initiative.

\*Upon printing, this document is considered "uncontrolled". Please contact Triad Magnetics website for the most current version. For soldering and washing information please see http://www.triadmagnetics.com/faq.html



Web: www.TriadMagnetics.com Phone 951-277-0757 Fax 951-277-2757

460 Harley Knox Blvd. Perris, California 92571

Publish Date: June 3, 2016