

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







MF0 FCP2 U1

Flip chip package

Rev. 3.1 — 8 February 2007 073631

Product data sheet

1. General description

1.1 Scope

This document specifies the products MF0FCP2U10 and MF0FCP2U11:

- The MF0FCP2U10/DH is the integrated circuit MF0ICU10 in the package SOT732CA2.
- The MF0FCP2U11/DH is the integrated circuit MF0ICU11 in the package SOT732CA2.

Therefore this document encompasses all information not covered by the specification of the package and/or the functional specification of the integrated circuit:

- Detailed information on the package is given in the "specification FCP2 flip chip package".
- Functionality of the integrated circuit is described in the functional specification MF0 IC U1.

2. Features

3. Applications

4. Ordering information

Table 1. Ordering information

Type number	Package				
	Name	Description	Ordering Code		
MF0FCP2U10/DH		Hot laminated transport tape	12NC: 9352 725 94118		
MF0FCP2U11/DH		Hot laminated transport tape	12NC: 9352 725 96118		

5. Functional description

5.1 Integrated circuit

Functionality of the integrated circuit is described in the "Functional specification MF0 IC U1x".



6. Limiting values

Table 2. Limiting values [1][2][3][4]

In accordance with the Absolute Maximum Rating System(IEC 134)

Symbol	Parameter	Conditions		Min	Max	Unit
T_{OP}	Operating temperature			-25	70	°C
I _{IN}	Input Current				30	mA
T _{STOR}	Storage temperature		<u>[5]</u>			
V_{ESD}	ESD Voltage Level	MIL883D, human body	[6]	2		kV_{peak}

- [1] Stresses above one or more of the limiting values may cause permanent damage to the device
- [2] These are stress ratings only. Operation of the device at these or any other conditions above those given in the Characteristics section of the specification is not implied
- [3] Exposure to limiting values for extended periods may affect device reliability
- [4] This product includes circuitry specifically designed for the protection of its internal devices from the damaging effects of excessive static charge. Nonetheless, it is suggested that conventional precautions be taken to avoid applying greater than the rated maxima
- [5] Storage & Processing Temperature: refer to Package Specification "FCP2 Flip Chip Package"
- [6] MIL Standard 883-C method 3015; Human body model: C = 100 pF, $R = 1.5 \text{ k}\Omega$

7. Characteristics

7.1 Electrical characteristics

 $T_{iop} = -25 \text{ to } +70^{\circ}\text{C}$

Table 3. Characteristics [1][2][3][4]

Symbol	Parameter	Conditions		Min	Туре	Max	Unit
F_{IN}	Input Frequency			-	13.56	-	MHz
C _{IN}	Input capacitance between LA - LB for the integrated circuit MF0ICU10.	22°C, Cp-D, 13.56 MHz, 2 V	<u>[5]</u>	14.85	17	20.13	pF
C _{IN}	Input capacitance between LA - LB for the integrated circuit MF0ICU11.	22°C, Cp-D, 13.56 MHz, 2 V	<u>[5]</u>	42.5	50	57.5	pF
t _W	EEPROM write time			-	3.8	-	ms
t _{RET}	EEPROM data retention	$T_{amb} \leq 55^{\circ}C$		5	-	-	years
N _{WE}	EEPROM write endurance			10000	-	-	cycles

- [1] Stresses above one or more of the limiting values may cause permanent damage to the device
- [2] These are stress ratings only. Operation of the device at these or any other conditions above those given in the Characteristics section of the specification is not implied
- [3] Exposure to limiting values for extended periods may affect device reliability
- [4] Typical ratings are not guaranteed. These values listed are at room temperature
- [5] Measured with an HP4258 LCR meter at 13.56 MHz

073631 © NXP B.V. 2007. All rights reserved.

3 of 5

8. Support information

For additional information, please visit: http://www.nxp.com

9. Revision history

Table 4. Revision history

Document ID	Release date	Data sheet status	Change notice	Supersedes
073610	June 2002	Initial version		1.0
073620	November 2002	Preliminary version		2.0
073630	October 2004	Product data sheet		3.0
073631	8 February 2007	Product data sheet		3.1
Modifications:		f this data sheet has been rede NXP Semiconductors.	esigned to comply w	ith the new identity
	 Legal texts h 	ave been adapted to the new o	company name whe	re appropriate.

10. Legal information

10.1 Data sheet status

Document status[1][2]	Product status[3]	Definition
Objective [short] data sheet	Development	This document contains data from the objective specification for product development.
Preliminary [short] data sheet	Qualification	This document contains data from the preliminary specification.
Product [short] data sheet	Production	This document contains the product specification.

- [1] Please consult the most recently issued document before initiating or completing a design.
- [2] The term 'short data sheet' is explained in section "Definitions"
- [3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL http://www.nxp.com.

10.2 Definitions

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. NXP Semiconductors does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

Short data sheet — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local NXP Semiconductors sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

10.3 Disclaimers

General — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

Right to make changes — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — NXP Semiconductors products are not designed, authorized or warranted to be suitable for use in medical, military, aircraft, space or life support equipment, nor in applications where failure or malfunction of a NXP Semiconductors product can reasonably be expected to

result in personal injury, death or severe property or environmental damage. NXP Semiconductors accepts no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) may cause permanent damage to the device. Limiting values are stress ratings only and operation of the device at these or any other conditions above those given in the Characteristics sections of this document is not implied. Exposure to limiting values for extended periods may affect device reliability.

Terms and conditions of sale — NXP Semiconductors products are sold subject to the general terms and conditions of commercial sale, as published at http://www.nxp.com/profile/terms, including those pertaining to warranty, intellectual property rights infringement and limitation of liability, unless explicitly otherwise agreed to in writing by NXP Semiconductors. In case of any inconsistency or conflict between information in this document and such terms and conditions, the latter will prevail.

No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

10.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

Mifare — is a trademark of NXP B.V.

11. Contact information

For additional information, please visit: http://www.nxp.com

For sales office addresses, send an email to: salesaddresses@nxp.com

12. Tables

Table 1.	Ordering information1	Table 3.	Characteristics [1][2][3][4]
Table 2.	Limiting values[1][2][3][4]	Table 4.	Revision history

13. Contents

1	General description
1.1	Scope
2	Features
3	Applications
4	Ordering information 1
5	Functional description 1
5.1	Integrated Circuit 1
6	Limiting values
7	Characteristics
7.1	Electrical Characteristics
8	Support information 3
9	Revision history 3
10	Legal information 4
10.1	Data sheet status 4
10.2	Definitions4
10.3	Disclaimers 4
10.4	Trademarks4
11	Contact information 4
12	Tables
13	Contents

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.





© NXP B.V. 2007. All rights reserved.