mail

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Flexible Ferrite Sheets For NFC & Wireless Charging MHLL Series



FEATURES VROHS ®

- Flexible ferrite sheets for 13.56 MHz NFC, RFID application & wireless charging application
- Made by thin, high permeability sintered ferrite with PET film and adhesive tape
- Standard ferrite layer thickness 0.05mm,0.1mm and 0.2mm
- Custom size or thickness available upon request
- Operating temperature -40 $^\circ\!\mathrm{C}$ to 85 $^\circ\!\mathrm{C}$

SHAPES AND DIMENSIONS

RoHS compliant

APPLICATIONS

- NFC antenna for mobile phones
- NFC antenna for automobile
- NFC or RFID antenna for security & access control system
- Wireless charging for mobile phones and battery powered handheld electronic devices
- NFC or RFID read/write devices, improved read distance
- EMI suppression for IC or IC circuitry

PART	A mm	B mm	C mm	D mm MAX				
NUMBER	(inches)	(inches)	(inches)	(inches)				
	50	40	0.20	0.35				
WINLL3040-000	(1.969)	(1.575)	(0.008)	(0.014)				
MHLL5040-200	50	40	0.10	0.20				
	(1.969)	(1.575)	(0.004)	(0.008)				
MHLL6060-300	60	60	0.05	0.09				
	(2.362)	(2.362)	(0.002)	(0.004)				
MHLL12060-000	120	60	0.20	0.35				
	(4.724)	(2.362)	(0.008)	(0.014)				
MHLL12060-200	120	60	0.10	0.20				
	(4.724)	(2.362)	(0.004)	(0.008)				



MHLL	12060	-	000	
Material Code	Part Size Code		Thickness Code	
		Catalog or Custom Information		

USA: +1.423.308.1690 Europe: +42.0.4885.7511.1 Asia: +86.757.2563.8860

MCP-DS-MHLL SHEET REV1.2 0814

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user, Laird Technologies makes no warrantize as to the fitness, merchantability, suitability or non-infringement of any Laird Technologies materials or products for any specific or general uses. Laird Technologies materials or technologies. The Laird Technologies shall not be liable for incidental or consequential damages of any Kind. All Laird Technologies is not be liable for incidental or consequential damages of any Kind. All Laird Technologies is not be liable for incidental or consequential damages of any Kind. All Laird Technologies is full exchanged as the start are trademarks or registered trademarks of Laird Technologies, Inc. and filiate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Yendemarks of Laird Technologies, Inc. and filiate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.



Flexible Ferrite Sheets For NFC & Wireless Charging MHLL Series

MATERIAL SPECIFICATIONS

Property	MHLL Series	
Real Permeability, $\mu'@$ 13.56MHz, 0.1V	130 <u>+</u> 20%	
Imaginary Permeability, µ"@13.56MHz, 0.1V	5 max	
Operating Temperature, °C	-40°C ~ +85°C	

TYPICAL ELECTRICAL CHARACTERISTICS



USA: +1.423.308.1690 Europe: +42.0.4885.7511.1 Asia: +86.757.2563.8860

MCP-DS-MHLL SHEET REV1.2 0814

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user. Laird Technologies makes no warrantize as to the fitness, mechantability, suitability or non- infringement of any Laird Technologies materials or products for any specific or general uses. Laird Technologies in the Laird for incidental or consequential damages of any kind. All Laird Technologies shall use Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies shall use the little shall be used to the liable for incidental or consequential damages of any kind. All Laird Technologies shall use Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies shall have a copy of which will be furnished upon request. © Copyright 2013 Laird Technologies, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Laird are trademarks or registered trademarks of Laird Technologies, inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.