



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Raychem Corporation  
 300 Constitution Drive  
 Menlo Park, CA 94025  
 800-227-4856  
 FAX 800-227-4866

**Raychem**  
**PolySwitch®**  
**PTC Devices**  
 Overcurrent Protection Device

**PRODUCT: microSMD035**

DOCUMENT: SCD 24367  
 PCN: 672499  
 REV LETTER: C  
 REV DATE: JULY 23, 1999  
 PAGE NO.: 1 OF 1


**Specification Status: RELEASED**

**Maximum Electrical Rating**

**Voltage: 6.0V<sub>DC</sub>**  
**Current: 40A**

**Notes:**

1. All terminations are tin/lead plated.
2. Devices can be wave soldered.
3. Drawing not to scale



**Marking:**



PART IDENTIFICATION

MANUFACTURER'S MARK

**TABLE I. DIMENSIONS:**

	A		B		C		D	E
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MIN
mm	3.00	3.43	2.35	2.80	0.38	0.62	0.30	0.25
in:	0.118	0.135	0.092	0.110	0.015	0.025	0.012	0.010

**TABLE II. PERFORMANCE RATINGS:**

IHOLD ** RATED CURRENT	HOLD CURRENT AT TEMPERATURE**				TIME TO TRIP **	RESISTANCE VALUES		** TRIPPED-STATE POWER DISSIPATION
	AMPERES AT 20°C HOLD	AMPERES AT 0°C HOLD	AMPERES AT 20°C HOLD	AMPERES AT 60°C HOLD		OHMS AT 20°C		
0.35	0.40	0.35	0.75	0.24	0.2	0.32	1.30	0.8

\* Maximum resistance is measured 1 hour after reflow.

\*\*Values specified were determined using PCB's with 0.030"X1.5 ounce copper traces.

Reference Documents: PS300, E. N. SMD1.0x

Precedence: This specification takes precedence over documents referenced herein.

Effectivity: Reference documents shall be the issue in effect on the date of invitation for bid.

CAUTION: Operation beyond the rated voltage or current may result in rupture, electrical arcing or flame.