imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





PolySwitch® PTC Devices

Overcurrent Protection Device

PRODUCT: microSMD110F

DOCUMENT: SCD25059 **REV LETTER: I REV DATE: JULY 26, 2016** PAGE NO.: 1 OF 2

Specification Status: Released

Maximum Electrical Rating Voltage: 6VDC Short Circuit Current: 40A

Notes:

1. All terminations are tin plated.

2. Drawing not to scale

Marking:






TABLE I. DIMENSIONS:										
	Α		В		C		D		E	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	
mm:	3.00	3.43	0.28	0.48	2.35	2.80	0.25	0.75	0.076	
in:	(0.118)	(0.135)	(0.011)	(0.019)	(0.092)	(0.110)	(0.010)	(0.030)	(0.003)	

TABLE II. PERFORMANCE RATINGS:

MANUFACTURER'S MARK

CI	JRRENT I	RATING	S**		TIME TO TRIP**	RESISTANCE VALUES		TRIPPED-STATE POWER DISSIPATION**	
AMPERES AT 0°C		AMPERES AT 20°C		ERES 60°C	SECONDS AT 20°C, 8A	OHMS AT 20°C		WATTS AT 20°C, 6V	
HOLD TRIP	HOLD	TRIP	AT HOLD		MAX	MIN	MAX*	MAX	
1.26 2.52	1.10	2.20	0.80	1.60	0.2	0.07	0.21	0.8	

*Maximum resistance is measured 1 hour after reflow.

** Values specified were determined using PCB's with 0.030"X1.5 ounce copper traces.

Agency Recognition:	UL, CSA, TÜV
Reference Documents:	PS300
Precedence:	This specification takes precedence over documents referenced herein.
Effectivity:	Reference documents shall be the issue in effect on the date of invitation for bid.
CAUTION:	Operation beyond the rated voltage or current may result in rupture, electrical arcing or flame.

Materials Information





PolySwitch® PTC Devices Overcurrent Protection Device

PRODUCT: microSMD110F

DOCUMENT: SCD25059 REV LETTER: I REV DATE:JULY 26, 2016 PAGE NO.: 2 OF 2

Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littlefuse products are not designed for, and shall not be used for, any purpose (including, without limitation, military, aerospace, medical, lifesaving, life-sustaining or nuclear facility applications, devices intended for surgical implant into the body, or any other application in which the failure or lack of desired operation of the product may result in personal injury, death, or property damage) other than those expressly set forth in applicable Littlefuse product documentation. Warranties granted by Littlefuse shall be deemed void for products used for any purpose not expressly set forth in applicable Littlefuse documentation. Littlefuse shall not be liable for any claims or damages arising out of products used in applications not expressly intended by Littlefuse as set forth in applicable Littlefuse documentation. The sale and use of Littlefuse products is subject to Littlefuse Terms and Conditions of Sale, unless otherwise agreed by Littlefuse.