

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Riverdi Display 2.8"

PID: MIKROE-2156

Weight: 73 g

Condition: New product

A high-quality cost-effective **2.83" TFT display** module suitable for use in consumer or industrial applications, well integrated with MikroElektronika tools.





The **240x320px** screen is driven by an **FT800** graphic controller which is supported in Visual TFT, the GUI design tool for rapid development of user interfaces.

This model doesn't have a touchscreen layer which results in increased brightness – 300 cd/m2. The addition of anti-glare surface treatment makes further increases clarity.

The connector uses a **I2C/SPI** interface. To use it with various MikroElektronika hardware, a Riverdi click adapter board is available (interface between the connector on the display and a mikroBUSTM socket).

• Specification

Display size	2.8"
Resolution	320x240px
Graphic controller	FT800
Brightness	300 cd/m2
Touch Screen	None
Interface	I2C or SPI
Power Supply	2.8V