

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Riverdi Display 2.8" Res

PID: MIKROE-2157

Weight: 70 g

Condition: New product

A high-quality cost-effective **2.8" TFT display** with a resistive touch screen. Easy to integrate with MikroElektronika development tools.



The **240x320px** screen is driven by an **FT800** graphic controller which is supported in <u>Visual</u> TFT, the GUI design tool for rapid development of user interfaces.

Resistive touchscreens have a higher resistance to dust and water compared to capacitive screens. They can also be used with a gloved finger. Those two features make them a better option for applications where a more robust user interface is required.

The connector uses an **I2C/SPI** interface. To use it with various MikroElektronika hardware, a <u>Riverdi click</u> adapter board is available (interface between the connector on the display and a mikroBUSTM socket).

SPECIFICATION

Display size	2.8"
Resolution	320x240px
Graphic controller	FT800
Brightness	240
Touch Screen	Resistive
Interface	I2C/SPI