



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832


Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



MIO-5271

4th Gen Intel® Core™ U-series (i5/Celeron®), 3.5" MI/O-Compact SBC, DDR3L, VGA, HDMI/DP*, 48-bit LVDS, 2GbE, 2 x Mini PCIe, mSATA, Fanless, MIOe



iManager susiAccess CE FCC

Features

- 4th Gen Intel® Core™ U-series (i5/Celeron®), 1 x DDR3L-1600/1333 SO-DIMM support up to 8 GB
- DirectX11.1, OpenGL4.0, OpenCL1.2, 3 independent display: VGA + LVDS + HDMI/Displayport*
- Optimized thermal design with fanless solution for wide temperature
- Flexible design using integrated multiple I/O: MIOe to approach vertical applications & keep domain knowhow.
- 2 GbE support, HD Audio, Rich I/O interface with 4 COM, 2 SATA, SMBus/iPC, GPIO, Half-size Mini PCIe, Full-size Mini PCIe w/ mSATA & 2 USB 3.0
- Supports Intel AMT9.0, iManager, SUSIAccess and Embedded Software APIs

Software APIs:



Utilities:




Specifications

Processor System	CPU	Intel Core i5-4300U	Intel Celeron 2980U
	Base Frequency	1.9 GHz (Dual-Core)	1.6GHz (Dual-Core)
	Max Turbo Frequency	2.9 GHz	N/A
	L3 Cache	3MB	2MB
	System Chipset	Integrated Intel 8 Series Chipset	
	BIOS	AMI UEFI 128 Mbit	
Memory	Technology	DDR3L 1333/1600 MHz	
	Max. Capacity	8 GB	
	Socket	1 x 204-pin SODIMM	
Display	Controller	Intel HD Graphics 4400 / Intel HD Graphics (Celeron)	
	Processor Graphics	DirectX11.1, OpenGL 4.0, and OpenCL 1.2 Full AVC/VC1/MPEG2 HW Decode	
	VGA	Up to 1920 x 1200 with 60 Hz, 154 MHz pixel clock rate	
	LVDS	LVDS with 3.3V, 5V and 12V on LCD VDD power. 5V and 12V support on LVDS inverter Dual channel 24-bit LVDS, max resolution up to 1920 x 1200 with 60Hz	
	HDMI / DisplayPort*	Supports HDMI 1.4 for HD Video playback Max resolution up to 3200 x 2000 at 60 Hz on DisplayPort, 4096 x 2304 at 24 Hz on HDMI	
Ethernet	Speed	10/100/1000Mbps	
	Controller	GbE1: Intel i218, GbE2: Intel i210	
Audio	Connector	2 RJ45 on Rear I/O	
	Codec	High Definition Audio (HD), Line-in, Line out, Mic-in	
WatchDog Timer	Amplifier	Optional via MIOe	
	Output	System reset, Programmable counter from 1 ~ 255 minutes/ seconds	
Storage	SATA	2, up to 6.0 Gb/s (600 MB/s)	
	mSATA	1 x Full-size (support either mSATA or miniPCIe, select by switch)	
Rear I/O	Ethernet	2	
	VGA	1	
	HDMI / DisplayPort*	1	
	USB 2.0	2	
	USB 3.0	2	
	LED	Power, HDD	
	DC Jack*	1	
Internal I/O	Serial	2 x RS-232 from COM1/2, 2 x RS-232/422/485 from COM3/4 with auto flow control (ESD protection: Air gap ±15kV, Contact ±8kV)	
	USB*	1 (Shares with the USB port for Mini PCIe)	
	iPC	1 (Shares with SMBus pin)	
	SMBus	1	
	GPIO	8-bit general purpose input/output	
Expansion	Mini PCIe	1 x Full-size with SIM card holder (default support mSATA) 1 x Half-size	
	MIOe	Displayport*, SMBus, 3 x USB2.0, LPC, 1 x PCIe x1, line out, +5 Vsb/+12 Vsb power, Power On, Reset	
Power	Power Type	Single 12V DC power input	
	Power Supply Voltage	Supports single 12V input, ± 10%	
	Power Consumption (Typical)	MIO-5271U-S6A1E: 0.38 A @ 12 V (4.56 W) MIO-5271U-S9A1E: 0.39 A @ 12 V (4.68 W)	
	Power Consumption (Max)	MIO-5271U-S6A1E: 1.71 A @ 12 V (20.52 W) MIO-5271U-S9A1E: 2.46 A @ 12 V (29.52 W)	
	Power Management	ACPI	
	Battery	Lithium 3 V / 210 mAh	
Environment	Operational	0 ~ 60° C (32 ~ 140° F) (Operational humidity: 40° C @ 95% RH Non-Condensing)	
	Non-Operational	-40° C ~ 85° C and 60° C @ 95% RH Non-Condensing	
Physical Characteristics	Dimensions (L x W)	146 x 102 mm (5.7" x 4"), same as 3.5"	
	Weight	0.84 kg (1.72lb), weight of total package	
	Height	Top Side: 24 mm (MIO-5271U), 34 mm (MIO-5271Z&Z2); Bottom Side: 6.8 mm; PCB: 1.6mm	

*It will not be supported in default, please contact to Advantech if this function is needed.

Block Diagram



¹ Support by request

Ordering Information

Part No.	CPU	L3 Cache	Memory	LVDS	VGA	HDMI/DP¹	GbE	HD Audio	RS-232/422/485	RS-232	USB 3.0	USB 2.0	SATAIII	Half-size Mini PCIe	Full-size Mini PCIe²	MIOe	Power connector	Thermal Solution²	Operation Temp.
MIO-5271U-S9A1E	Intel i5-4300U 1.9GHz 15W	3MB	SO-DIMM	48-bit	Yes	HDMI	2	1	2	2	2	2	2	1	1	1	2x2 pin	Passive	0 – 60° C
MIO-5271U-S6A1E	Intel Celeron 2980U 1.6GHz 15W	2MB	SO-DIMM	48-bit	Yes	HDMI	2	1	2	2	2	2	2	1	1	1	2x2 pin	Passive	0 – 60° C
MIO-5271Z-4GS9A1E	Intel i5-4300U 1.9GHz 15W	3MB	4GB bundle	48-bit	Yes	HDMI	2	1	2	2	2	2	2	1	1	1	2x2 pin	Passive	-20 – 80° C
MIO-5271Z2-4GS9A1E	Intel i5-4300U 1.9GHz 15W	3MB	4GB bundle	48-bit	Yes	HDMI	2	1	2	2	2	2	2	1	1	1	2x2 pin	Passive	-40 – 85° C

¹ Support by request
² Default support mSATA

Packing List

Part No.	Description	Quantity
	MIO-5271 SBC	1
2006527100	Startup Manual	1
1700006291	M Cable SATA 7P/SATA 7P 30cm C-R 180/90	1
1700018785	SATA 35cm power cable	1
1701200220	COM RS-232 Cable 2*10P-2.0/D-SUB 9P (M)*2 22CM	2
1700019584	Audio Cable 2*5P-2.0/JACK*3 20cm	1
9689000002	mini Jumper pack	1
1960062041T001	Heatsink (104 x 83 x 24 mm) for MIO-5271U only	1
1960066765T001	Heatsink (145 x 84 x 34 mm) for MIO-5271Z&Z2 only	1

Optional Accessories

Part No.	Description
1960063980N001	Heat spreader for MIO-5271
1700023098-01	Internal 1 x USB-A cable 15CM

Embedded OS/API

Embedded OS/API	Part No.	Description
Windows Embedded Standard 7	2070012422	WES7E MIO-5271 x86 V5.1.6 EN/TC/SC/JP
VxWorks		6.9.2
Linux		Ubuntu 13.04
Software API		iManager 2.0

Rear I/O View



- MIO-5271U-S9A1E
- MIO-5271U-S6A1E
- MIO-5271Z-4GS9A1E
- MIO-5271Z2-4GS9A1E