



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



# MJE18008, MJF18008

## Switch-mode NPN Bipolar Power Transistor For Switching Power Supply Applications

The MJE/MJF18008 have an applications specific state-of-the-art die designed for use in 220 V line-operated switch-mode Power supplies and electronic light ballasts.

### Features

- Improved Efficiency Due to Low Base Drive Requirements:
  - High and Flat DC Current Gain  $h_{FE}$
  - Fast Switching
  - No Coil Required in Base Circuit for Turn-Off (No Current Tail)
- Tight Parametric Distributions are Consistent Lot-to-Lot
- Two Package Choices: Standard TO-220 or Isolated TO-220
- MJF18008, Case 221D, is UL Recognized at 3500  $V_{RMS}$ : File #E69369
- These Devices are Pb-Free and are RoHS Compliant\*

### MAXIMUM RATINGS

| Rating  | Symbol         | Value                                   | Unit                     |
|---|----------------|---|--------------------------|
| Collector-Emitter Sustaining Voltage  | $V_{CEO}$      | 450                                     | Vdc                      |
| Collector-Base Breakdown Voltage  | $V_{CES}$      | 1000                                    | Vdc                      |
| Emitter-Base Voltage  | $V_{EBO}$      | 9.0                                     | Vdc                      |
| Collector Current – Continuous  | $I_C$          | 8.0                                     | Adc                      |
| Collector Current – Peak (Note 1)   | $I_{CM}$       | 16                                      | Adc                      |
| Base Current – Continuous   | $I_B$          | 4.0                                     | Adc                      |
| Base Current – Peak (Note 1)  | $I_{BM}$       | 8.0                                     | Adc                      |
| RMS Isolation Voltage (Note 2)<br>Test No. 1 Per Figure 22a<br>Test No. 1 Per Figure 22b<br>Test No. 1 Per Figure 22c<br>(for 1 sec, R.H. < 30%, $T_A = 25^\circ\text{C}$ ) | $V_{ISOL}$     | <b>MJF18008</b><br>4500<br>3500<br>1500 | V                        |
| Total Device Dissipation @ $T_C = 25^\circ\text{C}$<br>MJE18008<br>MJF18008   | $P_D$          | 125<br>45                               | W<br>W/ $^\circ\text{C}$ |
| Derate above $25^\circ\text{C}$<br>MJE18008<br>MJF18008   |                | 1.0<br>0.36                             |                          |
| Operating and Storage Temperature   | $T_J, T_{stg}$ | -65 to 150                              | $^\circ\text{C}$         |

### THERMAL CHARACTERISTICS

| Characteristics  | Symbol          | Max         | Unit                      |
|--|-----------------|-------------|---------------------------|
| Thermal Resistance, Junction-to-Case<br>MJE18008<br>MJF18008                 | $R_{\theta JC}$ | 1.0<br>2.78 | $^\circ\text{C}/\text{W}$ |
| Thermal Resistance, Junction-to-Ambient                                      | $R_{\theta JA}$ | 62.5        | $^\circ\text{C}/\text{W}$ |
| Maximum Lead Temperature for Soldering Purposes 1/8" from Case for 5 Seconds | $T_L$           | 260         | $^\circ\text{C}$          |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.


- Pulse Test: Pulse Width = 5 ms, Duty Cycle  $\leq 10\%$ .
- Proper strike and creepage distance must be provided.




ON Semiconductor®

[www.onsemi.com](http://www.onsemi.com)



**POWER TRANSISTOR**  
**8.0 AMPERES**  
**1000 VOLTS**  
**45 and 125 WATTS**




### MARKING DIAGRAMS



**TO-220AB**  
**CASE 221A-09**  
**STYLE 1**



**TO-220 FULLPACK**  
**CASE 221D**  
**STYLE 2**  
**UL RECOGNIZED**



G = Pb-Free Package  
A = Assembly Location  
Y = Year  
WW = Work Week

### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 7 of this data sheet.

\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.



# MJE18008, MJF18008

## ELECTRICAL CHARACTERISTICS (T<sub>C</sub> = 25°C unless otherwise specified)

| Characteristic | Symbol | Min | Typ | Max | Unit |
|----------------|--------|-----|-----|-----|------|
|----------------|--------|-----|-----|-----|------|

### OFF CHARACTERISTICS

|   |                          |     |   |     |      |
|---|--------------------------|-----|---|-----|------|
| Collector–Emitter Sustaining Voltage (I <sub>C</sub> = 100 mA, L = 25 mH)                 | V <sub>CEO(sus)</sub>    | 450 | – | –   | Vdc  |
| Collector Cutoff Current (V <sub>CE</sub> = Rated V <sub>CEO</sub> , I <sub>B</sub> = 0)  | I <sub>CEO</sub>         | –   | – | 100 | μAdc |
| Collector Cutoff Current (V <sub>CE</sub> = Rated V <sub>CES</sub> , V <sub>EB</sub> = 0) | I <sub>CES</sub>         | –   | – | 100 | μAdc |
| (V <sub>CE</sub> = 800 V, V <sub>EB</sub> = 0)  | (T <sub>C</sub> = 125°C) | –   | – | 500 |      |
|   | (T <sub>C</sub> = 125°C) | –   | – | 100 |      |
| Emitter Cutoff Current (V <sub>EB</sub> = 9.0 Vdc, I <sub>C</sub> = 0)                    | I <sub>EBO</sub>         | –   | – | 100 | μAdc |

### ON CHARACTERISTICS

|  |                          |     |              |             |     |
|--|--------------------------|-----|--------------|-------------|-----|
| Base–Emitter Saturation Voltage (I <sub>C</sub> = 2.0 Adc, I <sub>B</sub> = 0.2 Adc)<br>(I <sub>C</sub> = 4.5 Adc, I <sub>B</sub> = 0.9 Adc) | V <sub>BE(sat)</sub>     | –   | 0.82<br>0.92 | 1.1<br>1.25 | Vdc |
| Collector–Emitter Saturation Voltage<br>(I <sub>C</sub> = 2.0 Adc, I <sub>B</sub> = 0.2 Adc)   | V <sub>CE(sat)</sub>     | –   | 0.3          | 0.6         | Vdc |
| (I <sub>C</sub> = 4.5 Adc, I <sub>B</sub> = 0.9 Adc)   | (T <sub>C</sub> = 125°C) | –   | 0.3          | 0.65        |     |
|  | (T <sub>C</sub> = 125°C) | –   | 0.35         | 0.7         |     |
|  | (T <sub>C</sub> = 125°C) | –   | 0.4          | 0.8         |     |
| DC Current Gain (I <sub>C</sub> = 1.0 Adc, V <sub>CE</sub> = 5.0 Vdc)  | h <sub>FE</sub>          | 14  | –            | 34          | –   |
| (I <sub>C</sub> = 4.5 Adc, V <sub>CE</sub> = 1.0 Vdc)  | (T <sub>C</sub> = 125°C) | –   | 28           | –           |     |
| (I <sub>C</sub> = 2.0 Adc, V <sub>CE</sub> = 1.0 Vdc)  | (T <sub>C</sub> = 125°C) | 6.0 | 9.0          | –           |     |
| (I <sub>C</sub> = 2.0 Adc, V <sub>CE</sub> = 1.0 Vdc)  | (T <sub>C</sub> = 125°C) | 5.0 | 8.0          | –           |     |
| (I <sub>C</sub> = 10 mAdc, V <sub>CE</sub> = 5.0 Vdc)  | (T <sub>C</sub> = 125°C) | 11  | 15           | –           |     |
|  | (T <sub>C</sub> = 125°C) | 11  | 16           | –           |     |
|  | (T <sub>C</sub> = 125°C) | 10  | 20           | –           |     |

### DYNAMIC CHARACTERISTICS

|  |                          |   |                          |                          |     |     |      |     |  |
|--|--------------------------|---|--------------------------|--------------------------|-----|-----|------|-----|--|
| Current Gain Bandwidth (I <sub>C</sub> = 0.5 Adc, V <sub>CE</sub> = 10 Vdc, f = 1.0 MHz)   | f <sub>T</sub>           | –   | 13                       | –                        | MHz |     |      |     |  |
| Output Capacitance (V <sub>CB</sub> = 10 Vdc, I <sub>E</sub> = 0, f = 1.0 MHz)   | C <sub>ob</sub>          | –   | 100                      | 150                      | pF  |     |      |     |  |
| Input Capacitance (V <sub>EB</sub> = 8.0 V)  | C <sub>ib</sub>          | –   | 1750                     | 2500                     | pF  |     |      |     |  |
| Dynamic Saturation Voltage:<br>Determined 1.0 μs and<br>3.0 μs respectively after<br>rising I <sub>B1</sub> reaches 90% of<br>final I <sub>B1</sub><br>(see Figure 18) | V <sub>CE(dsat)</sub>    | (I <sub>C</sub> = 2.0 Adc<br>I <sub>B1</sub> = 200 mAdc<br>V <sub>CC</sub> = 300 V) | 1.0 μs                   | (T <sub>C</sub> = 125°C) | –   | 5.5 | –    | Vdc |  |
| –  |                          |   | –                        | 11.5                     | –   |     |      |     |  |
| (I <sub>C</sub> = 5.0 Adc<br>I <sub>B1</sub> = 1.0 Adc<br>V <sub>CC</sub> = 300 V)   |                          | 3.0 μs  | (T <sub>C</sub> = 125°C) | –                        | –   | –   | 3.5  | –   |  |
|  |                          |   |                          | –                        | –   | –   | 6.5  | –   |  |
|  |                          | 1.0 μs  | (T <sub>C</sub> = 125°C) | –                        | –   | –   | 11.5 | –   |  |
|  |                          |   |                          | –                        | –   | –   | 14.5 | –   |  |
| 3.0 μs   | (T <sub>C</sub> = 125°C) | –   | –                        | –                        | 2.4 | –   |      |     |  |
|  |                          | –   | –                        | –                        | 9.0 | –   |      |     |  |

### SWITCHING CHARACTERISTICS: Resistive Load (D.C. ≤ 10%, Pulse Width = 20 μs)

|               |   |                          |                  |   |     |     |    |
|---------------|---|--------------------------|------------------|---|-----|-----|----|
| Turn–On Time  | (I <sub>C</sub> = 2.0 Adc, I <sub>B1</sub> = 0.2 Adc,<br>I <sub>B2</sub> = 1.0 Adc, V <sub>CC</sub> = 300 V)  | (T <sub>C</sub> = 125°C) | t <sub>on</sub>  | – | 200 | 300 | ns |
| Turn–Off Time |   |                          | t <sub>off</sub> | – | 190 | –   |    |
|               |   | (T <sub>C</sub> = 125°C) |                  | – | 1.2 | 2.5 | μs |
|               |   | (T <sub>C</sub> = 125°C) |                  | – | 1.5 | –   |    |
| Turn–On Time  | (I <sub>C</sub> = 4.5 Adc, I <sub>B1</sub> = 0.9 Adc,<br>I <sub>B2</sub> = 2.25 Adc, V <sub>CC</sub> = 300 V) | (T <sub>C</sub> = 125°C) | t <sub>on</sub>  | – | 100 | 180 | ns |
| Turn–Off Time |   |                          | t <sub>off</sub> | – | 250 | –   |    |
|               |   | (T <sub>C</sub> = 125°C) |                  | – | 1.6 | 2.5 | μs |
|               |   | (T <sub>C</sub> = 125°C) |                  | – | 2.0 | –   |    |

### SWITCHING CHARACTERISTICS: Inductive Load (V<sub>clamp</sub> = 300 V, V<sub>CC</sub> = 15 V, L = 200 μH)

|                |  |                          |                 |   |     |      |    |
|----------------|--|--------------------------|-----------------|---|-----|------|----|
| Fall Time      | (I <sub>C</sub> = 2.0 Adc, I <sub>B1</sub> = 0.2 Adc,<br>I <sub>B2</sub> = 1.0 Adc)  | (T <sub>C</sub> = 125°C) | t <sub>fi</sub> | – | 100 | 180  | ns |
| Storage Time   |  |                          | t <sub>si</sub> | – | 120 | –    |    |
|                |  |                          | –               | – | 1.5 | 2.75 | μs |
|                |  | (T <sub>C</sub> = 125°C) |                 | – | 1.9 | –    |    |
| Crossover Time |  | (T <sub>C</sub> = 125°C) | t <sub>c</sub>  | – | 250 | 350  | ns |
|                |  | (T <sub>C</sub> = 125°C) |                 | – | 230 | –    |    |
| Fall Time      | (I <sub>C</sub> = 4.5 Adc, I <sub>B1</sub> = 0.9 Adc,<br>I <sub>B2</sub> = 2.25 Adc) | (T <sub>C</sub> = 125°C) | t <sub>fi</sub> | – | 85  | 150  | ns |
| Storage Time   |  |                          | t <sub>si</sub> | – | 135 | –    |    |
|                |  |                          | –               | – | 2.0 | 3.2  | μs |
|                |  | (T <sub>C</sub> = 125°C) |                 | – | 2.6 | –    |    |
| Crossover Time |  | (T <sub>C</sub> = 125°C) | t <sub>c</sub>  | – | 210 | 300  | ns |
|                |  | (T <sub>C</sub> = 125°C) |                 | – | 250 | –    |    |

- Pulse Test: Pulse Width = 5.0 ms, Duty Cycle ≤ 10%.
- Proper strike and creepage distance must be provided.

TYPICAL STATIC CHARACTERISTICS




Figure 1. DC Current Gain @ 1 Volt




Figure 2. DC Current Gain @ 5 Volts




Figure 3. Collector Saturation Region




Figure 4. Collector-Emitter Saturation Voltage




Figure 5. Base-Emitter Saturation Region




Figure 6. Capacitance

TYPICAL SWITCHING CHARACTERISTICS  
( $I_{B2} = I_C/2$  for all switching)




Figure 7. Resistive Switching,  $t_{on}$




Figure 8. Resistive Switching,  $t_{off}$




Figure 9. Inductive Storage Time,  $t_{si}$




Figure 10. Inductive Storage Time,  $t_{si}(h_{FE})$




Figure 11. Inductive Switching,  $t_c$  and  $t_{fi}$   
 $I_C/I_B = 5$




Figure 12. Inductive Switching,  $t_c$  and  $t_{fi}$   
 $I_C/I_B = 10$

**TYPICAL SWITCHING CHARACTERISTICS**  
( $I_{B2} = I_C/2$  for all switching)




Figure 13. Inductive Fall Time




Figure 14. Inductive Crossover Time

**GUARANTEED SAFE OPERATING AREA INFORMATION**




Figure 15. Forward Bias Safe Operating Area




Figure 16. Reverse Bias Switching Safe Operating Area




Figure 17. Forward Bias Power Derating

There are two limitations on the power handling ability of a transistor: average junction temperature and second breakdown. Safe operating area curves indicate  $I_C - V_{CE}$

limits of the transistor that must be observed for reliable operation; i.e., the transistor must not be subjected to greater dissipation than the curves indicate. The data of Figure 15 is based on  $T_C = 25^\circ\text{C}$ ;  $T_{J(pk)}$  is variable depending on power level. Second breakdown pulse limits are valid for duty cycles to 10% but must be derated when  $T_C > 25^\circ\text{C}$ . Second breakdown limitations do not derate the same as thermal limitations. Allowable current at the voltages shown in Figure 15 may be found at any case temperature by using the appropriate curve on Figure 17.  $T_{J(pk)}$  may be calculated from the data in Figure 20 and 21. At any case temperatures, thermal limitations will reduce the power that can be handled to values less than the limitations imposed by second breakdown. For inductive loads, high voltage and current must be sustained simultaneously during turn-off with the base-to-emitter junction reverse-biased. The safe level is specified as a reverse-biased safe operating area (Figure 16). This rating is verified under clamped conditions so that the device is never subjected to an avalanche mode.

# MJE18008, MJF18008




Figure 18. Dynamic Saturation Voltage Measurements




Figure 19. Inductive Switching Measurements




Table 1. Inductive Load Switching Drive Circuit

# MJE18008, MJF18008

## TYPICAL THERMAL RESPONSE




Figure 20. Typical Thermal Response ( $Z_{\theta_{JC}}(t)$ ) for MJE18008




Figure 21. Typical Thermal Response ( $Z_{\theta_{JC}}(t)$ ) for MJF18008

### ORDERING INFORMATION

| Device    | Package                        | Shipping        |
|-----------|--------------------------------|-----------------|
| MJE18008G | TO-220AB<br>(Pb-Free)          | 50 Units / Rail |
| MJF18008G | TO-220 (Fullpack)<br>(Pb-Free) | 50 Units / Rail |



TEST CONDITIONS FOR ISOLATION TESTS\*




Figure 22a. Screw or Clip Mounting Position for Isolation Test Number 1




Figure 22b. Clip Mounting Position for Isolation Test Number 2




Figure 22c. Screw Mounting Position for Isolation Test Number 3

\*Measurement made between leads and heatsink with all leads shorted together

MOUNTING INFORMATION\*\*




Figure 23a. Screw-Mounted




Figure 23b. Clip-Mounted

Figure 23. Typical Mounting Techniques for Isolated Package

Laboratory tests on a limited number of samples indicate, when using the screw and compression washer mounting technique, a screw torque of 6 to 8 in · lbs is sufficient to provide maximum power dissipation capability. The compression washer helps to maintain a constant pressure on the package over time and during large temperature excursions.

Destructive laboratory tests show that using a hex head 4-40 screw, without washers, and applying a torque in excess of 20 in · lbs will cause the plastic to crack around the mounting hole, resulting in a loss of isolation capability.


Additional tests on slotted 4-40 screws indicate that the screw slot fails between 15 to 20 in · lbs without adversely affecting the package. However, in order to positively ensure the package integrity of the fully isolated device, ON Semiconductor does not recommend exceeding 10 in · lbs of mounting torque under any mounting conditions.

\*\* For more information about mounting power semiconductors see Application Note AN1040.

# MJE18008, MJF18008

## PACKAGE DIMENSIONS

### TO-220 CASE 221A-09 ISSUE AH




- NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
  2. CONTROLLING DIMENSION: INCH.
  3. DIMENSION Z DEFINES A ZONE WHERE ALL BODY AND LEAD IRREGULARITIES ARE ALLOWED.

| DIM | INCHES |       | MILLIMETERS |       |
|-----|--------|-------|-------------|-------|
|     | MIN    | MAX   | MIN         | MAX   |
| A   | 0.570  | 0.620 | 14.48       | 15.75 |
| B   | 0.380  | 0.415 | 9.66        | 10.53 |
| C   | 0.160  | 0.190 | 4.07        | 4.83  |
| D   | 0.025  | 0.038 | 0.64        | 0.96  |
| F   | 0.142  | 0.161 | 3.61        | 4.09  |
| G   | 0.095  | 0.105 | 2.42        | 2.66  |
| H   | 0.110  | 0.161 | 2.80        | 4.10  |
| J   | 0.014  | 0.024 | 0.36        | 0.61  |
| K   | 0.500  | 0.562 | 12.70       | 14.27 |
| L   | 0.045  | 0.060 | 1.15        | 1.52  |
| N   | 0.190  | 0.210 | 4.83        | 5.33  |
| Q   | 0.100  | 0.120 | 2.54        | 3.04  |
| R   | 0.080  | 0.110 | 2.04        | 2.79  |
| S   | 0.045  | 0.055 | 1.15        | 1.39  |
| T   | 0.235  | 0.255 | 5.97        | 6.47  |
| U   | 0.000  | 0.050 | 0.00        | 1.27  |
| V   | 0.045  | ---   | 1.15        | ---   |
| Z   | ---    | 0.080 | ---         | 2.04  |

- STYLE 1:  
PIN 1. BASE  
2. COLLECTOR  
3. EMITTER  
4. COLLECTOR


### TO-220 FULLPAK CASE 221D-03 ISSUE K



- NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
  2. CONTROLLING DIMENSION: INCH
  3. 221D-01 THRU 221D-02 OBSOLETE, NEW STANDARD 221D-03.

| DIM | INCHES    |       | MILLIMETERS |       |
|-----|-----------|-------|-------------|-------|
|     | MIN       | MAX   | MIN         | MAX   |
| A   | 0.617     | 0.635 | 15.67       | 16.12 |
| B   | 0.392     | 0.419 | 9.96        | 10.63 |
| C   | 0.177     | 0.193 | 4.50        | 4.90  |
| D   | 0.024     | 0.039 | 0.60        | 1.00  |
| F   | 0.116     | 0.129 | 2.95        | 3.28  |
| G   | 0.100 BSC |       | 2.54 BSC    |       |
| H   | 0.118     | 0.135 | 3.00        | 3.43  |
| J   | 0.018     | 0.025 | 0.45        | 0.63  |
| K   | 0.503     | 0.541 | 12.78       | 13.73 |
| L   | 0.048     | 0.058 | 1.23        | 1.47  |
| N   | 0.200 BSC |       | 5.08 BSC    |       |
| Q   | 0.122     | 0.138 | 3.10        | 3.50  |
| R   | 0.099     | 0.117 | 2.51        | 2.96  |
| S   | 0.092     | 0.113 | 2.34        | 2.87  |
| U   | 0.239     | 0.271 | 6.06        | 6.88  |

- STYLE 2:  
PIN 1. BASE  
2. COLLECTOR  
3. EMITTER

**ON Semiconductor** and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

**PUBLICATION ORDERING INFORMATION**

**LITERATURE FULFILLMENT:**

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada  
**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910  
**Japan Customer Focus Center**  
Phone: 81-3-5817-1050

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)  
**Order Literature:** <http://www.onsemi.com/orderlit>  
For additional information, please contact your local  
Sales Representative