



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





ICs

Microcontroller

A

Microcontroller

CONTENTS

High Performance & Ultra Low Power MCU	P. A112
16bit ML620500 Series (LAPIS Semiconductor products)	P. A112
Ultra Low Operating Voltage & Ultra Low Power MCU	P. A112
8bit ML610400 Series (LAPIS Semiconductor products)	P. A112
High Noise Immunity MCU	P. A118
8bit ML610100 Series (LAPIS Semiconductor products)	P. A118
16bit ML620100 Series (LAPIS Semiconductor products)	P. A118
Built-in Speech Output Function MCU	P. A120
8bit ML610300 Series (LAPIS Semiconductor products)	P. A120
Sensor Hub MCU	P. A120
8bit ML610790 Family (LAPIS Semiconductor products)	P. A120
32bit ML630790 Family (LAPIS Semiconductor products)	P. A120
ARM-Based MCU	P. A120
32bit ML674xxx/ML675xxx (LAPIS Semiconductor products)	P. A120
Power-Saving Solar Power Supply Control LSI	P. A122
Secondary battery control LSI (LAPIS Semiconductor products)	P. A122
Primary battery control LSI (LAPIS Semiconductor products)	P. A122

High Performance & Ultra Low Power MCU

16bit ML620500 Series

Standard Type 16bit Low power MCU																		
Part No.	Operating Conditions					ROM/RAM				Functions / Features								
	Operating voltage (V)	Operating frequency (Max.)		Minimum instruction execution time	Current consumption (Typ.@HALT)	Operating temperature (°C)	ROM Type	ROM capacity (Byte)	Data Flash capacity (Byte)	RAM capacity (Byte)	port			PWM				
		Low speed	High speed								Input	Output	Input/Output					
☆ ML620Q503	1.8 to 5.5	32.768kHz (Internal RC oscillation/ Crystal oscillation/ External input)		16MHz	62.5 ns / 30.5µs	0.45µA	-40 to +85	Flash	32K	2K	2K	✓	2	—	36	8 (16bit×4)	4	16bit×4 (use 16bit timer)
New ML620Q504	1.8 to 5.5	32.768kHz (Internal RC oscillation/ Crystal oscillation/ External input)		16MHz	62.5 ns / 30.5µs	0.45µA	-40 to +85	Flash	64K	2K	6K	✓	2	—	36	8 (16bit×4)	4	16bit×4 (use 16bit timer)
☆ ML620Q506	1.8 to 5.5	32.768kHz (Internal RC oscillation/ Crystal oscillation/ External input)		16MHz	62.5 ns / 30.5µs	0.45µA	-40 to +85	Flash	128K	2K	12K	✓	2	—	36	8 (16bit×4)	4	16bit×4 (use 16bit timer)
☆ ML620Q546	1.8 to 5.5	32.768kHz (Internal RC oscillation/ Crystal oscillation/ External input)		16MHz	62.5 ns / 30.5µs	0.45µA	-40 to +85	Flash	128K	2K	10K	✓	—	—	70	12 (16bit×6)	8	16bit×8 (use 16bit timer) 3 phase motor PWM×1
☆ ML620Q558	1.8 to 5.5	32.768kHz (Internal RC oscillation/ Crystal oscillation/ External input)		16MHz	62.5 ns / 30.5µs	0.45µA	-40 to +85	Flash	256K	2K	20K	✓	—	—	90	12 (16bit×6)	8	16bit×8 (use 16bit timer) 3 phase motor PWM×1

Ultra Low Operating Voltage & Ultra Low Power MCU

8bit ML610400 Series

Standard Type 8bit Low power MCU																		
Part No.	Operating Conditions					ROM/RAM				Functions / Features								
	Operating voltage (V)	Operating frequency (Max.)		Minimum instruction execution time	Current consumption (Typ.@HALT)	Operating temperature (°C)	ROM Type	ROM capacity (Byte)	Data Flash capacity (Byte)	RAM capacity (Byte)	port			8bit timer	1kHz timer	PWM	Capture	WDT
		Low speed	High speed								Input	Output	Input/Output					
ML610482	1.1 to 3.6	32.768kHz (Crystal oscillation)	4.096MHz 500kHz	0.244µs/2µs/30.5µs	0.5µA	-20 to +70	Mask	64K	—	4K	6	4	22	4 (16bit×2)	—	16bit×1	—	1
ML610482P	1.1 to 3.6	32.768kHz (Crystal oscillation)	4.096MHz 500kHz	0.244µs/2µs/30.5µs	0.5µA	-40 to +85	Mask	64K	—	4K	6	4	22	4 (16bit×2)	—	16bit×1	—	1
ML610Q482	1.1 to 3.6	32.768kHz (Crystal oscillation)	4.096MHz 500kHz	0.244µs/2µs/30.5µs	0.5µA	-20 to +70	Flash	64K	—	4K	6	4	22	4 (16bit×2)	—	16bit×1	—	1
ML610Q482P	1.1 to 3.6	32.768kHz (Crystal oscillation)	4.096MHz 500kHz	0.244µs/2µs/30.5µs	0.5µA	-40 to +85	Flash	64K	—	4K	6	4	22	4 (16bit×2)	—	16bit×1	—	1
New ML610Q485	1.25 to 3.6	32.768kHz (Crystal oscillation)	4.096MHz 500kHz	0.25µs/2µs/30.5µs	0.35µA	-20 to +70	Flash	32K	—	2K	4	6	16	6 (16bit×3)	—	16bit×1	2	1
New ML610Q485P	1.25 to 3.6	32.768kHz (Crystal oscillation)	4.096MHz 500kHz	0.25µs/2µs/30.5µs	0.35µA	-40 to +85	Flash	32K	—	2K	4	6	16	6 (16bit×3)	—	16bit×1	2	1

Built-in LCD driver Dot Matrix Type 8bit Low power MCU																		
ML610421	1.1 to 3.6	32.768kHz (Crystal oscillation)	4.096MHz 500kHz	0.244µs/2µs/30.5µs	0.5µA	-20 to +70	Mask	32K	—	2K	6	3	22	4 (16bit×2)	1	16bit×1	2	1
ML610421P	1.1 to 3.6	32.768kHz (Crystal oscillation)	4.096MHz 500kHz	0.244µs/2µs/30.5µs	0.5µA	-40 to +85	Mask	32K	—	2K	6	3	22	4 (16bit×2)	1	16bit×1	2	1
ML610Q421	1.1 to 3.6	32.768kHz (Crystal oscillation)	4.096MHz 500kHz	0.244µs/2µs/30.5µs	0.5µA	-20 to +70	Flash	32K	—	2K	6	3	22	4 (16bit×2)	1	16bit×1	2	1
ML610Q421P	1.1 to 3.6	32.768kHz (Crystal oscillation)	4.096MHz 500kHz	0.244µs/2µs/30.5µs	0.5µA	-40 to +85	Flash	32K	—	2K	6	3	22	4 (16bit×2)	1	16bit×1	2	1
ML610Q422	1.1 to 3.6	32.768kHz (Crystal oscillation)	4.096MHz 500kHz	0.244µs/2µs/30.5µs	0.5µA	-20 to +70	Flash	32K	—	2K	6	3	14	4 (16bit×2)	1	16bit×1	2	1
ML610Q422P	1.1 to 3.6	32.768kHz (Crystal oscillation)	4.096MHz 500kHz	0.244µs/2µs/30.5µs	0.5µA	-40 to +85	Flash	32K	—	2K	6	3	14	4 (16bit×2)	1	16bit×1	2	1
ML610Q422B	1.1 to 3.6	32.768kHz (Crystal oscillation)	4.096MHz 500kHz	0.244µs/2µs/30.5µs	0.5µA	-20 to +70	Flash	32K	—	2K	6	3	14	4 (16bit×2)	1	16bit×1	2	1
ML610Q422PB	1.1 to 3.6	32.768kHz (Crystal oscillation)	4.096MHz 500kHz	0.244µs/2µs/30.5µs	0.5µA	-40 to +85	Flash	32K	—	2K	6	3	14	4 (16bit×2)	1	16bit×1	2	1
ML610426	1.1 to 3.6	32.768kHz (Crystal oscillation)	1MHz	1µs/30.5µs	0.5µA	-20 to +70	Mask	40K	—	2K	5	—	7	4 (16bit×2)	1	16bit×1	—	1
ML610Q426	1.1 to 3.6	32.768kHz (Crystal oscillation)	1MHz	1µs/30.5µs	0.5µA	-20 to +70	Flash	40K	—	2K	5	—	7	4 (16bit×2)	1	16bit×1	—	1
ML610Q426C	1.1 to 3.6	32.768kHz (Crystal oscillation)	1MHz	1µs/30.5µs	0.5µA	-20 to +70	Flash	40K	—	2K	7	—	13	4 (16bit×2)	1	16bit×1	—	1
ML610Q428	1.1 to 3.6	32.768kHz (Crystal oscillation)	4.096MHz 2MHz	0.244µs/0.5µs/30.5µs	0.5µA	-20 to +70	Flash	48K	—	4K	6	3	14	2 (16bit×1)	1	16bit×3	—	1
ML610429	1.1 to 3.6	32.768kHz (Crystal oscillation)	4.096MHz 2MHz	0.244µs/0.5µs/30.5µs	0.5µA	-20 to +70	Mask	48K	—	4K	10	3	20	2 (16bit×1)	1	16bit×3	—	1
ML610Q429	1.1 to 3.6	32.768kHz (Crystal oscillation)	4.096MHz 2MHz	0.244µs/0.5µs/30.5µs	0.5µA	-20 to +70	Flash	48K	—	4K	10	3	20	2 (16bit×1)	1	16bit×3	—	1
ML610Q431	1.1 to 3.6	32.768kHz (Crystal oscillation)	4.096MHz 500kHz	0.244µs/2µs/30.5µs	0.5µA	-20 to +70	Flash	64K	—	3K	6	3	22	4 (16bit×2)	1	16bit×1	2	1
ML610Q431A	1.1 to 3.6	32.768kHz (Crystal oscillation)	4.096MHz 500kHz	0.244µs/2µs/30.5µs	0.5µA	-20 to +70	Flash	64K	—	3K	6	3	22	4 (16bit×2)	1	16bit×1	2	1
ML610Q431PA	1.1 to 3.6	32.768kHz (Crystal oscillation)	4.096MHz 500kHz	0.244µs/2µs/30.5µs	0.5µA	-40 to +85	Flash	64K	—	3K	6	3	22	4 (16bit×2)	1	16bit×1	2	1
ML610Q432	1.1 to 3.6	32.768kHz (Crystal oscillation)	4.096MHz 500kHz	0.244µs/2µs/30.5µs	0.5µA	-20 to +70	Flash	64K	—	3K	6	3	14	4 (16bit×2)	1	16bit×1	2	1
ML610Q432A	1.1 to 3.6	32.768kHz (Crystal oscillation)	4.096MHz 500kHz	0.244µs/2µs/30.5µs	0.5µA	-20 to +70	Flash	64K	—	3K	6	3	14	4 (16bit×2)	1	16bit×1	2	1
ML610Q435	1.1 to 3.6	32.768kHz (Crystal oscillation)	4.096MHz 500kHz	0.244µs/2µs/30.5µs	0.5µA	-20 to +70	Flash	96K	—	3K	6	3	22	4 (16bit×2)	1	16bit×1	2	1
ML610Q435A	1.1 to 3.6	32.768kHz (Crystal oscillation)	4.096MHz 500kHz	0.244µs/2µs/30.5µs	0.5µA	-20 to +70	Flash	96K	—	3K	6	3	22	4 (16bit×2)	1	16bit×1	2	1
ML610Q436	1.1 to 3.6	32.768kHz (Crystal oscillation)	4.096MHz 500kHz	0.244µs/2µs/30.5µs	0.5µA	-20 to +70	Flash	96K	—	3K	6	3	14	4 (16bit×2)	1	16bit×1	2	1
ML610Q436A	1.1 to 3.6	32.768kHz (Crystal oscillation)	4.096MHz 500kHz	0.244µs/2µs/30.5µs	0.5µA	-20 to +70	Flash	96K	—	3K	6	3	14	4 (16bit×2)	1	16bit×1	2	1
ML610Q438	1.1 to 3.6	32.768kHz (Crystal oscillation)	4.096MHz 2MHz	0.244µs/0.5µs/30.5µs	0.5µA	-20 to +70	Flash	128K	—	7K	10	3	20	4 (16bit×2)	1	16bit×3	2	1
ML610Q438P	1.1 to 3.6	32.768kHz (Crystal oscillation)	4.096MHz 2MHz	0.244µs/0.5µs/30.5µs	0.5µA	-40 to +85	Flash	128K	—	7K	10	3	20	4 (16bit×2)	1	16bit×3	2	1
ML610Q439	1.1 to 3.6	32.768kHz (Crystal oscillation)	4.096MHz 2MHz	0.244µs/0.5µs/30.5µs	0.5µA	-20 to +70	Flash	128K	—	7K	10	3	20	4 (16bit×2)	1	16bit×3	2	1
ML610Q439P	1.1 to 3.6	32.768kHz (Crystal oscillation)	4.096MHz 2MHz	0.244µs/0.5µs/30.5µs	0.5µA	-40 to +85	Flash	128K	—	7K	10	3	20	4 (16bit×2)	1	16bit×3	2	1

(LAPIS Semiconductor products)

Functions / Features													
Capture	WDT	ADC (method)	Serial port			Supply voltage detection	LCD driver	External interrupt sources	Others	Industrial Equipment	Notes	Package	Chip Support
			FC	SSIO (Spi)	UART								
16bit×4 (use 16bit timer)	1	2 (RC type) 12bit×12 (SA type)	2	2	2	VLS×1 LLD×1	—	8	Low speed frequency correction/ Analog comparator×2/Melody : Buzzer	✓	—	P-TQFP48-0707-0.50	✓
16bit×4 (use 16bit timer)	1	2 (RC type) 12bit×12 (SA type)	2	2	2	VLS×1 LLD×1	—	8	Low speed frequency correction/ Analog comparator×2/Melody : Buzzer	✓	—	P-TQFP48-0707-0.50	✓
16bit×4 (use 16bit timer)	1	2 (RC type) 12bit×12 (SA type)	2	2	2	VLS×1 LLD×1	—	8	Low speed frequency correction/ Analog comparator×2/Melody : Buzzer	✓	—	P-TQFP48-0707-0.50	✓
16bit×8 (use 16bit timer)	1	2 (RC type) 10bit×20 (SA type)	2	2	5	VLS×1	—	8	RTC/Low speed frequency correction/ Analog comparator×2/Melody : Buzzer	✓	—	P-TQFP80-1212-0.50	—
16bit×8 (use 16bit timer)	1	2 (RC type) 10bit×20 (SA type)	2	2	5	VLS×1	—	8	RTC/Low speed frequency correction/ Analog comparator×2/Melody : Buzzer	✓	—	P-TQFP100-1414-0.50	—

☆ : Under development

(LAPIS Semiconductor products)

Functions / Features												
ADC (method)	Serial port			Supply voltage detection	LCD driver	External interrupt sources	Others	Industrial Equipment	Notes	Package	Chip Support	
	FC	SSIO	UART									
2 (RC type)	1	1	1	BLD×1	—	5	Low speed frequency correction /Buzzer	—	—	—	✓	
2 (RC type)	1	1	1	BLD×1	—	5	Low speed frequency correction /Buzzer	✓	—	—	✓	
2 (RC type)	1	1	1	BLD×1	—	5	Low speed frequency correction /Buzzer	—	—	P-TQFP48-0707-0.50	✓	
2 (RC type)	1	1	1	BLD×1	—	5	Low speed frequency correction /Buzzer	✓	—	P-TQFP48-0707-0.50	✓	
—	—	1	1	—	—	12 (include 8bit-OR input)	Low speed frequency correction / Analog comparator / Melody : Buzzer / RTC / RNG (Random Number Generator)	—	—	—	✓	
—	—	1	1	—	—	12 (include 8bit-OR input)	Low speed frequency correction / Analog comparator / Melody : Buzzer / RTC / RNG (Random Number Generator)	✓	—	—	✓	

2 (RC type) 12bit×2 (SA type)	1	1	1	BLD×1	Max.400dot 50seg.×8com.	5	Low speed frequency correction/ Melody : Buzzer	—	—	—	✓
2 (RC type) 12bit×2 (SA type)	1	1	1	BLD×1	Max.400dot 50seg.×8com.	5	Low speed frequency correction/ Melody : Buzzer	✓	—	—	✓
2 (RC type) 12bit×2 (SA type)	1	1	1	BLD×1	Max.400dot 50seg.×8com.	5	Low speed frequency correction/ Melody : Buzzer	—	—	P-TQFP120-1414-0.40	✓
2 (RC type) 12bit×2 (SA type)	1	1	1	BLD×1	Max.400dot 50seg.×8com.	5	Low speed frequency correction/ Melody : Buzzer	✓	—	P-TQFP120-1414-0.40	✓
2 (RC type) 12bit×2 (SA type)	1	1	1	BLD×1	Max.800dot 50seg.×16com.	5	Low speed frequency correction/ Melody : Buzzer	—	Low-speed scillation stop detect reset : enable	P-TQFP120-1414-0.40	✓
2 (RC type) 12bit×2 (SA type)	1	1	1	BLD×1	Max.800dot 50seg.×16com.	5	Low speed frequency correction/ Melody : Buzzer	✓	Low-speed scillation stop detect reset : enable	P-TQFP120-1414-0.40	✓
2 (RC type) 12bit×2 (SA type)	1	1	1	BLD×1	Max.800dot 50seg.×16com.	5	Low speed frequency correction/ Melody : Buzzer	—	Low-speed scillation stop detect reset : disable	—	✓
2 (RC type) 12bit×2 (SA type)	1	1	1	BLD×1	Max.800dot 50seg.×16com.	5	Low speed frequency correction/ Melody : Buzzer	✓	Low-speed scillation stop detect reset : disable	—	✓
1 (RC type)	1	1	1	BLD×1	Max.800dot 50seg.×16com.	5	Low speed frequency correction/Melody : Buzzer/ EL Driver/External input voltage detection	—	—	—	✓
1 (RC type)	1	1	1	BLD×1	Max.800dot 50seg.×16com.	5	Low speed frequency correction/Melody : Buzzer/ EL Driver/External input voltage detection	—	—	—	✓
1 (RC type)	1	1	1	BLD×1	Max.672dot 42seg.×16com.	8	Low speed frequency correction/Melody : Buzzer/ EL Driver/External input voltage detection	—	—	—	✓
2 (RC type)	1	1	1	BLD×1	Max.1392dot 58seg.×24com.	5	Low speed frequency correction/ Melody : Buzzer	—	Selectable oscillation stop detection reset : function enable/disable according to mask option	TQFP128-P-1414-0.40	✓
2 (RC type)	1	1	1	BLD×1	Max.512dot 64seg.×8com.	9	Low speed frequency correction/ Melody : Buzzer	—	Selectable oscillation stop detection reset : function enable/disable according to mask option	—	✓
2 (RC type)	1	1	1	BLD×1	Max.512dot 64seg.×8com.	9	Low speed frequency correction/ Melody : Buzzer	—	Selectable oscillation stop detection reset : function enable/disable according to mask option	—	✓
2 (RC type) 12bit×2 (SA type)	1	1	1	BLD×1	Max.1024dot 64seg.×16com.	5	RTC/Low speed frequency correction/ Melody : Buzzer	—	Low-speed scillation stop detect reset : enable	P-LQFP144-2020-0.50	✓
2 (RC type) 12bit×2 (SA type)	1	1	1	BLD×1	Max.1024dot 64seg.×16com.	5	RTC/Low speed frequency correction/ Melody : Buzzer	—	Low-speed scillation stop detect reset : disable	P-LQFP144-2020-0.50	✓
2 (RC type) 12bit×2 (SA type)	1	1	1	BLD×1	Max.1024dot 64seg.×16com.	5	RTC/Low speed frequency correction/ Melody : Buzzer	✓	Low-speed scillation stop detect reset : disable	—	✓
2 (RC type) 12bit×2 (SA type)	1	1	1	BLD×1	Max.1536dot 64seg.×24com.	5	RTC/Low speed frequency correction/ Melody : Buzzer	—	Low-speed scillation stop detect reset : enable	P-LQFP144-2020-0.50	✓
2 (RC type) 12bit×2 (SA type)	1	1	1	BLD×1	Max.1536dot 64seg.×24com.	5	RTC/Low speed frequency correction/ Melody : Buzzer	—	Low-speed scillation stop detect reset : disable	P-LQFP144-2020-0.50	✓
2 (RC type) 12bit×2 (SA type)	1	1	1	BLD×1	Max.1024dot 64seg.×16com.	5	RTC/Low speed frequency correction/ Melody : Buzzer	—	Low-speed scillation stop detect reset : enable	—	✓
2 (RC type) 12bit×2 (SA type)	1	1	1	BLD×1	Max.1024dot 64seg.×16com.	5	RTC/Low speed frequency correction/ Melody : Buzzer	—	Low-speed scillation stop detect reset : disable	P-LQFP144-2020-0.50	✓
2 (RC type) 12bit×2 (SA type)	1	1	1	BLD×1	Max.1536dot 64seg.×24com.	5	RTC/Low speed frequency correction/ Melody : Buzzer	—	Low-speed scillation stop detect reset : enable	—	✓
2 (RC type) 12bit×2 (SA type)	1	1	1	BLD×1	Max.1536dot 64seg.×24com.	5	RTC/Low speed frequency correction/ Melody : Buzzer	—	Low-speed scillation stop detect reset : disable	P-LQFP144-2020-0.50	✓
2 (RC type) 12bit×2 (SA type)	1	1	1	BLD×1	Max.1344dot 56seg.×24com.	9	Low speed frequency correction/ Melody : Buzzer	—	Selectable oscillation stop detection reset : function enable/disable according to mask option	P-LQFP144-2020-0.50	✓
2 (RC type) 12bit×2 (SA type)	1	1	1	BLD×1	Max.1344dot 56seg.×24com.	9	Low speed frequency correction/ Melody : Buzzer	✓	Selectable oscillation stop detection reset : function enable/disable according to mask option	P-LQFP144-2020-0.50	—
2 (RC type) 12bit×2 (SA type)	1	1	1	BLD×1	Max.1024dot 64seg.×16com.	9	Low speed frequency correction/ Melody : Buzzer	—	Selectable oscillation stop detection reset : function enable/disable according to mask option	P-LQFP144-2020-0.50	✓
2 (RC type) 12bit×2 (SA type)	1	1	1	BLD×1	Max.1024dot 64seg.×16com.	9	Low speed frequency correction/ Melody : Buzzer	✓	Selectable oscillation stop detection reset : function enable/disable according to mask option	P-LQFP144-2020-0.50	✓

8bit ML610400 Series

Built-in LCD driver Segments type Low power 8bit MCU

Part No.	Operating Conditions					ROM/RAM				Functions / Features								
	Operating voltage (V)	Operating frequency (Max.)		Minimum instruction execution time	Current consumption (Typ.@HALT)	Operating temperature (°C)	ROM Type	ROM capacity (Byte)	Data Flash capacity (Byte)	RAM capacity (Byte)	port			8bit timer	1kHz timer	PWM	Capture	WDT
		Low speed	High speed								Input	Output	Input/Output					
ML610401	1.25 to 3.6	32.768kHz (Crystal oscillation)	500kHz	2μs/30.5μs	0.9μA	-20 to +70	Mask	6K	—	192	4	12	18	2 (16bit×1)	—	—	2	1
ML610401P	1.25 to 3.6	32.768kHz (Crystal oscillation)	500kHz	2μs/30.5μs	0.9μA	-40 to +85	Mask	6K	—	192	4	12	18	2 (16bit×1)	—	—	2	1
ML610402	1.25 to 3.6	32.768kHz (Crystal oscillation)	500kHz	2μs/30.5μs	0.9μA	-20 to +70	Mask	6K	—	192	4	8	18	2 (16bit×1)	—	—	2	1
ML610402P	1.25 to 3.6	32.768kHz (Crystal oscillation)	500kHz	2μs/30.5μs	0.9μA	-40 to +85	Mask	6K	—	192	4	8	18	2 (16bit×1)	—	—	2	1
ML610403	1.25 to 3.6	32.768kHz (Crystal oscillation)	500kHz	2μs/30.5μs	0.9μA	-20 to +70	Mask	6K	—	192	4	4	18	2 (16bit×1)	—	—	2	1
ML610403P	1.25 to 3.6	32.768kHz (Crystal oscillation)	500kHz	2μs/30.5μs	0.9μA	-40 to +85	Mask	6K	—	192	4	4	18	2 (16bit×1)	—	—	2	1
ML610404	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz	0.5μs/30.5μs	0.9μA	-20 to +70	Mask	8K	—	256	5	12	22	4 (16bit×2)	—	16bit×1	2	1
ML610404P	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz	0.5μs/30.5μs	0.9μA	-40 to +85	Mask	8K	—	256	5	12	22	4 (16bit×2)	—	16bit×1	2	1
ML610405	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz	0.5μs/30.5μs	0.9μA	-20 to +70	Mask	8K	—	256	5	8	22	4 (16bit×2)	—	16bit×1	2	1
ML610405P	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz	0.5μs/30.5μs	0.9μA	-40 to +85	Mask	8K	—	256	5	8	22	4 (16bit×2)	—	16bit×1	2	1
ML610406	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz	0.5μs/30.5μs	0.9μA	-20 to +70	Mask	8K	—	256	5	4	22	4 (16bit×2)	—	16bit×1	2	1
ML610406P	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz	0.5μs/30.5μs	0.9μA	-40 to +85	Mask	8K	—	256	5	4	22	4 (16bit×2)	—	16bit×1	2	1
ML610407	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz	0.5μs/30.5μs	0.9μA	-20 to +70	Mask	16K	—	1K	5	12	22	4 (16bit×2)	—	16bit×1	2	1
ML610407P	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz	0.5μs/30.5μs	0.9μA	-40 to +85	Mask	16K	—	1K	5	12	22	4 (16bit×2)	—	16bit×1	2	1
ML610Q407	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz	0.5μs/30.5μs	0.9μA	-20 to +70	Flash	16K	—	1K	5	12	22	4 (16bit×2)	—	16bit×1	2	1
ML610Q407P	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz	0.5μs/30.5μs	0.9μA	-40 to +85	Flash	16K	—	1K	5	12	22	4 (16bit×2)	—	16bit×1	2	1
ML610Q407A	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz	0.5μs/30.5μs	0.9μA	-20 to +70	Flash	16K	—	1K	5	12	22	4 (16bit×2)	—	16bit×1	2	1
ML610Q407PA	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz	0.5μs/30.5μs	0.9μA	-40 to +85	Flash	16K	—	1K	5	12	22	4 (16bit×2)	—	16bit×1	2	1
ML610Q407D	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz	0.5μs/30.5μs	0.9μA	-20 to +70	Flash	16K	—	1K	5	12	22	4 (16bit×2)	—	16bit×1	2	1
ML610408	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz	0.5μs/30.5μs	0.9μA	-20 to +70	Mask	16K	—	1K	5	8	22	4 (16bit×2)	—	16bit×1	2	1
ML610408P	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz	0.5μs/30.5μs	0.9μA	-40 to +85	Mask	16K	—	1K	5	8	22	4 (16bit×2)	—	16bit×1	2	1
ML610Q408	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz	0.5μs/30.5μs	0.9μA	-20 to +70	Flash	16K	—	1K	5	8	22	4 (16bit×2)	—	16bit×1	2	1
ML610Q408P	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz	0.5μs/30.5μs	0.9μA	-40 to +85	Flash	16K	—	1K	5	8	22	4 (16bit×2)	—	16bit×1	2	1
ML610409	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz	0.5μs/30.5μs	0.9μA	-20 to +70	Mask	16K	—	1K	5	4	22	4 (16bit×2)	—	16bit×1	2	1
ML610409P	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz	0.5μs/30.5μs	0.9μA	-40 to +85	Mask	16K	—	1K	5	4	22	4 (16bit×2)	—	16bit×1	2	1
ML610Q409	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz	0.5μs/30.5μs	0.9μA	-20 to +70	Flash	16K	—	1K	5	4	22	4 (16bit×2)	—	16bit×1	2	1
ML610Q409P	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz	0.5μs/30.5μs	0.9μA	-40 to +85	Flash	16K	—	1K	5	4	22	4 (16bit×2)	—	16bit×1	2	1
ML610Q409A	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz	0.5μs/30.5μs	0.9μA	-20 to +70	Flash	16K	—	1K	5	4	22	4 (16bit×2)	—	16bit×1	2	1
ML610Q411	1.1 to 3.6	32.768kHz (Crystal oscillation)	500kHz	2μs/30.5μs	0.5μA	-20 to +70	Flash	16K	—	1K	6	3	22	4 (16bit×2)	1	16bit×1	2	1
ML610Q411P	1.1 to 3.6	32.768kHz (Crystal oscillation)	500kHz	2μs/30.5μs	0.5μA	-40 to +85	Flash	16K	—	1K	6	3	22	4 (16bit×2)	1	16bit×1	2	1
ML610Q411PA	1.1 to 3.6	32.768kHz (Crystal oscillation)	500kHz	2μs/30.5μs	0.5μA	-40 to +85	Flash	16K	—	1K	6	3	22	4 (16bit×2)	1	16bit×1	2	1
ML610Q412	1.1 to 3.6	32.768kHz (Crystal oscillation)	500kHz	2μs/30.5μs	0.5μA	-20 to +70	Flash	16K	—	1K	6	3	14	4 (16bit×2)	1	16bit×1	2	1
ML610Q412P	1.1 to 3.6	32.768kHz (Crystal oscillation)	500kHz	2μs/30.5μs	0.5μA	-40 to +85	Flash	16K	—	1K	6	3	14	4 (16bit×2)	1	16bit×1	2	1
ML610Q419	1.1 to 3.6	32.768kHz (Crystal oscillation)	4.096MHz 500kHz	0.244μs/2μs/30.5μs	0.9μA	-20 to +70	Flash	64K	4K	2K	6	3	18	4 (16bit×2)	—	16bit×1	2	1
ML610Q419P	1.1 to 3.6	32.768kHz (Crystal oscillation)	4.096MHz 500kHz	0.244μs/2μs/30.5μs	0.9μA	-40 to +85	Flash	64K	4K	2K	6	3	18	4 (16bit×2)	—	16bit×1	2	1

A
Microcontroller

8bit ML610400 Series

Built-in LCD driver Segments type Low power 8bit MCU

Part No.	Operating Conditions					ROM/RAM				Functions / Features								
	Operating voltage (V)	Operating frequency (Max.)		Minimum instruction execution time	Current consumption (Typ.@HALT)	Operating temperature (°C)	ROM Type	ROM capacity (Byte)	Data Flash capacity (Byte)	RAM capacity (Byte)	port			8bit timer	1kHz timer	PWM	Capture	WDT
		Low speed	High speed								Input	Output	Input/Output					
ML610Q419C	1.1 to 3.6	32.768kHz (Crystal oscillation)	4.096MHz 500kHz	0.244μs/ 2μs/ 30.5μs	0.9μA	-20 to +70	Flash	64K	4K	2K	6	3	26	4 (16bit×2)	-	16bit×1	2	1
ML610Q419PC	1.1 to 3.6	32.768kHz (Crystal oscillation)	4.096MHz 500kHz	0.244μs/ 2μs/ 30.5μs	0.9μA	-40 to +85	Flash	64K	4K	2K	6	3	26	4 (16bit×2)	-	16bit×1	2	1
ML610Q461	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz 500kHz	0.5μs/ 2μs/ 30.5μs	0.9μA	-20 to +70	Flash	16K	-	1K	5	10	14	4 (16bit×2)	-	16bit×1	2	1
ML610Q462	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz 500kHz	0.5μs/ 2μs/ 30.5μs	0.9μA	-20 to +70	Flash	16K	-	1K	5	6	14	4 (16bit×2)	-	16bit×1	2	1
ML610Q463	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz 500kHz	0.5μs/ 2μs/ 30.5μs	0.9μA	-20 to +70	Flash	16K	-	1K	5	2	14	4 (16bit×2)	-	16bit×1	2	1
ML610471	1.25 to 3.6	32.768kHz (Crystal oscillation)	500kHz	2μs/ 30.5μs	0.8μA	-20 to +70	Mask	8K	-	512	4	10	7	2 (16bit×1)	-	-	2	1
ML610Q471	1.25 to 3.6	32.768kHz (Crystal oscillation)	500kHz	2μs/ 30.5μs	0.8μA	-20 to +70	Flash	8K	-	512	4	10	7	2 (16bit×1)	-	-	2	1
ML610Q471P	1.25 to 3.6	32.768kHz (Crystal oscillation)	500kHz	2μs/ 30.5μs	0.8μA	-40 to +85	Flash	8K	-	512	4	10	7	2 (16bit×1)	-	-	2	1
ML610472	1.25 to 3.6	32.768kHz (Crystal oscillation)	500kHz	2μs/ 30.5μs	0.8μA	-20 to +70	Mask	8K	-	512	4	6	7	2 (16bit×1)	-	-	2	1
ML610Q472	1.25 to 3.6	32.768kHz (Crystal oscillation)	500kHz	2μs/ 30.5μs	0.8μA	-20 to +70	Flash	8K	-	512	4	6	7	2 (16bit×1)	-	-	2	1
ML610Q472P	1.25 to 3.6	32.768kHz (Crystal oscillation)	500kHz	2μs/ 30.5μs	0.8μA	-40 to +85	Flash	8K	-	512	4	6	7	2 (16bit×1)	-	-	2	1
ML610473	1.25 to 3.6	32.768kHz (Crystal oscillation)	500kHz	2μs/ 30.5μs	0.8μA	-20 to +70	Mask	8K	-	512	4	2	7	2 (16bit×1)	-	-	2	1
ML610Q473	1.25 to 3.6	32.768kHz (Crystal oscillation)	500kHz	2μs/ 30.5μs	0.8μA	-20 to +70	Flash	8K	-	512	4	2	7	2 (16bit×1)	-	-	2	1
ML610Q473P	1.25 to 3.6	32.768kHz (Crystal oscillation)	500kHz	2μs/ 30.5μs	0.8μA	-40 to +85	Flash	8K	-	512	4	2	7	2 (16bit×1)	-	-	2	1
ML610474	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz 500kHz	0.5μs/ 2μs/ 30.5μs	0.25μA	-20 to +70	Mask	16K	-	1K	4	10	10	6 (16bit×3)	-	-	2	1
ML610Q474	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz 500kHz	0.5μs/ 2μs/ 30.5μs	0.25μA	-20 to +70	Flash	16K	-	1K	4	10	10	6 (16bit×3)	-	-	2	1
ML610475	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz 500kHz	0.5μs/ 2μs/ 30.5μs	0.25μA	-20 to +70	Mask	16K	-	1K	4	6	10	6 (16bit×3)	-	-	2	1
ML610Q475	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz 500kHz	0.5μs/ 2μs/ 30.5μs	0.25μA	-20 to +70	Flash	16K	-	1K	4	6	10	6 (16bit×3)	-	-	2	1
ML610476	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz 500kHz	0.5μs/ 2μs/ 30.5μs	0.25μA	-20 to +70	Mask	16K	-	1K	4	2	10	6 (16bit×3)	-	-	2	1
ML610Q476	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz 500kHz	0.5μs/ 2μs/ 30.5μs	0.25μA	-20 to +70	Flash	16K	-	1K	4	2	10	6 (16bit×3)	-	-	2	1
ML610477	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz 500kHz	0.5μs/ 2μs/ 30.5μs	0.51μA	-20 to +70	Mask	24K	-	2K	4	10	15	6 (16bit×3)	-	-	2	1
ML610Q477	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz 500kHz	0.5μs/ 2μs/ 30.5μs	0.8μA	-20 to +70	Flash	24K	-	2K	4	10	15	6 (16bit×3)	-	-	2	1
ML610Q477P	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz 500kHz	0.5μs/ 2μs/ 30.5μs	0.8μA	-40 to +85	Flash	24K	-	2K	4	10	15	6 (16bit×3)	-	-	2	1
ML610478	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz 500kHz	0.5μs/ 2μs/ 30.5μs	0.51μA	-20 to +70	Mask	24K	-	2K	4	6	15	6 (16bit×3)	-	-	2	1
ML610Q478	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz 500kHz	0.5μs/ 2μs/ 30.5μs	0.8μA	-20 to +70	Flash	24K	-	2K	4	6	15	6 (16bit×3)	-	-	2	1
ML610Q478P	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz 500kHz	0.5μs/ 2μs/ 30.5μs	0.8μA	-40 to +85	Flash	24K	-	2K	4	6	15	6 (16bit×3)	-	-	2	1
ML610479	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz 500kHz	0.5μs/ 2μs/ 30.5μs	0.51μA	-20 to +70	Mask	24K	-	2K	4	2	15	6 (16bit×3)	-	-	2	1
ML610Q479	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz 500kHz	0.5μs/ 2μs/ 30.5μs	0.8μA	-20 to +70	Flash	24K	-	2K	4	2	15	6 (16bit×3)	-	-	2	1
ML610Q479P	1.25 to 3.6	32.768kHz (Crystal oscillation)	2MHz 500kHz	0.5μs/ 2μs/ 30.5μs	0.8μA	-40 to +85	Flash	24K	-	2K	4	2	15	6 (16bit×3)	-	-	2	1

A
Microcontroller

(LAPIS Semiconductor products)

	Functions / Features								Industrial Equipment	Notes	Package	Chip Support
	ADC (method)	Serial port			Supply voltage detection	LCD driver	External interrupt sources	Others				
		FC	SSIO	UART								
2 (RC type) 12bit×4 (SA type)	1	2	1	BLD×1	Max.160dot 40seg.×4com.	5	Low speed frequency correction/ Melody : Buzzer	—	—	P-TQFP100-1414-0.50	✓	
2 (RC type) 12bit×4 (SA type)	1	2	1	BLD×1	Max.160dot 40seg.×4com.	5	Low speed frequency correction/ Melody : Buzzer	✓	—	P-TQFP100-1414-0.50	✓	
2 (RC type)	—	1	1	—	Max.64dot 16seg.×4com.	5	Low speed frequency correction	—	—	P-TQFP64-1010-0.50	—	
2 (RC type)	—	1	1	—	Max.80dot 20seg.×4com.	5	Low speed frequency correction	—	—	P-TQFP64-1010-0.50	—	
2 (RC type)	—	1	1	—	Max.96dot 24seg.×4com.	5	Low speed frequency correction	—	—	P-TQFP64-1010-0.50	—	
1 (RC type)	—	—	1	—	Max.55dot 11seg.×5com.	4	Low speed frequency correction	—	—	—	✓	
1 (RC type)	—	—	1	—	Max.55dot 11seg.×5com.	4	Low speed frequency correction/ No debugging function	—	—	P-TQFP48-0707-0.50	✓	
1 (RC type)	—	—	1	—	Max.55dot 11seg.×5com.	4	Low speed frequency correction/ No debugging function	✓	—	P-TQFP48-0707-0.50	✓	
1 (RC type)	—	—	1	—	Max.75dot 15seg.×5com.	4	Low speed frequency correction	—	—	—	✓	
1 (RC type)	—	—	1	—	Max.75dot 15seg.×5com.	4	Low speed frequency correction/ No debugging function	—	—	P-TQFP48-0707-0.50	✓	
1 (RC type)	—	—	1	—	Max.75dot 15seg.×5com.	4	Low speed frequency correction/ No debugging function	✓	—	P-TQFP48-0707-0.50	✓	
1 (RC type)	—	—	1	—	Max.95dot 19seg.×5com.	4	Low speed frequency correction	—	—	—	✓	
1 (RC type)	—	—	1	—	Max.95dot 19seg.×5com.	4	Low speed frequency correction/ No debugging function	—	—	P-TQFP48-0707-0.50	✓	
1 (RC type)	—	—	1	—	Max.95dot 19seg.×5com.	4	Low speed frequency correction/ No debugging function	✓	—	P-TQFP48-0707-0.50	✓	
—	—	—	1	—	Max.135dot 27seg.×5com.	10 (include 6bit-OR input)	Low speed frequency correction/ Melody : Buzzer/ Analog comparator	—	Selectable oscillation stop detection reset : function enable according to software	—	✓	
—	—	—	1	—	Max.135dot 27seg.×5com.	10 (include 6bit-OR input)	Low speed frequency correction/ Melody : Buzzer/ Analog comparator	—	Selectable oscillation stop detection reset : function enable according to software	—	✓	
—	—	—	1	—	Max.155dot 31seg.×5com.	10 (include 6bit-OR input)	Low speed frequency correction/ Melody : Buzzer/ Analog comparator	—	Selectable oscillation stop detection reset : function enable according to software	—	✓	
—	—	—	1	—	Max.155dot 31seg.×5com.	10 (include 6bit-OR input)	Low speed frequency correction/ Melody : Buzzer/ Analog comparator	—	Selectable oscillation stop detection reset : function enable according to software	—	✓	
—	—	—	1	—	Max.175dot 35seg.×5com.	10 (include 6bit-OR input)	Low speed frequency correction/ Melody : Buzzer/ Analog comparator	—	Selectable oscillation stop detection reset : function enable according to software	—	✓	
—	—	—	1	—	Max.175dot 35seg.×5com.	10 (include 6bit-OR input)	Low speed frequency correction/ Melody : Buzzer/ Analog comparator	—	Selectable oscillation stop detection reset : function enable according to software	—	✓	
1 (RC type)	—	—	1	—	Max.135dot 27seg.×5com.	12 (include 8bit-OR input)	Low speed frequency correction/Analog comparator	—	—	—	✓	
1 (RC type)	—	—	1	—	Max.135dot 27seg.×5com.	12 (include 8bit-OR input)	Low speed frequency correction/Analog comparator	—	—	—	✓	
1 (RC type)	—	—	1	—	Max.135dot 27seg.×5com.	12 (include 8bit-OR input)	Low speed frequency correction/Analog comparator	✓	—	—	✓	
1 (RC type)	—	—	1	—	Max.155dot 31seg.×5com.	12 (include 8bit-OR input)	Low speed frequency correction/Analog comparator	—	—	—	✓	
1 (RC type)	—	—	1	—	Max.155dot 31seg.×5com.	12 (include 8bit-OR input)	Low speed frequency correction/Analog comparator	—	—	—	✓	
1 (RC type)	—	—	1	—	Max.155dot 31seg.×5com.	12 (include 8bit-OR input)	Low speed frequency correction/Analog comparator	✓	—	—	✓	
1 (RC type)	—	—	1	—	Max.175dot 35seg.×5com.	12 (include 8bit-OR input)	Low speed frequency correction/Analog comparator	—	—	—	✓	
1 (RC type)	—	—	1	—	Max.175dot 35seg.×5com.	12 (include 8bit-OR input)	Low speed frequency correction/Analog comparator	—	—	—	✓	
1 (RC type)	—	—	1	—	Max.175dot 35seg.×5com.	12 (include 8bit-OR input)	Low speed frequency correction/Analog comparator	✓	—	—	✓	

A
Microcontroller

High Noise Immunity MCU

8bit ML610100 Series

Standard Type 8bit Low power MCU													
Part No.	Operating Conditions					ROM/RAM				Functions / Features			
	Operating voltage (V)	Operating frequency (Max.)		Minimum instruction execution time	Current consumption (Typ.@HALT)	Operating temperature (°C)	ROM Type	ROM capacity (Byte)	Data Flash capacity (Byte)	RAM capacity (Byte)	port		
		Low speed	High speed								Input	Output	Input/Output
ML610Q101	2.7 to 5.5	32.768kHz (Internal RC oscillation)	8.192MHz	0.122μs/30.5μs	—	-40 to +85	Flash	4K	—	256	—	—	11
ML610Q102	2.7 to 5.5	32.768kHz (Internal RC oscillation)	8.192MHz	0.122μs/30.5μs	—	-40 to +85	Flash	6K	—	256	—	—	11
ML610Q111	2.7 to 5.5	32.768kHz (Internal RC oscillation)	8.192MHz	0.122μs/30.5μs	—	-40 to +105	Flash	24K	4K	2K	—	—	15
ML610Q112	2.7 to 5.5	32.768kHz (Internal RC oscillation)	8.192MHz	0.122μs/30.5μs	—	-40 to +105	Flash	32K	4K	4K	—	—	25

Built-in LCD driver Segments type Low power 8bit MCU													
ML610Q172	2.2 to 5.5	32.768kHz (Internal RC oscillation/ Crystal oscillation)	8.192MHz	0.122μs/30.5μs	2.0μA	-40 to +85	Flash	128K	2K	4K	6	2	37
ML610Q173	2.2 to 5.5	32.768kHz (Internal RC oscillation/ Crystal oscillation)	8.192MHz	0.122μs/30.5μs	2.0μA	-40 to +85	Flash	128K	2K	4K	6	2	37
ML610Q174	2.2 to 5.5	32.768kHz (Internal RC oscillation/ Crystal oscillation)	8.192MHz	0.122μs/30.5μs	2.0μA	-40 to +85	Flash	128K	2K	4K	6	6	49
ML610Q178	2.2 to 5.5	32.768kHz (Internal RC oscillation/ Crystal oscillation)	8.192MHz	0.122μs/30.5μs	2.0μA	-40 to +85	Flash	128K	—	4K	7	8	59

16bit ML620100 Series

Standard Type 16bit Low power MCU													
Part No.	Operating Conditions					ROM/RAM				Functions / Features			
	Operating voltage (V)	Operating frequency (Max.)		Minimum instruction execution time	Current consumption (Typ.@HALT)	Operating temperature (°C)	ROM Type	ROM capacity (Byte)	Data Flash capacity (Byte)	RAM capacity (Byte)	port		
		Low speed	High speed								Input	Output	Input/Output
☆ ML620Q131	1.6 to 5.5	32.768kHz (Internal RC oscillation)	16.384MHz	61.0 ns/30.5μs	3.5 (T.B.D)	-40 to +105	Flash	8K	4K	2K	—	—	11
☆ ML620Q132	1.6 to 5.5	32.768kHz (Internal RC oscillation)	16.384MHz	61.0 ns/30.5μs	3.5 (T.B.D)	-40 to +105	Flash	16K	4K	2K	—	—	11
☆ ML620Q133	1.6 to 5.5	32.768kHz (Internal RC oscillation)	16.384MHz	61.0 ns/30.5μs	3.5 (T.B.D)	-40 to +105	Flash	20K	4K	2K	—	—	11
☆ ML620Q134	1.6 to 5.5	32.768kHz (Internal RC oscillation)	16.384MHz	61.0 ns/30.5μs	3.5 (T.B.D)	-40 to +105	Flash	16K	4K	2K	—	—	15
☆ ML620Q135	1.6 to 5.5	32.768kHz (Internal RC oscillation)	16.384MHz	61.0 ns/30.5μs	3.5 (T.B.D)	-40 to +105	Flash	20K	4K	2K	—	—	15
New ML620Q151	1.8 to 5.5	32.768kHz (Internal RC oscillation/ Crystal oscillation)	8.192MHz	0.122μs/30.5μs	2.5 (Crystal oscillation)(T.B.D) 3.5 (Internal RC oscillation)(T.B.D)	-40 to +105	Flash	32K	2K	2K	5 (Use crystal oscillation) 6 (Not use crystal oscillation)	4	30 (Use crystal oscillation) 31 (Not use crystal oscillation)
New ML620Q152	1.8 to 5.5	32.768kHz (Internal RC oscillation/ Crystal oscillation)	8.192MHz	0.122μs/30.5μs	2.5 (Crystal oscillation)(T.B.D) 3.5 (Internal RC oscillation)(T.B.D)	-40 to +105	Flash	48K	2K	2K	5 (Use crystal oscillation) 6 (Not use crystal oscillation)	4	30 (Use crystal oscillation) 31 (Not use crystal oscillation)
New ML620Q153	1.8 to 5.5	32.768kHz (Internal RC oscillation/ Crystal oscillation)	8.192MHz	0.122μs/30.5μs	2.5 (Crystal oscillation)(T.B.D) 3.5 (Internal RC oscillation)(T.B.D)	-40 to +105	Flash	64K	2K	2K	5 (Use crystal oscillation) 6 (Not use crystal oscillation)	4	30 (Use crystal oscillation) 31 (Not use crystal oscillation)
New ML620Q154	1.8 to 5.5	32.768kHz (Internal RC oscillation/ Crystal oscillation)	8.192MHz	0.122μs/30.5μs	2.5 (Crystal oscillation)(T.B.D) 3.5 (Internal RC oscillation)(T.B.D)	-40 to +105	Flash	32K	2K	2K	6 (Use crystal oscillation) 7 (Not use crystal oscillation)	4	33 (Use crystal oscillation) 34 (Not use crystal oscillation)
New ML620Q155	1.8 to 5.5	32.768kHz (Internal RC oscillation/ Crystal oscillation)	8.192MHz	0.122μs/30.5μs	2.5 (Crystal oscillation)(T.B.D) 3.5 (Internal RC oscillation)(T.B.D)	-40 to +105	Flash	48K	2K	2K	6 (Use crystal oscillation) 7 (Not use crystal oscillation)	4	33 (Use crystal oscillation) 34 (Not use crystal oscillation)
New ML620Q156	1.8 to 5.5	32.768kHz (Internal RC oscillation/ Crystal oscillation)	8.192MHz	0.122μs/30.5μs	2.5 (Crystal oscillation)(T.B.D) 3.5 (Internal RC oscillation)(T.B.D)	-40 to +105	Flash	64K	2K	2K	6 (Use crystal oscillation) 7 (Not use crystal oscillation)	4	33 (Use crystal oscillation) 34 (Not use crystal oscillation)
New ML620Q157	1.8 to 5.5	32.768kHz (Internal RC oscillation/ Crystal oscillation)	8.192MHz	0.122μs/30.5μs	2.5 (Crystal oscillation)(T.B.D) 3.5 (Internal RC oscillation)(T.B.D)	-40 to +105	Flash	32K	2K	2K	6 (Use crystal oscillation) 7 (Not use crystal oscillation)	4	45 (Use crystal oscillation) 46 (Not use crystal oscillation)
New ML620Q158	1.8 to 5.5	32.768kHz (Internal RC oscillation/ Crystal oscillation)	8.192MHz	0.122μs/30.5μs	2.5 (Crystal oscillation)(T.B.D) 3.5 (Internal RC oscillation)(T.B.D)	-40 to +105	Flash	48K	2K	2K	6 (Use crystal oscillation) 7 (Not use crystal oscillation)	4	45 (Use crystal oscillation) 46 (Not use crystal oscillation)
New ML620Q159	1.8 to 5.5	32.768kHz (Internal RC oscillation/ Crystal oscillation)	8.192MHz	0.122μs/30.5μs	2.5 (Crystal oscillation)(T.B.D) 3.5 (Internal RC oscillation)(T.B.D)	-40 to +105	Flash	64K	2K	2K	6 (Use crystal oscillation) 7 (Not use crystal oscillation)	4	45 (Use crystal oscillation) 46 (Not use crystal oscillation)

A
Microcontroller

(LAPIS Semiconductor products)

	Functions / Features												Industrial Equipment	Notes	Package	Chip Support
	8bit timer	16bit timer	PWM	WDT	ADC(method)	Serial port			Supply voltage detection	LCD driver	External interrupt sources	Others				
						PC	SSIO	UART								
6 (16bit×3)	—	16bit×1 (with dead time)	1	10bit×6 (SA type)	—	—	1	VLS×2	—	5	Analog comparator×2	✓	—	P-SSOP16-0225-0.65 P-WQFN16-0404-0.50	—	
6 (16bit×3)	—	16bit×1 (with dead time)	1	10bit×6 (SA type)	—	—	1	VLS×2	—	5	Analog comparator×2	✓	—	P-SSOP16-0225-0.65 P-WQFN16-0404-0.50	—	
6 (16bit×3)	—	16bit×4 (Complementary type)	1	10bit×6 (SA type)	1	1	2	VLS×2	—	7	Analog comparator×2	✓	—	P-TSSOP20-0225-0.65	—	
6 (16bit×3)	—	16bit×4 (Complementary type)	1	10bit×8 (SA type)	1	1	2	VLS×2	—	7	Analog comparator×2	✓	—	P-LQFP32-0707-0.80	—	
6 (16bit×3)	—	16bit×3 (Supports IGBT control)	1	10bit×12 (SA type)	1	2	2	BLD×1	Max. 96dot 24seg. ×4com.	4	Low speed frequency correction	—	—	QFP64-P-1414-0.80	—	
6 (16bit×3)	—	16bit×3 (Supports IGBT control)	1	10bit×8 (SA type)	1	2	2	BLD×1	Max. 96dot 24seg. ×4com.	4	Low speed frequency correction/ Analog comparator	—	—	QFP64-P-1414-0.80	—	
6 (16bit×3)	—	16bit×3 (Supports IGBT control)	1	10bit×12 (SA type)	1	2	2	BLD×1	Max. 128dot 32seg. ×4com.	4	Low speed frequency correction/ Analog comparator	—	—	QFP80-P-1420-0.80	—	
6 (16bit×3)	—	16bit×2 (Supports IGBT control)	1	10bit×16 (SA type)	1	2	2	BLD×1	Max. 160dot 40seg. ×4com.	5	Low speed frequency correction/ Analog comparator	—	—	P-QFP100-1420-0.65	—	

(LAPIS Semiconductor products)

	Functions / Features												Industrial Equipment	Notes	Package	Chip Support
	8bit timer	16bit timer	PWM	WDT	ADC(method)	Serial port			Supply voltage detection	LCD driver	External interrupt sources	Others				
						PC	SSIO	UART								
8 (16bit×4)	—	16bit×1 (Complementary type)	1	10bit×6 (SA type)	1	1	1	LLD×1 VLS×1	—	5	Analog comparator×2	✓	—	P-SSOP16-0225-0.65 P-WQFN16-0404-0.50	—	
8 (16bit×4)	—	16bit×1 (Complementary type)	1	10bit×6 (SA type)	1	1	1	LLD×1 VLS×1	—	5	Analog comparator×2	✓	—	P-SSOP16-0225-0.65 P-WQFN16-0404-0.50	—	
8 (16bit×4)	—	16bit×1 (Complementary type)	1	10bit×6 (SA type)	1	1	1	LLD×1 VLS×1	—	5	Analog comparator×2	✓	—	P-SSOP16-0225-0.65 P-WQFN16-0404-0.50	—	
8 (16bit×4)	—	16bit×1 (Complementary type)	1	10bit×8 (SA type)	1	1	1	LLD×1 VLS×1	—	5	Analog comparator×2	✓	—	P-TSSOP20-0225-0.65	—	
8 (16bit×4)	—	16bit×1 (Complementary type)	1	10bit×8 (SA type)	1	1	1	LLD×1 VLS×1	—	5	Analog comparator×2	✓	—	P-TSSOP20-0225-0.65	—	
2 (16bit×1)	4	16bit×4 (Complementary type)	1	10bit×12 (SA type)	1	1	1	LLD×1	—	7	Analog comparator	—	—	P-TQFP48-0707-0.50	—	
2 (16bit×1)	4	16bit×4 (Complementary type)	1	10bit×12 (SA type)	1	1	1	LLD×1	—	7	Analog comparator	—	—	P-TQFP48-0707-0.50	—	
2 (16bit×1)	4	16bit×4 (Complementary type)	1	10bit×12 (SA type)	1	1	1	LLD×1	—	7	Analog comparator	—	—	P-TQFP48-0707-0.50	—	
2 (16bit×1)	4	16bit×4 (Complementary type)	1	10bit×12 (SA type)	1	1	1	LLD×1	—	8	Analog comparator	—	—	P-TQFP52-1010-0.65	—	
2 (16bit×1)	4	16bit×4 (Complementary type)	1	10bit×12 (SA type)	1	1	1	LLD×1	—	8	Analog comparator	—	—	P-TQFP52-1010-0.65	—	
2 (16bit×1)	4	16bit×4 (Complementary type)	1	10bit×12 (SA type)	1	1	1	LLD×1	—	8	Analog comparator	—	—	P-TQFP52-1010-0.65	—	
2 (16bit×1)	4	16bit×4 (Complementary type)	1	10bit×12 (SA type)	1	1	1	LLD×1	—	8	Analog comparator	—	—	P-QFP64-1414-0.80	—	
2 (16bit×1)	4	16bit×4 (Complementary type)	1	10bit×12 (SA type)	1	1	1	LLD×1	—	8	Analog comparator	—	—	P-QFP64-1414-0.80	—	
2 (16bit×1)	4	16bit×4 (Complementary type)	1	10bit×12 (SA type)	1	1	1	LLD×1	—	8	Analog comparator	—	—	P-QFP64-1414-0.80	—	

☆ : Under development

Built-in Speech Output Function MCU

8bit ML610300 Series

Standard Type 8bit Low power MCU

Part No.	Operating Conditions						ROM/RAM				Functions / Features			
	Operating voltage (V)	Operating frequency (Max.)		Minimum instruction execution time	Current consumption (Typ.@HALT)	Operating temperature (°C)	ROM Type	ROM capacity (Byte)	Data Flash capacity (Byte)	Memory for sound	RAM capacity (Byte)	port		
		Low speed	High speed									Input	Output	Input/Output
New ML610Q304	2.0 to 5.5	32.768kHz (Internal RC oscillation)	8.192MHz	0.122µs/30.5µs	2.7µA	-40 to +85	Flash	96K	2K	Flash ROM	1K	1	3	11
ML610Q359	2.2 to 3.6	32.768kHz (Crystal oscillation)	8.192MHz	0.122µs/30.5µs	1.7µA	-40 to +85	Flash	160K	3K	Flash ROM	2K	8	3	29
ML610Q360	2.2 to 3.6	32.768kHz (Crystal oscillation)	8.192MHz	0.122µs/30.5µs	1.7µA	-40 to +85	Flash P2ROM	160K	3K	P2ROM: 16M bit	2K	8	3	29

Built-in LCD driver Segments type Low power 8bit MCU

ML610Q380	2.2 to 5.5	32.768kHz (Internal RC oscillation/ Crystal oscillation)	8.192MHz	0.122µs/30.5µs	2.0µA	-40 to +70	Flash	128K	—	Flash ROM	2K	7	4	34
-----------	------------	--	----------	----------------	-------	------------	-------	------	---	-----------	----	---	---	----

Sensor Hub MCU

8bit ML610790 Family

U8 Core Based Standard Type 8bit Low power MCU

Part No.	Operating Conditions						ROM/RAM				Functions / Features		
	Operating voltage (V)	Operating frequency (Max.)		Minimum instruction execution time	Current consumption (Typ.@HALT)	Operating temperature (°C)	ROM Type	ROM capacity (Byte)	Data Flash capacity (Byte)	RAM capacity (Byte)	port		
		Low speed	High speed								Input	Output	Input/Output
ML610Q793	VDD:1.7 to 1.9 AVDD:2.5 to 3.6	32.768kHz (External clock)	4.096MHz	0.25µs/30.5µs	0.6µA	-30 to +85	Flash	64K	—	4K	—	—	21
ML610Q794G	2.5 to 3.6	32.768kHz (Crystal oscillation)	4.096MHz	0.25µs/30.5µs	1.1µA	-30 to +85	Flash	64K	—	4K	—	—	21

32bit ML630790 Family

ARM Cortex-M0 Based Standard Type 32bit Low power MCU

Part No.	Operating Conditions						ROM/RAM				Functions / Features		
	Operating voltage (V)	Operating frequency (Max.)		Minimum instruction execution time	Current consumption (Typ.@SLEEPDEEP)	Operating temperature (°C)	ROM Type	ROM capacity (Byte)	Data Flash capacity (Byte)	RAM capacity (Byte)	port		
		Low speed	High speed								Input	Output	Input/Output
New ML630Q791	VDD:1.7 to 1.9	32.768kHz (External clock)	32MHz	—	2.5µA	-40 to +85	Flash	128K	—	16K	—	—	7

ARM-Based MCU

32bit MCU ML674xxx/ML675xxx

For General-purpose Applications

Part No.	Built-in Memory			CPU Core	Operating Frequency (Max.)	Operating Condition		
	ROM/Flash	RAM	Cash			Supply Voltage (V)	Operating Temperature (°C)	Supply Current (Typ.)
ML674001	—	32KByte	—	ARM7TDMI	33MHz	I/O:3.0 to 3.6 core:2.25 to 2.75	-40 to 85	52mA (33MHz, when using external ROM)
ML675001			8KByte unified		60MHz			92mA (60MHz, when using external ROM)

(LAPIS Semiconductor products)

Functions / Features														Industrial Equipment	Notes	Package	Chip Support
8bit timer	PWM	WDT	ADC (method)	Serial port			Supply voltage detection	LCD driver	External interrupt sources	SP Amp Output(W)/Class	Others						
				I ² C	SSIO	UART											
4 (16bit×2)	—	1	10bit×3 (SA type)	1	2	1	—	—	9	1.0 (@5V) /D class	Speech function/ ADPCM decoder/ Built-in speaker amp	✓	—	P-QFN28-0505-0.50	—		
8 (16bit×4)	—	1	12bit×4 (SA type)	—	2	2	VLS×1	—	7	0.5 (@3V) /AB class	Speech function/ ADPCM decoder/ Built-in speaker amp	✓	—	P-TQFP64-1010-0.50	—		
8 (16bit×4)	—	1	12bit×4 (SA type)	—	2	2	VLS×1	—	7	0.5 (@3V) /AB class	Speech function/ ADPCM decoder/ Built-in speaker amp	✓	—	P-TQFP64-1010-0.50	—		
6 (16bit×3)	16bit×2	1	10bit×8 (SA type)	1	2	2	BLD×1	Max. 96dot 24seg. ×4com.	5	0.6 (@5V) /AB class	Speech function/ ADPCM decoder/ Built-in speaker amp	—	—	P-QFP80-1414-0.65	—		

(LAPIS Semiconductor products)

Functions / Features											Industrial Equipment	Notes	Package	Chip Support
8bit timer	PWM	WDT	ADC (method)	Serial port				External interrupt sources	Others					
				I ² C	SSIO	UART	I ² C/SPI (for Host Communication)							
6 (16bit×3)	—	1	12bit×3 (SA type)	1	1	2	1	16	16bit Square Root, Multiply, Divider, Host I/F (SPI/I ² C/Logging RAM:8KB)	—	—	S-UFLGA48-3.06×2.96-0.40 (WCSP48)	—	
6 (16bit×3)	—	1	12bit×2 (SA type)	1	1	2	1	16	16bit Square Root, Multiply, Divider, Host I/F (SPI/I ² C/Logging RAM:8KB)	—	—	TQFP-48-P-0707-0.50	—	

(LAPIS Semiconductor products)

Functions / Features										Industrial Equipment	Notes	Package	Chip Support
8bit timer	PWM	WDT	ADC (method)	Serial port				External interrupt sources	Others				
				I ² C	SSIO	UART	I ² C/SPI (for Host Communication)						
8 (16bit×4)	1	1	—	2	—	1	1	7	Square Root, Division operations, Host I/F (Built-in 512 byte communication register)	—	—	(WCSP)	—

(LAPIS Semiconductor products)

Peripherals									Package
General-purpose Ports	Timer	PWM	WDT	A/D	Serial Ports	Interrupt Internal/ External	Additional Peripheral Functions		
42	7	16bit×2	16bit×1	10bit A/D 4ch	UART 2ch SSIO 2ch I ² C 1ch	23/5	DMA controller 2ch External memory controller [ROM (Flash), SRAM, DRAM (EDO/SDRAM), IO] STOP mode		LQFP144-P-2020-0.50 P-LFBGA144-1111-0.8

Power-Saving Solar Power Supply Control LSI (LAPIS Semiconductor products)

Secondary battery control LSI

Part No.	Operating Conditions				Functions/Features			
	Operating voltage VBAT (V)	Operating voltage VSC (V)	VBAT side Current consumption (A)	Operating temperature (°C)	VBAT-VDO Output Impedance	VSC-VBAT Input Impedance	OCP (Overcharge prevention) voltage (V)	BOD (Brown out detection) voltage (V)
ML9077	0.0 to 3.2	0.0 to 3.6	80n	-20 to +70	2.5Ω or less/20mA @VBAT ≥1.8V	100Ω or less /1mA @VSC ≥2V	2.6/3.1	1.15/1.8

Primary battery control LSI

Part No.	Operating Conditions				Functions/Features		
	Operating voltage VBAT (V)	Operating voltage VSC (V)	VBAT side Current consumption (A)	Operating temperature (°C)	VBAT-VDO Output Impedance	VSC-VDO Output Impedance	Regulator voltage solar limiter voltage (V)
ML9078-001	1.1 to 3.6	0.0 to 4.0	80n	-20 to +70	75Ω or less/2mA @VBAT ≥2V	65Ω or less/2mA @VBAT ≥2V	3.3/1.65
ML9078-002	1.1 to 3.6	0.0 to 4.0	80n	-20 to +70	75Ω or less/2mA @VBAT ≥2V	65Ω or less/2mA @VBAT ≥2V	3.0/1.5
ML9078-003	1.1 to 3.6	0.0 to 4.0	80n	-20 to +70	75Ω or less/2mA @VBAT ≥2V	65Ω or less/2mA @VBAT ≥2V	VBAT