

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: [info@chipsmall.com](mailto:info@chipsmall.com) Web: [www.chipsmall.com](http://www.chipsmall.com)

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China

## MM74HC151 8-Channel Digital Multiplexer

### General Description

The MM74HC151 high speed Digital multiplexer utilizes advanced silicon-gate CMOS technology. Along with the high noise immunity and low power dissipation of standard CMOS integrated circuits, it possesses the ability to drive 10 LS-TTL loads. The MM74HC151 selects one of the 8 data sources, depending on the address presented on the A, B, and C inputs. It features both true (Y) and complement (W) outputs. The STROBE input must be at a low logic level to enable this multiplexer. A high logic level at the STROBE forces the W output HIGH and the Y output LOW.

The 74HC logic family is functionally as well as pin-out compatible with the standard 74LS logic family. All inputs are protected from damage due to static discharge by internal diode clamps to  $V_{CC}$  and ground.

### Features


- Typical propagation delay data select to output Y: 26 ns
- Wide operating supply voltage range: 2–6V
- Low input current: 1  $\mu$ A maximum
- Low quiescent supply current: 80  $\mu$ A maximum (74HC)
- High output drive current: 4 mA minimum

### Ordering Code:

Order Number	Package Number	Package Description
MM74HC151M	M16A	16-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-012, 0.150" Narrow
MM74HC151SJ	M16D	16-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide
MM74HC151MTC	MTC16	16-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide
MM74HC151N	N16E	16-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300" Wide

Devices also available in Tape and Reel. Specify by appending the suffix letter "X" to the ordering code.

### Connection Diagram




### Truth Table

Inputs			Outputs	
Select			Strobe	
C	B	A	S	Y      W
X	X	X	H	L      H
L	L	L	L	D0 $\overline{D0}$
L	L	H	L	D1 $\overline{D1}$
L	H	L	L	D2 $\overline{D2}$
L	H	H	L	D3 $\overline{D3}$
H	L	L	L	D4 $\overline{D4}$
H	L	H	L	D5 $\overline{D5}$
H	H	L	L	D6 $\overline{D6}$
H	H	H	L	D7 $\overline{D7}$

H = HIGH Level, L = LOW Level, X = Don't Care  
D0, D1...D7 = the level of the respective D input

## Logic Diagram



Absolute Maximum Ratings (Note 1)			Recommended Operating Conditions					
(Note 2)								
Supply Voltage ( $V_{CC}$ )	–0.5 to +7.0V				Min	Max	Units	
DC Input Voltage ( $V_{IN}$ )	–1.5 to $V_{CC}$ +1.5V		Supply Voltage ( $V_{CC}$ )	2	6	V		
DC Output Voltage ( $V_{OUT}$ )	–0.5 to $V_{CC}$ +0.5V		DC Input or Output Voltage ( $V_{IN}$ , $V_{OUT}$ )	0	$V_{CC}$	V		
Clamp Diode Current ( $I_{IK}$ , $I_{OK}$ )	±20 mA		Operating Temperature Range ( $T_A$ )	–40	+85	°C		
DC Output Current, per pin ( $I_{OUT}$ )	±25 mA							
DC $V_{CC}$ or GND Current, per pin ( $I_{CC}$ )	±50 mA							
Storage Temperature Range ( $T_{STG}$ )	–65°C to +150°C							
Power Dissipation ( $P_D$ ) (Note 3)	600 mW							
S.O. Package only	500 mW							
Lead Temperature ( $T_L$ ) (Soldering 10 seconds)	260°C							
			<p><b>Note 1:</b> Absolute Maximum Ratings are those values beyond which damage to the device may occur.</p> <p><b>Note 2:</b> Unless otherwise specified all voltages are referenced to ground.</p> <p><b>Note 3:</b> Power Dissipation temperature derating — plastic "N" package: –12 mW/°C from 65°C to 85°C.</p>					
DC Electrical Characteristics (Note 4)								
Symbol	Parameter	Conditions	$V_{CC}$	$T_A = 25^\circ C$		$T_A = -40$ to $85^\circ C$	$T_A = -55$ to $125^\circ C$	Units
				Typ		Guaranteed Limits		
$V_{IH}$	Minimum HIGH Level Input Voltage		2.0V	1.5	1.5	1.5	V	
			4.5V	3.15	3.15	3.15	V	
			6.0V	4.2	4.2	4.2	V	
$V_{IL}$	Maximum LOW Level Input Voltage		2.0V	0.5	0.5	0.5	V	
			4.5V	1.35	1.35	1.35	V	
			6.0V	1.8	1.8	1.8	V	
$V_{OH}$	Minimum HIGH Level Output Voltage $ I_{OUT}  \leq 20 \mu A$	$V_{IN} = V_{IH}$ or $V_{IL}$	2.0V	2.0	1.9	1.9	V	
			4.5V	4.5	4.4	4.4	V	
			6.0V	6.0	5.9	5.9	V	
		$V_{IN} = V_{IH}$ or $V_{IL}$ $ I_{OUT}  \leq 4.0$ mA	4.5V	4.2	3.98	3.84	3.7	V
		$ I_{OUT}  \leq 5.2$ mA	6.0V	5.7	5.48	5.34	5.2	V
		$V_{IN} = V_{IH}$ or $V_{IL}$ $ I_{OUT}  \leq 20 \mu A$	2.0V	0	0.1	0.1	0.1	V
$V_{OL}$	Maximum LOW Level Output Voltage		4.5V	0	0.1	0.1	V	
			6.0V	0	0.1	0.1	V	
			$V_{IN} = V_{IH}$ or $V_{IL}$ $ I_{OUT}  \leq 4.0$ mA	4.5V	0.2	0.26	0.33	0.4
	$ I_{OUT}  \leq 5.2$ mA	6.0V	0.2	0.26	0.33	0.4	V	
$I_{IN}$	Maximum Input Current	$V_{IN} = V_{CC}$ or GND	6.0V		±0.1	±1.0	±1.0	μA
$I_{CC}$	Maximum Quiescent Supply Current	$V_{IN} = V_{CC}$ or GND $ I_{OUT}  = 0 \mu A$	6.0V		8.0	80	160	μA
<p><b>Note 4:</b> For a power supply of 5V ±10% the worst case output voltages (<math>V_{OH}</math> and <math>V_{OL}</math>) occur for HC at 4.5V. Thus the 4.5V values should be used when designing with this supply. Worst case <math>V_{IH}</math> and <math>V_{IL}</math> occur at <math>V_{CC} = 5.5</math>V and 4.5V respectively. (The <math>V_{IH}</math> value at 5.5V is 3.85V.) The worst case leakage current (<math>I_{IN}</math>, <math>I_{CC}</math>, and <math>I_{OZ}</math>) occur for CMOS at the higher voltage and so the 6.0V values should be used.</p>								

## AC Electrical Characteristics

$V_{CC} = 5V$ ,  $T_A = 25^\circ C$ ,  $C_L = 15 \text{ pF}$ ,  $t_r = t_f = 6 \text{ ns}$

Symbol	Parameter	Conditions	Typ	Guaranteed Limit	Units
$t_{PHL}, t_{PLH}$	Maximum Propagation Delay A, B or C to Y		26	35	ns
$t_{PHL}, t_{PLH}$	Maximum Propagation Delay A, B or C to W		27	35	ns
$t_{PHL}, t_{PLH}$	Maximum Propagation Delay Any D to Y		22	29	ns
$t_{PHL}, t_{PLH}$	Maximum Propagation Delay any D to W		24	32	ns
$t_{PHL}, t_{PLH}$	Maximum Propagation Delay Strobe to Y		17	23	ns
$t_{PHL}, t_{PLH}$	Maximum Propagation Delay Strobe to W		16	21	ns



## AC Electrical Characteristics

$C_L = 50 \text{ pF}$ ,  $t_r = t_f = 6 \text{ ns}$  (unless otherwise specified)



Symbol	Parameter	Conditions	$V_{CC}$	$T_A = 25^\circ C$			Guaranteed Limits	Units
				Typ	$T_A = -40 \text{ to } 85^\circ C$	$T_A = -55 \text{ to } 125^\circ C$		
$t_{PHL}, t_{PLH}$	Maximum Propagation Delay A, B or C to Y		2.0V	90	205	256	300	ns
			4.5V	31	41	51	60	ns
			6.0V	26	35	44	51	ns
$t_{PHL}, t_{PLH}$	Maximum Propagation Delay A, B or C to W		2.0V	95	205	256	300	ns
			4.5V	32	41	51	60	ns
			6.0V	27	35	44	51	ns
$t_{PHL}, t_{PLH}$	Maximum Propagation Delay any D to Y		2.0V	70	195	244	283	ns
			4.5V	27	39	49	57	ns
			6.0V	23	33	41	48	ns
$t_{PHL}, t_{PLH}$	Maximum Propagation Delay any D to W		2.0V	75	185	231	268	ns
			4.5V	29	37	46	54	ns
			6.0V	25	32	40	46	ns
$t_{PHL}, t_{PLH}$	Maximum Propagation Delay Strobe to Y		2.0V	50	140	175	203	ns
			4.5V	21	28	35	41	ns
			6.0V	18	24	30	35	ns
$t_{PHL}, t_{PLH}$	Maximum Propagation Delay Strobe to W		2.0V	45	127	159	185	ns
			4.5V	20	25	32	37	ns
			6.0V	17	22	28	32	ns
$t_{TLH}, t_{THL}$	Maximum Output Rise and Fall Time		2.0V	30	75	95	110	ns
			4.5V	8	15	19	22	ns
			6.0V	7	13	16	19	ns
$C_{PD}$	Power Dissipation Capacitance (Note 5)	(per package)		110				pF
$C_{IN}$	Maximum Input Capacitance			5	10	10	10	pF

**Note 5:**  $C_{PD}$  determines the no load dynamic power consumption,  $P_D = C_{PD} V_{CC}^2 f + I_{CC} V_{CC}$ , and the no load dynamic current consumption,  $I_S = C_{PD} V_{CC} f + I_{CC}$ .


## **Physical Dimensions** inches (millimeters) unless otherwise noted



**16-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-012, 0.150" Narrow  
Package Number M16A**




**16-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide  
Package Number M16D**

**Physical Dimensions** inches (millimeters) unless otherwise noted (Continued)

16-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide  
Package Number MTC16

### Physical Dimensions

inches (millimeters) unless otherwise noted (Continued)



16-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300" Wide  
Package Number N16E

#### LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

[www.fairchildsemi.com](http://www.fairchildsemi.com)