



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




### Features

- Designed for VHF/UHF Amplifier Applications and High Output VHF Oscillators
- High Current Gain Bandwidth Product
- Ideal for Mixer and RF Amplifier Applications with collector currents in the 100 $\mu$ A - 30 mA Range
- **Lead, Halogen and Antimony Free, RoHS Compliant "Green" Device (Notes 3 and 4)**

### Mechanical Data

- Case: SOT-23
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020C
- Terminals: Solderable per MIL-STD-202, Method 208
- Terminal Connections: See Diagram
- Lead Free Plating (Matte Tin Finish annealed over Alloy 42 leadframe).
- Marking Information: See Page 3
- Ordering Information: See Page 3
- Weight: 0.008 grams (approximate)



| SOT-23               |       |       |
|----------------------|-------|-------|
| Dim                  | Min   | Max   |
| A                    | 0.37  | 0.51  |
| B                    | 1.20  | 1.40  |
| C                    | 2.30  | 2.50  |
| D                    | 0.89  | 1.03  |
| E                    | 0.45  | 0.60  |
| G                    | 1.78  | 2.05  |
| H                    | 2.80  | 3.00  |
| J                    | 0.013 | 0.10  |
| K                    | 0.903 | 1.10  |
| L                    | 0.45  | 0.61  |
| M                    | 0.085 | 0.180 |
| $\alpha$             | 0°    | 8°    |
| All Dimensions in mm |       |       |






### Maximum Ratings @ $T_A = 25^\circ\text{C}$ unless otherwise specified

| Characteristic                                   | Symbol          | Value       | Unit               |
|--|-----------------|-------------|--------------------|
| Collector-Base Voltage                           | $V_{CBO}$       | 40          | V                  |
| Collector-Emitter Voltage                        | $V_{CEO}$       | 40          | V                  |
| Emitter-Base Voltage                             | $V_{EBO}$       | 4.0         | V                  |
| Collector Current - Continuous (Note 1)          | $I_C$           | 50          | mA                 |
| Power Dissipation (Note 1)                       | $P_d$           | 300         | mW                 |
| Thermal Resistance, Junction to Ambient (Note 1) | $R_{\theta JA}$ | 417         | $^\circ\text{C/W}$ |
| Operating and Storage Temperature Range          | $T_j, T_{STG}$  | -55 to +150 | $^\circ\text{C}$   |

### Electrical Characteristics @ $T_A = 25^\circ\text{C}$ unless otherwise specified

| Characteristic                       | Symbol        | Min | Max  | Unit | Test Condition  |
|--------------------------------------|---------------|-----|------|------|---|
| <b>OFF CHARACTERISTICS (Note 2)</b>  |               |     |      |      |   |
| Collector-Emitter Breakdown Voltage  | $V_{(BR)CEO}$ | 40  | —    | V    | $I_C = 1\text{mA}, I_B = 0$                                 |
| Collector-Base Breakdown Voltage     | $V_{(BR)CBO}$ | 40  | —    | V    | $I_C = 100\mu\text{A}, I_E = 0$                             |
| Emitter-Base Breakdown Voltage       | $V_{(BR)EBO}$ | 4.0 | —    | V    | $I_E = 10\mu\text{A}, I_C = 0$                              |
| Collector Cutoff Current             | $I_{CBO}$     | —   | 100  | nA   | $V_{CB} = 30\text{V}, I_E = 0$                              |
| Emitter Cutoff Current               | $I_{EBO}$     | —   | 100  | nA   | $V_{EB} = 2\text{V}, I_C = 0$                               |
| <b>ON CHARACTERISTICS (Note 2)</b>   |               |     |      |      |   |
| DC Current Gain                      | $h_{FE}$      | 30  | —    | —    | $I_C = 8\text{mA}, V_{CE} = 10.0\text{V}$                   |
| Collector-Emitter Saturation Voltage | $V_{CE(SAT)}$ | —   | 0.5  | V    | $I_C = 4\text{mA}, I_B = 400\mu\text{A}$                    |
| Base-Emitter On Voltage              | $V_{BE(SAT)}$ | —   | 0.95 | V    | $I_C = 4\text{mA}, V_{CE} = 10.0\text{V}$                   |
| <b>SMALL SIGNAL CHARACTERISTICS</b>  |               |     |      |      |   |
| Current Gain-Bandwidth Product       | $f_T$         | 400 | —    | MHz  | $V_{CE} = 10\text{V}, f = 100\text{MHz}, I_C = 8\text{mA}$  |
| Collector-Base Capacitance           | $C_{CB}$      | —   | 0.7  | pF   | $V_{CB} = 10\text{V}, f = 1.0\text{MHz}, I_E = 0$           |
| Collector-Base Feedback Capacitance  | $C_{RB}$      | —   | 0.65 | pF   | $V_{CB} = 10\text{V}, f = 1.0\text{MHz}, I_E = 0$           |
| Collector-Base Time Constant         | $R_b C_c$     | —   | 9    | ps   | $I_C = 4\text{mA}, V_{CB} = 10\text{V}, f = 31.8\text{MHz}$ |

- Notes:
1. Device mounted on FR-4 PCB, 1 inch x 0.85 inch x 0.062 inch pad layout, as shown on Diodes Inc. suggested pad layout document AP02001, which can be found on our website at <http://www.diodes.com/datasheets/ap02001.pdf>.
  2. Short duration pulse test used to minimize self-heating effect.
  3. No purposefully added lead. Halogen and Antimony Free.
  4. Product manufactured with Data Code V9 (week 33, 2008) and newer are built with Green Molding Compound. Product manufactured prior to Date Code V9 are built with Non-Green Molding Compound and may contain Halogens or  $\text{Sb}_2\text{O}_3$  Fire Retardants.




## Ordering Information (Note 5)

| Device      | Packaging | Shipping         |
|-------------|-----------|------------------|
| MMBTH24-7-F | SOT-23    | 3000/Tape & Reel |

Notes: 5. For packaging details, go to our website at <http://www.diodes.com/datasheets/ap02007.pdf>.

## Marking Information



K3Z = Product Type Marking Code  
 YM = Date Code Marking  
 Y = Year ex: N = 2002  
 M = Month ex: 9 = September

### Date Code Key

| Year | 1998 | 1999 | 2000 | 2001 | 2002 | 2003 | 2004 | 2005 | 2006 | 2007 | 2008 | 2009 | 2010 | 2011 | 2012 |
|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| Code | J    | K    | L    | M    | N    | P    | R    | S    | T    | U    | V    | W    | X    | Y    | Z    |

| Month | Jan | Feb | Mar | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec |
|-------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| Code  | 1   | 2   | 3   | 4   | 5   | 6   | 7   | 8   | 9   | O   | N   | D   |

### IMPORTANT NOTICE

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Diodes Incorporated does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

### LIFE SUPPORT

Diodes Incorporated products are not authorized for use as critical components in life support devices or systems without the expressed written approval of the President of Diodes Incorporated.